

## Advanced LinCMOS™ RAIL-TO-RAIL OUTPUT WIDE-INPUT-VOLTAGE OPERATIONAL AMPLIFIERS

### FEATURES

- Qualified for Automotive Applications
- ESD Protection Exceeds 2000 V Per MIL-STD-883, Method 3015; Exceeds 200 V Using Machine Model (C = 200 pF, R = 0)
- Output Swing Includes Both Supply Rails
- Extended Common-Mode Input Voltage Range: 0 V to 4.25 V (Min) at 5-V Single Supply
- No Phase Inversion
- Low Noise: 16 nV/√Hz Typ at f = 1 kHz
- Low Input Offset Voltage: 950 μV Max at T<sub>A</sub> = 25°C (TLV244xA)
- Low Input Bias Current: 1 pA (Typ)
- 600-Ω Output Drive
- High-Gain Bandwidth: 1.8 MHz (Typ)
- Low Supply Current: 750 μA Per Channel (Typ)
- Macromodel Included


### DESCRIPTION

The TLV244x and TLV244xA are low-voltage operational amplifiers from Texas Instruments. The common-mode input voltage range of these devices has been extended over typical standard CMOS amplifiers, making them suitable for a wide range of applications. In addition, these devices do not phase invert when the common-mode input is driven to the supply rails. This satisfies most design requirements without paying a premium for rail-to-rail input performance. They also exhibit rail-to-rail output performance for increased dynamic range in single- or split-supply applications. This family is fully characterized at 3-V and 5-V supplies and is optimized for low-voltage operation. Both devices offer comparable ac performance while having lower noise, input offset voltage, and power dissipation than existing CMOS operational amplifiers. The TLV244x has increased output drive over previous rail-to-rail operational amplifiers and can drive 600-Ω loads for telecommunications applications.

The other members in the TLV244x family are the low-power, TLV243x, and micro-power, TLV2422, versions.

The TLV244x, exhibiting high input impedance and low noise, is excellent for small-signal conditioning for high-impedance sources, such as piezoelectric transducers. Because of the micropower dissipation levels and low-voltage operation, these devices work well in hand-held monitoring and remote-sensing applications. In addition, the rail-to-rail output feature with single- or split-supplies makes this family a great choice when interfacing with analog-to-digital converters (ADCs). For precision applications, the TLV244xA is available with a maximum input offset voltage of 950 μV.

If the design requires single operational amplifiers, see the TI TLV2211/21/31. This is a family of rail-to-rail output operational amplifiers in the SOT-23 package. Their small size and low power consumption make them ideal for high-density battery-powered equipment.



**Figure 1.**



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.



Advanced LinCMOS is a trademark of Texas Instruments.

PSpice, Parts are trademarks of MicroSim.


# ORDERING INFORMATION<sup>(1)</sup>

| $T_A$          | $V_{IO\max}$<br>AT 25 = C | PACKAGE <sup>(2)</sup> |            |              | ORDERABLE PART<br>NUMBER | TOP-SIDE MARKING |
|----------------|---------------------------|------------------------|------------|--------------|--------------------------|------------------|
| –40°C to 125°C | 950 $\mu$ V               | Dual                   | SOIC – D   | Reel of 2500 | TLV2442AQDRQ1            | 2442AQ           |
|                |                           |                        | TSSOP – PW | Reel of 2000 | TLV2442AQPWRQ1           | 2442AQ           |
|                | 2.5 mV                    | Dual                   | MSOP – DGK | Reel of 2500 | TLV2442QDGKRQ1           | OBR              |
|                |                           |                        | SOIC – D   | Reel of 2500 | TLV2442QDRQ1             | 2442Q1           |
|                |                           |                        | TSSOP – PW | Reel of 2000 | TLV2442QPWRQ1            | 2442Q1           |
|                | 950 $\mu$ V               | Quad                   | TSSOP – PW | Reel of 2000 | TLV2444AQPWRQ1           | 2444AQ           |

- (1) For the most current package and ordering information, see the Package Option Addendum at the end of this document, or see the TI web site at [www.ti.com](http://www.ti.com).
- (2) Package drawings, thermal data, and symbolization are available at [www.ti.com/packaging](http://www.ti.com/packaging).



# EQUIVALENT SCHEMATIC (EACH AMPLIFIER)



## ABSOLUTE MAXIMUM RATINGS<sup>(1)</sup>

over operating free-air temperature range (unless otherwise noted)

|                  |                                                                      |                              |
|------------------|----------------------------------------------------------------------|------------------------------|
| V <sub>DD</sub>  | Supply voltage <sup>(2)</sup>                                        | 12 V                         |
| V <sub>ID</sub>  | Differential input voltage <sup>(3)</sup>                            | ±V <sub>DD</sub>             |
| V <sub>I</sub>   | Input voltage (any input) <sup>(2)</sup>                             | −0.3 V to V <sub>DD</sub>    |
| I <sub>I</sub>   | Input current (any input)                                            | ±5 mA                        |
| I <sub>O</sub>   | Output current                                                       | ±50 mA                       |
|                  | Total current into V <sub>DD+</sub>                                  | ±50 mA                       |
|                  | Total current out of V <sub>DD−</sub>                                | ±50 mA                       |
|                  | Duration of short-circuit current at (or below) 25 °C <sup>(4)</sup> | Unlimited                    |
|                  | Continuous total dissipation                                         | See Dissipation Rating Table |
| T <sub>A</sub>   | Operating free-air temperature range                                 | −40°C to 125°C               |
| T <sub>stg</sub> | Storage temperature range                                            | −65°C to 150°C               |
|                  | Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds         | 260°C                        |

- (1) Stresses beyond those listed under *absolute maximum ratings* may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under *recommended operating conditions* is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) All voltage values, except differential voltages, are with respect to the midpoint between V<sub>DD+</sub> and V<sub>DD−</sub>.
- (3) Differential voltages are at IN+ with respect to IN−. Excessive current will flow if input is brought below V<sub>DD−</sub> − 0.3 V.
- (4) The output may be shorted to either supply. Temperature and/or supply voltages must be limited to ensure that the maximum dissipation rating is not exceeded.

## DISSIPATION RATINGS

| PACKAGE     | T <sub>A</sub> ≤ 25°C<br>POWER RATING | DERATING FACTOR<br>ABOVE T <sub>A</sub> = 25°C | T <sub>A</sub> = 70°C<br>POWER RATING | T <sub>A</sub> = 85°C<br>POWER RATING | T <sub>A</sub> = 125°C<br>POWER RATING |
|-------------|---------------------------------------|------------------------------------------------|---------------------------------------|---------------------------------------|----------------------------------------|
| D (8 pin)   | 725 mW                                | 5.8 mW/°C                                      | 464 mW                                | 377 mW                                | 145 mW                                 |
| DGK (8 pin) | 606 mW                                | 4.847 mW/°C                                    | 388 mW                                | 315 mW                                | 121 mW                                 |
| PW (8 pin)  | 525 mW                                | 4.2 mW/°C                                      | 336 mW                                | 273 mW                                | 105 mW                                 |
| PW (14 pin) | 720 mW                                | 5.6 mW/°C                                      | 634 mW                                | 547 mW                                | 317 mW                                 |

## RECOMMENDED OPERATING CONDITIONS

|                 |                                | MIN              | MAX                  | UNIT |
|-----------------|--------------------------------|------------------|----------------------|------|
| V <sub>DD</sub> | Supply voltage                 | 2.7              | 10                   | V    |
| V <sub>I</sub>  | Input voltage                  | V <sub>DD−</sub> | V <sub>DD+</sub> − 1 | V    |
| V <sub>IC</sub> | Common-mode input voltage      | V <sub>DD−</sub> | V <sub>DD+</sub> − 1 | V    |
| T <sub>A</sub>  | Operating free-air temperature | −40              | 125                  | °C   |

## ELECTRICAL CHARACTERISTICS

$V_{DD} = 3\text{ V}$ , at specified free-air temperature (unless otherwise noted)

| PARAMETER        |                                                                       | TEST CONDITIONS                                                                                    |                         | T <sub>A</sub> <sup>(1)</sup> | MIN  | TYP       | MAX          | UNIT  |
|------------------|-----------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|-------------------------|-------------------------------|------|-----------|--------------|-------|
| V <sub>IO</sub>  | Input offset voltage                                                  | V <sub>IC</sub> = 1.5 V, V <sub>O</sub> = 1.5 V, R <sub>S</sub> = 50 Ω                             | TLV244x                 | 25°C                          |      | 300       | 2000         | μV    |
|                  |                                                                       |                                                                                                    |                         | Full range                    |      | 2500      |              |       |
|                  |                                                                       |                                                                                                    | TLV244xA                | 25°C                          |      | 300       | 950          |       |
|                  |                                                                       |                                                                                                    |                         | Full range                    |      | 1600      |              |       |
| α <sub>VIO</sub> | Temperature coefficient of input offset voltage                       | V <sub>IC</sub> = 1.5 V, V <sub>O</sub> = 1.5 V, R <sub>S</sub> = 50 Ω                             |                         | 25°C to 85°C                  |      | 2         |              | μV/°C |
|                  | Input offset voltage long-term drift <sup>(2)</sup>                   | V <sub>IC</sub> = 1.5 V, V <sub>O</sub> = 1.5 V, R <sub>S</sub> = 50 Ω                             |                         | 25°C                          |      | 0.002     |              | μV/mo |
| I <sub>IO</sub>  | Input offset current                                                  | V <sub>IC</sub> = 1.5 V, V <sub>O</sub> = 1.5 V, R <sub>S</sub> = 50 Ω                             |                         | 25°C                          |      | 0.5       |              | pA    |
|                  |                                                                       |                                                                                                    |                         | Full range                    |      | 150       |              |       |
| I <sub>IB</sub>  | Input bias current                                                    | V <sub>IC</sub> = 1.5 V, V <sub>O</sub> = 1.5 V, R <sub>S</sub> = 50 Ω                             |                         | 25°C                          |      | 1         |              | pA    |
|                  |                                                                       |                                                                                                    |                         | Full range                    |      | 260       |              |       |
| V <sub>ICR</sub> | Common-mode input voltage range                                       | V <sub>IO</sub>   ≤ 8 mV, R <sub>S</sub> = 50 Ω                                                    |                         | 25°C                          |      | 0 to 2.25 | –0.25 to 2.5 | V     |
|                  |                                                                       |                                                                                                    |                         | Full range                    |      | 0.2 to 2  |              |       |
| V <sub>OH</sub>  | High-level output voltage                                             | I <sub>O</sub> = –100 μA                                                                           |                         | 25°C                          |      | 2.98      |              | V     |
|                  |                                                                       | I <sub>O</sub> = –3 mA                                                                             |                         | 25°C                          |      | 2.5       |              |       |
|                  |                                                                       |                                                                                                    |                         | Full range                    |      | 2.25      |              |       |
| V <sub>OL</sub>  | Low-level output voltage                                              | V <sub>IC</sub> = 1.5 V                                                                            | I <sub>O</sub> = 100 μA | 25°C                          |      | 0.02      |              | V     |
|                  |                                                                       |                                                                                                    | I <sub>O</sub> = 3 mA   | 25°C                          |      | 0.63      |              |       |
|                  |                                                                       |                                                                                                    |                         | Full range                    |      | 1         |              |       |
| A <sub>VD</sub>  | Large-signal differential voltage amplification                       | V <sub>O</sub> = 1 V to 2 V                                                                        | R <sub>L</sub> = 600 Ω  | 25°C                          |      | 0.7       | 1            | V/mV  |
|                  |                                                                       |                                                                                                    | R <sub>L</sub> = 1 MΩ   | Full range                    |      | 0.4       |              |       |
|                  |                                                                       |                                                                                                    |                         |                               | 25°C |           | 750          |       |
| r <sub>id</sub>  | Differential input resistance                                         |                                                                                                    |                         | 25°C                          |      | 1000      |              | GΩ    |
| r <sub>i</sub>   | Common-mode input resistance                                          |                                                                                                    |                         | 25°C                          |      | 1000      |              | GΩ    |
| c <sub>i</sub>   | Common-mode input capacitance                                         | f = 10 kHz                                                                                         |                         | 25°C                          |      | 8         |              | pF    |
| z <sub>o</sub>   | Closed-loop output impedance                                          | f = 1 MHz, A <sub>V</sub> = 10                                                                     |                         | 25°C                          |      | 130       |              | Ω     |
| CMRR             | Common-mode rejection ratio                                           | V <sub>IC</sub> = V <sub>ICR</sub> MIN, V <sub>O</sub> = V <sub>DD</sub> /2, R <sub>S</sub> = 50 Ω |                         | 25°C                          |      | 65        | 75           | dB    |
|                  |                                                                       |                                                                                                    |                         | Full range                    |      | 50        |              |       |
| k <sub>SVR</sub> | Supply-voltage rejection ratio (ΔV <sub>DD</sub> ±/ΔV <sub>IO</sub> ) | V <sub>DD</sub> = 2.7 V to 8 V, V <sub>IC</sub> = V <sub>DD</sub> /2, No load                      |                         | 25°C                          |      | 80        | 95           | dB    |
|                  |                                                                       |                                                                                                    |                         | Full range                    |      | 80        |              |       |
| I <sub>DD</sub>  | Supply current (per channel)                                          | V <sub>O</sub> = 1.5 V, No load                                                                    |                         | 25°C                          |      | 725       | 1100         | μA    |
|                  |                                                                       |                                                                                                    |                         | Full range                    |      | 1100      |              |       |

(1) Full range is –40°C to 125°C.

(2) Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at  $T_A = 150^\circ\text{C}$  extrapolated to  $T_A = 25^\circ\text{C}$  using the Arrhenius equation and assuming an activation energy of 0.96 eV.

## OPERATING CHARACTERISTICS

$V_{DD} = 3\text{ V}$ , at specified free-air temperature (unless otherwise noted)

| PARAMETER          |                                             | TEST CONDITIONS                                                                                    |                      | T <sub>A</sub> <sup>(1)</sup> | MIN  | TYP  | MAX | UNIT   |
|--------------------|---------------------------------------------|----------------------------------------------------------------------------------------------------|----------------------|-------------------------------|------|------|-----|--------|
| SR                 | Slew rate at unity gain                     | V <sub>O</sub> = 1 V to 2 V, R <sub>L</sub> = 600 Ω,<br>C <sub>L</sub> = 100 pF                    |                      | 25°C                          | 0.65 | 1.3  |     | V/μs   |
|                    |                                             |                                                                                                    |                      | Full range                    | 0.4  |      |     |        |
| V <sub>n</sub>     | Equivalent input noise voltage              | f = 10 Hz                                                                                          |                      | 25°C                          |      | 170  |     | nV/√Hz |
|                    |                                             | f = 1 kHz                                                                                          |                      |                               |      | 18   |     |        |
| V <sub>n(PP)</sub> | Peak-to-peak equivalent input noise voltage | f = 0.1 Hz to 1 Hz                                                                                 |                      | 25°C                          |      | 2.6  |     | μV     |
|                    |                                             | f = 0.1 Hz to 10 Hz                                                                                |                      |                               |      | 5.1  |     |        |
| I <sub>n</sub>     | Equivalent input noise current              |                                                                                                    |                      | 25°C                          |      | 0.6  |     | fA/√Hz |
| THD+N              | Total harmonic distortion plus noise        | V <sub>O</sub> = 0.5 V to 2.5 V,<br>R <sub>L</sub> = 600 Ω, f = 1 kHz                              | A <sub>V</sub> = 1   | 25°C                          |      | 0.08 |     | %      |
|                    |                                             |                                                                                                    | A <sub>V</sub> = 10  |                               |      | 0.3  |     |        |
|                    |                                             |                                                                                                    | A <sub>V</sub> = 100 |                               |      | 2    |     |        |
|                    | Gain-bandwidth product                      | f = 10 kHz, R <sub>L</sub> = 600 Ω, C <sub>L</sub> = 100 pF                                        |                      | 25°C                          |      | 1.75 |     | MHz    |
| BOM                | Maximum output-swing bandwidth              | V <sub>O(PP)</sub> = 1 V, R <sub>L</sub> = 600 Ω, A <sub>V</sub> = 1,<br>C <sub>L</sub> = 100 pF   |                      | 25°C                          |      | 0.9  |     | MHz    |
| t <sub>s</sub>     | Settling time                               | A <sub>V</sub> = −1,<br>Step = −2.3 V to 2.3 V,<br>R <sub>L</sub> = 600 Ω, C <sub>L</sub> = 100 pF | To 0.1%              | 25°C                          |      | 1.5  |     | μs     |
|                    |                                             |                                                                                                    | To 0.01%             |                               |      | 3.2  |     |        |
| φ <sub>m</sub>     | Phase margin at unity gain                  | R <sub>L</sub> = 600 Ω, C <sub>L</sub> = 100 pF                                                    |                      | 25°C                          |      | 65   |     | °      |
|                    | Gain margin                                 | R <sub>L</sub> = 600 Ω, C <sub>L</sub> = 100 pF                                                    |                      | 25°C                          |      | 9    |     | dB     |

(1) Full range is  $-40^\circ\text{C}$  to  $125^\circ\text{C}$ .

## ELECTRICAL CHARACTERISTICS

 $V_{DD} = 5\text{ V}$ , at specified free-air temperature (unless otherwise noted)

| PARAMETER                                                                  | TEST CONDITIONS                                                                   | $T_A^{(1)}$                    | MIN        | TYP          | MAX  | UNIT                         |
|----------------------------------------------------------------------------|-----------------------------------------------------------------------------------|--------------------------------|------------|--------------|------|------------------------------|
| $V_{IO}$ Input offset voltage                                              | $V_{DD\pm} = \pm 2.5\text{ V}$ , $V_{IC} = 0$ ,<br>$V_O = 0$ , $R_S = 50\ \Omega$ | TLV244x                        | 25°C       | 300          | 2000 | $\mu\text{V}$                |
|                                                                            |                                                                                   | TLV244xA                       | Full range |              | 2500 |                              |
|                                                                            |                                                                                   |                                | 25°C       | 300          | 950  |                              |
|                                                                            |                                                                                   |                                | Full range |              | 1600 |                              |
| $\alpha_{VIO}$ Temperature coefficient of input offset voltage             | $V_{DD\pm} = \pm 2.5\text{ V}$ , $V_{IC} = 0$ , $V_O = 0$ , $R_S = 50\ \Omega$    | 25°C to 85°C                   |            | 2            |      | $\mu\text{V}/^\circ\text{C}$ |
| Input offset voltage long-term drift <sup>(2)</sup>                        | $V_{DD\pm} = \pm 2.5\text{ V}$ , $V_{IC} = 0$ , $V_O = 0$ , $R_S = 50\ \Omega$    | 25°C                           |            | 0.002        |      | $\mu\text{V}/\text{mo}$      |
| $I_{IO}$ Input offset current                                              | $V_{DD\pm} = \pm 2.5\text{ V}$ , $V_{IC} = 0$ , $V_O = 0$ , $R_S = 50\ \Omega$    | 25°C                           |            | 0.5          |      | pA                           |
|                                                                            |                                                                                   | Full range                     |            |              | 150  |                              |
| $I_{IB}$ Input bias current                                                | $V_{DD\pm} = \pm 2.5\text{ V}$ , $V_{IC} = 0$ , $V_O = 0$ , $R_S = 50\ \Omega$    | 25°C                           |            | 1            |      | pA                           |
|                                                                            |                                                                                   | Full range                     |            |              | 260  |                              |
| $V_{ICR}$ Common-mode input voltage range                                  | $ V_{IO}  \leq 5\text{ mV}$ , $R_S = 50\ \Omega$                                  | 25°C                           | 0 to 4.25  | –0.25 to 4.5 |      | V                            |
|                                                                            |                                                                                   | Full range                     | 0 to 4     |              |      |                              |
| $V_{OH}$ High-level output voltage                                         | $I_{OH} = -100\ \mu\text{A}$<br>$I_{OH} = -5\text{ mA}$                           | 25°C                           |            | 4.97         |      | V                            |
|                                                                            |                                                                                   | 25°C                           | 4          | 4.35         |      |                              |
|                                                                            |                                                                                   | Full range                     | 4          |              |      |                              |
| $V_{OL}$ Low-level output voltage                                          | $V_{IC} = 2.5\text{ V}$                                                           | $I_{OL} = 100\ \mu\text{A}$    | 25°C       |              | 0.01 | V                            |
|                                                                            |                                                                                   | $I_{OL} = 5\text{ mA}$         | 25°C       |              | 0.8  |                              |
|                                                                            |                                                                                   |                                | Full range |              | 1.25 |                              |
| $A_{VD}$ Large-signal differential voltage amplification                   | $V_{IC} = 2.5\text{ V}$ ,<br>$V_O = 1\text{ V to }4\text{ V}$                     | $R_L = 600\ \Omega^{(3)}$      | 25°C       | 0.9          | 1.3  | V/mV                         |
|                                                                            |                                                                                   |                                | Full range | 0.5          |      |                              |
|                                                                            |                                                                                   | $R_L = 1\text{ M}\Omega^{(3)}$ | 25°C       |              | 950  |                              |
| $r_{id}$ Differential input resistance                                     |                                                                                   | 25°C                           |            | 1000         |      | G $\Omega$                   |
| $r_i$ Common-mode input resistance                                         |                                                                                   | 25°C                           |            | 1000         |      | G $\Omega$                   |
| $c_i$ Common-mode input capacitance                                        | $f = 10\text{ kHz}$                                                               | 25°C                           |            | 8            |      | pF                           |
| $z_o$ Closed-loop output impedance                                         | $f = 1\text{ MHz}$ , $A_V = 10$                                                   | 25°C                           |            | 140          |      | $\Omega$                     |
| CMRR Common-mode rejection ratio                                           | $V_{IC} = V_{ICR}\text{ MIN}$ , $V_O = V_{DD}/2$ , $R_S = 50\ \Omega$             | 25°C                           | 70         | 75           |      | dB                           |
|                                                                            |                                                                                   | Full range                     | 70         |              |      |                              |
| $k_{SVR}$ Supply-voltage rejection ratio ( $\Delta V_{DD}/\Delta V_{IO}$ ) | $V_{DD} = 4.4\text{ V to }8\text{ V}$ , $V_{IC} = V_{DD}/2$ , No load             | 25°C                           | 80         | 95           |      | dB                           |
|                                                                            |                                                                                   | Full range                     | 80         |              |      |                              |
| $I_{DD}$ Supply current (per channel)                                      | $V_O = 2.5\text{ V}$ , No load                                                    | 25°C                           |            | 750          | 1100 | $\mu\text{A}$                |
|                                                                            |                                                                                   | Full range                     |            |              | 1100 |                              |

(1) Full range is –40°C to 125°C.

(2) Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at  $T_A = 150^\circ\text{C}$  extrapolated to  $T_A = 25^\circ\text{C}$  using the Arrhenius equation and assuming an activation energy of 0.96 eV.

(3) Referenced to 2.5 V

## OPERATING CHARACTERISTICS

$V_{DD} = 5\text{ V}$ , at specified free-air temperature (unless otherwise noted)

| PARAMETER              |                                             | TEST CONDITIONS                                                                                                                      |                      | T <sub>A</sub> <sup>(1)</sup> | MIN   | TYP | MAX | UNIT   |
|------------------------|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------|-------|-----|-----|--------|
| SR                     | Slew rate at unity gain                     | V <sub>O</sub> = 0.5 V to 2.5 V, R <sub>L</sub> = 600 Ω <sup>(2)</sup> ,<br>C <sub>L</sub> = 100 pF <sup>(2)</sup>                   |                      | 25°C                          | 0.75  | 1.4 |     | V/μs   |
|                        |                                             |                                                                                                                                      |                      | Full range                    | 0.5   |     |     |        |
| V <sub>n</sub>         | Equivalent input noise voltage              | f = 10 Hz                                                                                                                            |                      | 25°C                          | 130   |     |     | nV/√Hz |
|                        |                                             | f = 1 kHz                                                                                                                            |                      |                               | 16    |     |     |        |
| V <sub>n(PP)</sub>     | Peak-to-peak equivalent input noise voltage | f = 0.1 Hz to 1 Hz                                                                                                                   |                      | 25°C                          | 1.8   |     |     | μV     |
|                        |                                             | f = 0.1 Hz to 10 Hz                                                                                                                  |                      |                               | 3.6   |     |     |        |
| I <sub>n</sub>         | Equivalent input noise current              |                                                                                                                                      |                      | 25°C                          | 0.6   |     |     | fA/√Hz |
| THD+N                  | Total harmonic distortion plus noise        | V <sub>O</sub> = 1.5 V to 3.5V,<br>f = 1 kHz, R <sub>L</sub> = 600 Ω <sup>(2)</sup>                                                  | A <sub>V</sub> = 1   | 25°C                          | 0.017 |     |     | %      |
|                        |                                             |                                                                                                                                      | A <sub>V</sub> = 10  |                               | 0.17  |     |     |        |
|                        |                                             |                                                                                                                                      | A <sub>V</sub> = 100 |                               | 1.5   |     |     |        |
| Gain-bandwidth product |                                             | f = 10 kHz, R <sub>L</sub> = 600 Ω <sup>(2)</sup> ,<br>C <sub>L</sub> = 100 pF <sup>(2)</sup>                                        |                      | 25°C                          | 1.81  |     |     | MHz    |
| BOM                    | Maximum output-swing bandwidth              | V <sub>O(PP)</sub> = 2 V, A <sub>V</sub> = 1, R <sub>L</sub> = 600 Ω <sup>(2)</sup> ,<br>C <sub>L</sub> = 100 pF <sup>(2)</sup>      |                      | 25°C                          | 0.5   |     |     | MHz    |
| t <sub>s</sub>         | Settling time                               | A <sub>V</sub> = −1,<br>Step = −0.5 V to 2.5 V,<br>R <sub>L</sub> = 600 Ω <sup>(2)</sup> ,<br>C <sub>L</sub> = 100 pF <sup>(2)</sup> | To 0.1%              | 25°C                          | 1.5   |     |     | μs     |
|                        |                                             |                                                                                                                                      | To 0.01%             |                               | 2.6   |     |     |        |
| φ <sub>m</sub>         | Phase margin at unity gain                  | R <sub>L</sub> = 600 Ω <sup>(2)</sup> , C <sub>L</sub> = 100 pF <sup>(2)</sup>                                                       |                      | 25°C                          | 68    |     |     | °      |
| Gain margin            |                                             | R <sub>L</sub> = 600 Ω <sup>(2)</sup> , C <sub>L</sub> = 100 pF <sup>(2)</sup>                                                       |                      | 25°C                          | 8     |     |     | dB     |

(1) Full range is  $-40^\circ\text{C}$  to  $125^\circ\text{C}$ .

(2) Referenced to 2.5 V

## TYPICAL CHARACTERISTICS

Table of Graphs<sup>(1)</sup>

|                |                                                                  |                               | FIGURE |
|----------------|------------------------------------------------------------------|-------------------------------|--------|
| $V_{IO}$       | Input offset voltage                                             | Distribution                  | 2, 3   |
|                |                                                                  | vs Common-mode input voltage  | 4, 5   |
| $\alpha_{VIO}$ | Input offset voltage temperature coefficient                     | Distribution                  | 6, 7   |
| $I_B/I_{IO}$   | Input bias and input offset currents                             | vs Free-air temperature       | 8      |
| $V_{OH}$       | High-level output voltage                                        | vs High-level output current  | 9, 10  |
| $V_{OL}$       | Low-level output voltage                                         | vs Low-level output current   | 11, 12 |
| $V_{O(PP)}$    | Maximum peak-to-peak output voltage                              | vs Frequency                  | 13     |
| $I_{OS}$       | Short-circuit output current                                     | vs Supply voltage             | 14     |
|                |                                                                  | vs Free-air temperature       | 15     |
| $V_O$          | Output voltage                                                   | vs Differential input voltage | 16, 17 |
| $A_{VD}$       | Differential voltage amplification                               | vs Load resistance            | 18     |
|                | Large-signal differential voltage amplification and phase margin | vs Frequency                  | 19, 20 |
|                | Large-signal differential voltage amplification                  | vs Free-air temperature       | 21, 22 |
| $z_o$          | Output impedance                                                 | vs Frequency                  | 23, 24 |
| CMRR           | Common-mode rejection ratio                                      | vs Frequency                  | 25     |
|                |                                                                  | vs Free-air temperature       | 26     |
| $k_{SVR}$      | Supply-voltage rejection ratio                                   | vs Frequency                  | 27, 28 |
|                |                                                                  | vs Free-air temperature       | 29     |
| $I_{DD}$       | Supply current                                                   | vs Supply voltage             | 30     |
| SR             | Slew rate                                                        | vs Load capacitance           | 31     |
|                |                                                                  | vs Free-air temperature       | 32     |
| $V_O$          | Inverting large-signal pulse response                            |                               | 33, 34 |
|                | Voltage-follower large-signal pulse response                     |                               | 35, 36 |
|                | Inverting small-signal pulse response                            |                               | 37, 38 |
|                | Voltage-follower small-signal pulse response                     |                               | 39, 40 |
| $V_n$          | Equivalent input noise voltage                                   | vs Frequency                  | 41, 42 |
|                | Noise voltage                                                    | Over a 10-second period       | 43     |
| THD + N        | Total harmonic distortion plus noise                             | vs Frequency                  | 44, 45 |
|                |                                                                  | vs Free-air temperature       | 46     |
|                |                                                                  | vs Supply voltage             | 47     |
| $\phi_m$       | Phase margin                                                     | vs Frequency                  | 19, 20 |
|                |                                                                  | vs Load capacitance           | 48     |
|                |                                                                  | vs Load capacitance           | 49     |
| $B_1$          | Unity-gain bandwidth                                             | vs Load capacitance           | 50     |

(1) For all graphs where  $V_{DD} = 5\text{ V}$ , all loads are referenced to 2.5 V.

**DISTRIBUTION OF TLV2442  
INPUT OFFSET VOLTAGE**




Figure 2.

**INPUT OFFSET VOLTAGE**

**VS**

**COMMON-MODE INPUT VOLTAGE**




Figure 4.

**DISTRIBUTION OF TLV2442  
INPUT OFFSET VOLTAGE**




Figure 3.

**INPUT OFFSET VOLTAGE**

**VS**

**COMMON-MODE INPUT VOLTAGE**




Figure 5.




Figure 6.




Figure 7.




Figure 8.












Figure 9.








Figure 18.  
**LARGE-SIGNAL DIFFERENTIAL VOLTAGE  
AMPLIFICATION AND PHASE MARGIN  
VS  
FREQUENCY**




Figure 19.

LARGE-SIGNAL DIFFERENTIAL VOLTAGE  
AMPLIFICATION AND PHASE MARGIN  
vs  
FREQUENCY




Figure 20.

LARGE-SIGNAL DIFFERENTIAL  
VOLTAGE AMPLIFICATION  
vs  
FREE-AIR TEMPERATURE




Figure 21.

LARGE-SIGNAL DIFFERENTIAL  
VOLTAGE AMPLIFICATION  
vs  
FREE-AIR TEMPERATURE








Figure 22.






Figure 27.




Figure 28.




Figure 29.




Figure 30.




Figure 31.




Figure 32.




Figure 33.




Figure 34.




Figure 35.




Figure 36.




Figure 37.




Figure 38.




Figure 39.




Figure 40.




Figure 41.




Figure 42.




Figure 43.




Figure 44.




Figure 45.








Figure 46.




## APPLICATION INFORMATION

### macromodel information

Macromodel information provided was derived using PSpice™ Parts™ model generation software. The Boyle macromodel<sup>(2)</sup> and subcircuit in Figure 51 were generated using the TLV244x typical electrical and operating characteristics at  $T_A = 25^\circ\text{C}$ . Using this information, output simulations of the following key parameters can be generated to a tolerance of 20% (in most cases):

(2) G. R. Boyle, B. M. Cohn, D. O. Pederson, and J. E. Solomon, "Macromodeling of Integrated Circuit Operational Amplifiers," *IEEE Journal of Solid-State Circuits*, SC-9, 353 (1974).

- Maximum positive output voltage swing
- Maximum negative output voltage swing
- Slew rate
- Quiescent power dissipation
- Input bias current
- Open-loop voltage amplification
- Unity gain frequency
- Common-mode rejection ratio
- Phase margin
- DC output resistance
- AC output resistance
- Short-circuit output current limit



```
.SUBCKT TLV2442 1 2 3 4 5
C1      11      12      14E-12
C2      6       7       60.00E-12
DC      5       53      DX
DE      54      5       DX
DLP     90      91      DX
DLN     92      90      DX
DP      4       3       DX
EGND    99      0       POLY (2) (3,0) (4,) 0 .5 .5
FB      7       99      POLY (5) VB VC VE VLP VLN 0
+ 984.9E3 -1E6 1E6 1E6 -1E6
GA      6       0       11      12 377.0E-6
GCM     0       6       10      99 134E-9
ISS     3       10      DC 216.0E-6
HLIM    90      0       VLIM 1K
J1      11      2       10 JX
J2      12      1       10 JX
R2      6       9       100.OE3
```

```
RD1     60      11      2.653E3
RD2     60      12      2.653E3
R01     8       5       50
R02     7       99      50
RP      3       4       4.310E3
RSS     10      99      925.9E3
VAD     60      4       -.5
VB      9       0       DC 0
VC      3       53      DC .78
VE      54      4       DC .78
VLIM    7       8       DC 0
VLP     91      0       DC 1.9
VLN     0       92      DC 9.4
.MODEL DX D (IS=800.0E-18)
.MODEL JX PJF (IS=1.500E-12BETA=1.316E-3
+ VTO=-.270)
.ENDS
```

Figure 51. Boyle Macromodel and Subcircuit

## PACKAGING INFORMATION

| Orderable Device | Status<br>(1) | Package Type | Package<br>Drawing | Pins | Package<br>Qty | Eco Plan<br>(2) | Lead finish/<br>Ball material<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5) | Samples                 |
|------------------|---------------|--------------|--------------------|------|----------------|-----------------|--------------------------------------|----------------------|--------------|-------------------------|-------------------------|
| TLV2442AQDRG4Q1  | ACTIVE        | SOIC         | D                  | 8    | 2500           | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | 2442AQ                  | <a href="#">Samples</a> |
| TLV2442AQDRQ1    | ACTIVE        | SOIC         | D                  | 8    | 2500           | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | 2442AQ                  | <a href="#">Samples</a> |
| TLV2442QDGKRQ1   | ACTIVE        | VSSOP        | DGK                | 8    | 2500           | RoHS & Green    | NIPDAU   NIPDAUAG                    | Level-2-260C-1 YEAR  | -40 to 125   | OBR                     | <a href="#">Samples</a> |
| TLV2442QPWRG4Q1  | ACTIVE        | TSSOP        | PW                 | 8    | 2000           | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | 2442Q1                  | <a href="#">Samples</a> |

<sup>(1)</sup> The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSELETE:** TI has discontinued the production of the device.

<sup>(2)</sup> **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

**RoHS Exempt:** TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

**Green:** TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

<sup>(3)</sup> MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

<sup>(4)</sup> There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

<sup>(5)</sup> Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "-" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

<sup>(6)</sup> Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and

continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**OTHER QUALIFIED VERSIONS OF TLV2442-Q1, TLV2442A-Q1 :**

- Catalog : [TLV2442](#), [TLV2442A](#)
- Military : [TLV2442M](#), [TLV2442AM](#)

**NOTE: Qualified Version Definitions:**

- Catalog - TI's standard catalog product
- Military - QML certified for Military and Defense Applications

## TAPE AND REEL INFORMATION



\*All dimensions are nominal

| Device          | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|-----------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| TLV2442QPWRG4Q1 | TSSOP        | PW              | 8    | 2000 | 330.0              | 12.4               | 7.0     | 3.6     | 1.6     | 8.0     | 12.0   | Q1            |

## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal

| Device          | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|-----------------|--------------|-----------------|------|------|-------------|------------|-------------|
| TLV2442QPWRG4Q1 | TSSOP        | PW              | 8    | 2000 | 367.0       | 367.0      | 35.0        |



## PACKAGE OUTLINE

**SOIC - 1.75 mm max height**

SMALL OUTLINE INTEGRATED CIRCUIT



1. Linear dimensions are in inches [millimeters]. Dimensions in parenthesis are for reference only. Controlling dimensions are in inches. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed .006 [0.15] per side.
4. This dimension does not include interlead flash.
5. Reference JEDEC registration MS-012, variation AA.

**D0008A**

**SOIC - 1.75 mm max height**

## SMALL OUTLINE INTEGRATED CIRCUIT



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE:8X



## SOLDER MASK DETAILS

4214825/C 02/2019

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.

7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

D0008A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



SOLDER PASTE EXAMPLE  
BASED ON .005 INCH [0.125 MM] THICK STENCIL  
SCALE:8X

4214825/C 02/2019

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

DGK (S-PDSO-G8)


PLASTIC SMALL-OUTLINE PACKAGE



4073329/E 05/06

DGK (S-PDSO-G8)

PLASTIC SMALL OUTLINE PACKAGE



- NOTES:
- All linear dimensions are in millimeters.
  - This drawing is subject to change without notice.
  - Publication IPC-7351 is recommended for alternate designs.
  - Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
  - Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.




# EXAMPLE BOARD LAYOUT


PW0008A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



LAND PATTERN EXAMPLE  
SCALE:10X



SOLDER MASK DETAILS  
NOT TO SCALE

4221848/A 02/2015

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

PW0008A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:10X

4221848/A 02/2015

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale (<https://www.ti.com/legal/termsofsale.html>) or other applicable terms available either on [ti.com](https://www.ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2021, Texas Instruments Incorporated