

## LM2903-Q1 汽车类双路差动比较器

### 1 特性

- 符合汽车应用 标准
- 具有符合 AEC-Q100 标准的下列结果：
  - 器件温度 0 级：-40°C 至 150° 的环境运行温度范围 (LM2903E-Q1)
  - 器件温度 1 级：-40°C 至 125°C 的环境运行温度范围 (LM2903-Q1)
  - 器件 HBM ESD 分类等级 H1C
  - 器件 CDM ESD 分类等级 C4B
- ESD 保护超过 1000V（根据 MIL-STD-883 方法 3015）；超过 100V（使用机器放电模型，C = 200pF，R = 0Ω）
- 单电源或双电源
- 独立于电源电压的低漏极电源电流：每个比较器 0.4mA（典型值）
- 低输入偏置电流：25nA（典型值）
- 低输入失调电流：5nA（典型值）
- 低输入失调电压：2mV（典型值）
- 共模输入电压范围包括接地
- 差动输入电压范围等于最大额定电源电压 ±36V
- 低输出饱和电压
- 输出与 TTL、MOS 和 CMOS 兼容

### 2 应用

- 汽车
  - HEV/EV 和动力传动
  - 信息娱乐系统与仪表组
  - 车身控制模块
- 工业
- 电源监控
- 振荡器
- 峰值检测器
- 逻辑电压转换

### 3 说明

该器件包含两个独立的电压比较器，这些比较器可在宽电压范围内由单电源供电运行。如果两个电源之间的电压差在 2V 至 36V 的范围之内且 VCC 比输入共模电压至少高 +1.5V 以上，那么它们也可以由双电源供电运行。漏极电流不受电源电压的影响。可将输出连接到其它集电极开路输出，以实现有线 AND 关联。

LM2903-Q1 符合 AEC-Q100 1 级温度范围（-40°C 至 +125°C）标准。LM2903E-Q1 符合 AEC-Q100 0 级温度范围（-40°C 至 +150°C）标准。

器件信息<sup>(1)</sup>

| 器件型号       | 封装        | 封装尺寸（标称值）       |
|------------|-----------|-----------------|
| LM2903-Q1  | VSSOP (8) | 3.00mm × 3.00mm |
|            | SOIC (8)  | 4.90mm × 3.91mm |
|            | TSSOP (8) | 3.00mm × 4.40mm |
| LM2903E-Q1 | TSSOP (8) | 3.00mm × 4.40mm |

(1) 如需了解所有可用封装，请参阅产品说明书末尾的可订购产品附录。

简化原理图



## 目录


|          |                                                    |          |           |                                             |           |
|----------|----------------------------------------------------|----------|-----------|---------------------------------------------|-----------|
| <b>1</b> | <b>特性</b> .....                                    | <b>1</b> | 7.3       | Feature Description.....                    | 7         |
| <b>2</b> | <b>应用</b> .....                                    | <b>1</b> | 7.4       | Device Functional Modes.....                | 7         |
| <b>3</b> | <b>说明</b> .....                                    | <b>1</b> | <b>8</b>  | <b>Application and Implementation</b> ..... | <b>8</b>  |
| <b>4</b> | <b>修订历史记录</b> .....                                | <b>2</b> | 8.1       | Application Information.....                | 8         |
| <b>5</b> | <b>Pin Configuration and Functions</b> .....       | <b>3</b> | 8.2       | Typical Application .....                   | 8         |
| <b>6</b> | <b>Specifications</b> .....                        | <b>3</b> | <b>9</b>  | <b>Power Supply Recommendations</b> .....   | <b>10</b> |
| 6.1      | Absolute Maximum Ratings .....                     | 3        | <b>10</b> | <b>Layout</b> .....                         | <b>10</b> |
| 6.2      | Handling Ratings.....                              | 4        | 10.1      | Layout Guidelines .....                     | 10        |
| 6.3      | Recommended Operating Conditions, LM2903-Q1..      | 4        | 10.2      | Layout Example .....                        | 10        |
| 6.4      | Recommended Operating Conditions, LM2903E-Q1 ..... | 4        | <b>11</b> | <b>器件和文档支持</b> .....                        | <b>11</b> |
| 6.5      | Thermal Information .....                          | 4        | 11.1      | 相关链接.....                                   | 11        |
| 6.6      | Electrical Characteristics.....                    | 5        | 11.2      | 接收文档更新通知 .....                              | 11        |
| 6.7      | Switching Characteristics .....                    | 5        | 11.3      | 社区资源.....                                   | 11        |
| 6.8      | Typical Characteristics .....                      | 6        | 11.4      | 商标.....                                     | 11        |
| <b>7</b> | <b>Detailed Description</b> .....                  | <b>7</b> | 11.5      | 静电放电警告.....                                 | 11        |
| 7.1      | Overview .....                                     | 7        | 11.6      | 术语表 .....                                   | 11        |
| 7.2      | Functional Block Diagram .....                     | 7        | <b>12</b> | <b>机械、封装和可订购信息</b> .....                    | <b>11</b> |

## 4 修订历史记录

| Changes from Revision F (May 2018) to Revision G   |                                                             | Page |
|----------------------------------------------------|-------------------------------------------------------------|------|
| •                                                  | 已更改 previous Q1 graphs to match new format .....            | 6    |
| •                                                  | 已添加 LM2903E-Q1 specific graphs .....                        | 6    |
| Changes from Revision E (June 2014) to Revision F  |                                                             | Page |
| •                                                  | Added Pin Functions table. ....                             | 3    |
| •                                                  | Changed Thermal Information Table .....                     | 4    |
| Changes from Revision D (April 2008) to Revision E |                                                             | Page |
| •                                                  | 在 特性中添加了 AEC-Q100 信息。 .....                                 | 1    |
| •                                                  | 已添加 应用中添加了 AEC-Q100 信息。 .....                               | 1    |
| •                                                  | 已添加 器件信息表。 .....                                            | 1    |
| •                                                  | Added Handling Ratings table. ....                          | 4    |
| •                                                  | Added T <sub>j</sub> and ESD ratings to Abs Max table. .... | 4    |
| •                                                  | Updated Recommended Operating Conditions table. ....        | 4    |
| •                                                  | Added Thermal Information table. ....                       | 4    |
| •                                                  | Updated Electrical Characteristics table. ....              | 5    |

## 5 Pin Configuration and Functions

**D, DGK OR PW PACKAGE**  
Top View



**Pin Functions**

| PIN             |     | I/O    | DESCRIPTION                       |
|-----------------|-----|--------|-----------------------------------|
| NAME            | NO. |        |                                   |
| 1OUT            | 1   | Output | Comparator 1's output pin         |
| 1IN-            | 2   | Input  | Comparator 1's negative input pin |
| 1IN+            | 3   | Input  | Comparator 1's positive input pin |
| GND             | 4   | Input  | Ground                            |
| 2IN+            | 5   | Input  | Comparator 2's positive input pin |
| 2IN-            | 6   | Input  | Comparator 2's negative input pin |
| 2OUT            | 7   | Output | Comparator 2's output pin         |
| V <sub>CC</sub> | 8   | Input  | Supply Pin                        |

## 6 Specifications

### 6.1 Absolute Maximum Ratings<sup>(1)</sup>

over operating free-air temperature range (unless otherwise noted)

|                                                                | MIN  | MAX       | UNIT |
|----------------------------------------------------------------|------|-----------|------|
| V <sub>CC</sub> Supply voltage <sup>(2)</sup>                  |      | 36        | V    |
| V <sub>CC</sub> Supply voltage, LM2903E-Q1 Only <sup>(2)</sup> |      | 32        | V    |
| V <sub>ID</sub> Differential input voltage <sup>(3)</sup>      | -36  | 36        | V    |
| V <sub>I</sub> Input voltage range (either input)              | -0.3 | 36        | V    |
| V <sub>O</sub> Output voltage                                  |      | 36        | V    |
| I <sub>O</sub> Output current                                  |      | 20        | mA   |
| Duration of output short-circuit to ground                     |      | Unlimited |      |

- (1) Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions* is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) All voltage values, except differential voltages, are with respect to GND.
- (3) Differential voltages are at IN+ with respect to IN-.

## LM2903-Q1

ZHCSIA9G –MAY 2003–REVISED NOVEMBER 2018

www.ti.com.cn

### 6.2 Handling Ratings

|                    |                           |                                                         |                | MIN | MAX  | UNIT |
|--------------------|---------------------------|---------------------------------------------------------|----------------|-----|------|------|
| T <sub>stg</sub>   | Storage temperature range |                                                         | LM2903-Q1 Only | –65 | 150  | °C   |
| V <sub>(ESD)</sub> | Electrostatic discharge   | Human body model (HBM), per AEC Q100-002 <sup>(1)</sup> |                | 0   | 1000 | V    |
|                    |                           | Charged device model (CDM), per AEC Q100-011            |                | 0   | 750  |      |

(1) AEC Q100-002 indicates HBM stressing is done in accordance with the ANSI/ESDA/JEDEC JS-001 specification.

### 6.3 Recommended Operating Conditions, LM2903-Q1

over operating free-air temperature range (unless otherwise noted)

|                                 |                      | MIN | NOM | MAX | UNIT |
|---------------------------------|----------------------|-----|-----|-----|------|
| V <sub>CC</sub> (non-V devices) |                      | 2   |     | 30  | V    |
| V <sub>CC</sub> (V devices)     |                      | 2   |     | 32  | V    |
| T <sub>J</sub>                  | Junction Temperature | –40 |     | 125 | °C   |

### 6.4 Recommended Operating Conditions, LM2903E-Q1

over operating free-air temperature range (unless otherwise noted)

|                 |                      | MIN | NOM | MAX | UNIT |
|-----------------|----------------------|-----|-----|-----|------|
| V <sub>CC</sub> |                      | 2   |     | 30  | V    |
| T <sub>J</sub>  | Junction Temperature | –40 |     | 150 | °C   |

### 6.5 Thermal Information

| THERMAL METRIC <sup>(1)</sup> |                                              | LM2903E-Q1 | LM2903-Q1 | LM2903-Q1 | LM2903-Q1 | UNIT |
|-------------------------------|----------------------------------------------|------------|-----------|-----------|-----------|------|
|                               |                                              | PW         | DGK       | PW        | D         |      |
|                               |                                              | 8 PINS     | 8 PINS    | 8 PINS    | 8 PINS    |      |
| R <sub>θJA</sub>              | Junction-to-ambient thermal resistance       | 178.9      | 199.4     | 186.6     | 126.0     | °C/W |
| R <sub>θJCTop</sub>           | Junction-to-case (top) thermal resistance    | 70.7       | 120.8     | 79.6      | 74.2      |      |
| R <sub>θJB</sub>              | Junction-to-board thermal resistance         | 108.9      | 90.2      | 116.5     | 66.4      |      |
| ψ <sub>JT</sub>               | Junction-to-top characterization parameter   | 11.9       | 21.5      | 17.7      | 25.4      |      |
| ψ <sub>JB</sub>               | Junction-to-board characterization parameter | 107.3      | 119.1     | 114.9     | 65.9      |      |

(1) 有关传统和新热指标的更多信息，请参见应用报告《半导体和 IC 封装热指标》（文献编号：SPRA953）。

## 6.6 Electrical Characteristics

at specified free-air temperature,  $V_{CC} = 5\text{ V}$  (unless otherwise noted)

| PARAMETER                                                       | TEST CONDITIONS                                                                                                    |                                      | T <sub>A</sub> <sup>(1)</sup> | MIN                       | TYP | MAX  | UNIT |
|-----------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|--------------------------------------|-------------------------------|---------------------------|-----|------|------|
| V <sub>IO</sub> Input offset voltage                            | V <sub>O</sub> = 1.4 V,<br>V <sub>IC</sub> = V <sub>IC(min)</sub> ,<br>V <sub>CC</sub> = 5 V to MAX <sup>(2)</sup> | Non-A devices                        | 25°C                          |                           | 2   | 7    | mV   |
|                                                                 |                                                                                                                    |                                      | Full range                    |                           |     | 15   |      |
|                                                                 |                                                                                                                    | A-suffix devices                     | 25°C                          |                           | 1   | 2    |      |
|                                                                 |                                                                                                                    |                                      | Full range                    |                           |     | 4    |      |
| I <sub>IO</sub> Input offset current                            | V <sub>O</sub> = 1.4 V                                                                                             |                                      | 25°C                          |                           | 5   | 50   | nA   |
|                                                                 |                                                                                                                    |                                      | Full range                    |                           |     | 200  |      |
| I <sub>IB</sub> Input bias current                              | V <sub>O</sub> = 1.4 V                                                                                             |                                      | 25°C                          |                           | −25 | −250 | nA   |
|                                                                 |                                                                                                                    |                                      | Full range                    |                           |     | −500 |      |
| V <sub>ICR</sub> Common-mode input voltage range <sup>(3)</sup> |                                                                                                                    |                                      | 25°C                          | 0 to V <sub>CC</sub> −1.5 |     | V    |      |
|                                                                 |                                                                                                                    |                                      | Full range                    | 0 to V <sub>CC</sub> −2   |     |      |      |
| A <sub>VD</sub> Large-signal differential-voltage amplification | V <sub>CC</sub> = 15 V,<br>V <sub>O</sub> = 1.4 V to 11.4 V,<br>R <sub>L</sub> ≥ 15 kΩ to V <sub>CC</sub>          |                                      | 25°C                          | 25                        | 100 | V/mV |      |
| I <sub>OH</sub> High-level output current                       | V <sub>OH</sub> = 5 V                                                                                              | V <sub>ID</sub> = 1 V                | 25°C                          |                           | 0.1 | 50   | nA   |
|                                                                 | V <sub>OH</sub> = V <sub>CC</sub> MAX <sup>(2)</sup>                                                               |                                      | Full range                    |                           |     | 1    | μA   |
| V <sub>OL</sub> Low-level output voltage                        | I <sub>OL</sub> = 4 mA,                                                                                            | V <sub>ID</sub> = −1 V               | 25°C                          |                           | 150 | 400  | mV   |
|                                                                 |                                                                                                                    |                                      | Full range                    |                           |     | 700  |      |
| I <sub>OL</sub> Low-level output current                        | V <sub>OL</sub> = 1.5 V,                                                                                           | V <sub>ID</sub> = −1 V               | 25°C                          | 6                         |     | mA   |      |
| I <sub>CC</sub> Supply current                                  | R <sub>L</sub> = ∞                                                                                                 | V <sub>CC</sub> = 5 V                | 25°C                          |                           | 0.8 | 1    | mA   |
|                                                                 |                                                                                                                    | V <sub>CC</sub> = MAX <sup>(2)</sup> | Full range                    |                           |     | 2.5  |      |

- (1) Full range (MIN or MAX) for LM2903-Q1 is -40°C to 125°C and -40°C to 150°C for the LM2903E-Q1. All characteristics are measured with zero common-mode input voltage, unless otherwise specified.
- (2)  $V_{CC}\text{ MAX} = 30\text{ V}$  for non-V devices and 32 V for V-suffix devices.
- (3) The voltage at either input or common-mode should not be allowed to go negative by more than 0.3 V. The upper end of the common-mode voltage range is  $V_{CC} + 1.5\text{ V}$  for the inverting input (-), and the non-inverting input (+) can exceed the  $V_{CC}$  level; the comparator provides a proper output state. Either or both inputs can go to 30 V (32V for V-suffix devices) without damage.

## 6.7 Switching Characteristics

$V_{CC} = 5\text{ V}$ ,  $T_A = 25^\circ\text{C}$

| PARAMETER     | TEST CONDITIONS                                 |                                       | TYP | UNIT          |
|---------------|-------------------------------------------------|---------------------------------------|-----|---------------|
| Response time | $R_L$ connected to 5 V through 5.1 k $\Omega$ , | 100-mV input step with 5-mV overdrive | 1.3 | $\mu\text{s}$ |
|               | $C_L = 15\text{ pF}^{(1)(2)}$                   | TTL-level input step                  | 0.3 |               |

- (1)  $C_L$  includes probe and jig capacitance.
- (2) The response time specified is the interval between the input step function and the instant when the output crosses 1.4 V.

## 6.8 Typical Characteristics




图 1. Supply Current vs. Supply Voltage




图 2. Supply Current vs. Supply Voltage  
LM2903E-Q1 Only




图 3. Input Bias Current vs. Supply Voltage




图 4. Input Bias Current vs. Supply Voltage  
LM2903E-Q1 Only




图 5. Output Low Voltage vs. Output Current




图 6. Output Low Voltage vs. Output Current  
LM2903E-Q1 Only

## 7 Detailed Description

### 7.1 Overview

The LM2903-Q1 family is a dual comparator with the ability to operate up to 36 V on the supply pin. This standard device has proven ubiquity and versatility across a wide range of applications. This is due to its very wide supply voltages range (2 V to 36 V), low  $I_q$  and fast response.

This device is AEC-Q100 qualified and can operate over a wide temperature range of  $-40^{\circ}\text{C}$  to  $125^{\circ}\text{C}$  (LM2903-Q1) or  $-40^{\circ}\text{C}$  to  $150^{\circ}\text{C}$  (LM2903E-Q1).

The open-drain output allows the user to configure the output's logic low voltage ( $V_{OL}$ ) and can be utilized to enable the comparator to be used in AND functionality.

### 7.2 Functional Block Diagram




图 7. Schematic (Each Comparator)

### 7.3 Feature Description

LM2903-Q1 family consists of a PNP darlington pair input, allowing the device to operate with very high gain and fast response with minimal input bias current. The input Darlington pair creates a limit on the input common mode voltage capability, allowing LM2903-Q1 to accurately function from ground to  $V_{CC}-1.5\text{V}$  differential input. This enables much head room for modern day supplies of 3.3 V and 5.0 V.

The output consists of an open drain NPN (pull-down or low side) transistor. The output NPN will sink current when the positive input voltage is higher than the negative input voltage and the offset voltage. The  $V_{OL}$  is resistive and will scale with the output current. Please see 图 3 in the [Typical Characteristics](#) section for  $V_{OL}$  values with respect to the output current.

### 7.4 Device Functional Modes

#### 7.4.1 Voltage Comparison

The LM2903-Q1 family operates solely as a voltage comparator, comparing the differential voltage between the positive and negative pins and outputting a logic low or high impedance (logic high with pull-up) based on the input differential polarity.

## 8 Application and Implementation

### 8.1 Application Information

LM2903-Q1 will typically be used to compare a single signal to a reference or two signals against each other. Many users take advantage of the open drain output to drive the comparison logic output to a logic voltage level to an MCU or logic device. The wide supply range and high voltage capability makes LM2903Q1 optimal for level shifting to a higher or lower voltage.

### 8.2 Typical Application




图 8. Single-ended and Differential Comparator Configurations

#### 8.2.1 Design Requirements

For this design example, use the parameters listed in 表 1 as the input parameters.

表 1. Design Parameters

| DESIGN PARAMETER                      | EXAMPLE VALUE      |
|---------------------------------------|--------------------|
| Input Voltage Range                   | 0 V to Vsup-1.5 V  |
| Supply Voltage                        | 2 V to 36 V        |
| Logic Supply Voltage                  | 2 V to 36 V        |
| Output Current (R <sub>PULLUP</sub> ) | 1 $\mu$ A to 20 mA |
| Input Overdrive Voltage               | 100 mV             |
| Reference Voltage                     | 2.5 V              |
| Load Capacitance (C <sub>L</sub> )    | 15 pF              |

#### 8.2.2 Detailed Design Procedure

When using LM2903-Q1 family in a general comparator application, determine the following:

- Input Voltage Range
- Minimum Overdrive Voltage
- Output and Drive Current
- Response Time

##### 8.2.2.1 Input Voltage Range

When choosing the input voltage range, the input common mode voltage range ( $V_{ICR}$ ) must be taken in to account. If temperature operation is above or below 25°C the  $V_{ICR}$  can range from 0 V to  $V_{CC} - 2.0$  V. This limits the input voltage range to as high as  $V_{CC} - 2.0$  V and as low as 0 V. Operation outside of this range can yield incorrect comparisons.

Below is a list of input voltage situation and their outcomes:

1. When both IN- and IN+ are both within the common mode range:
  - a. If IN- is higher than IN+ and the offset voltage, the output is low and the output transistor is sinking current
  - b. If IN- is lower than IN+ and the offset voltage, the output is high impedance and the output transistor is not conducting

2. When IN- is higher than common mode and IN+ is within common mode, the output is low and the output transistor is sinking current
3. When IN+ is higher than common mode and IN- is within common mode, the output is high impedance and the output transistor is not conducting
4. When IN- and IN+ are both higher than common mode, the output is low and the output transistor is sinking current

### 8.2.2.2 Minimum Overdrive Voltage

Overdrive Voltage is the differential voltage produced between the positive and negative inputs of the comparator over the offset voltage ( $V_{IO}$ ). In order to make an accurate comparison the Overdrive Voltage ( $V_{OD}$ ) should be higher than the input offset voltage ( $V_{IO}$ ). Overdrive voltage can also determine the response time of the comparator, with the response time decreasing with increasing overdrive. 图 9 and 图 10 show positive and negative response times with respect to overdrive voltage.

### 8.2.2.3 Output and Drive Current

Output current is determined by the load/pull-up resistance and logic/pull-up voltage. The output current will produce a output low voltage ( $V_{OL}$ ) from the comparator. In which  $V_{OL}$  is proportional to the output current. Use 图 5 to determine  $V_{OL}$  based on the output current.

The output current can also effect the transient response. More will be explained in the next section.

### 8.2.2.4 Response Time

The transient response can be determined by the load capacitance ( $C_L$ ), load/pull-up resistance ( $R_{PULLUP}$ ) and equivalent collector-emitter resistance ( $R_{CE}$ ).

- The positive response time ( $\tau_P$ ) is approximately  $\tau_P \sim R_{PULLUP} \times C_L$
- The negative response time ( $\tau_N$ ) is approximately  $\tau_N \sim R_{CE} \times C_L$ 
  - $R_{CE}$  can be determine by taking the slope of 图 5 in it's linear region at the desired temperature, or by dividing the  $V_{OL}$  by  $I_{out}$

### 8.2.3 Application Curves

The following curves were generated with 5 V on  $V_{CC}$  and  $V_{Logic}$ ,  $R_{PULLUP} = 5.1 \text{ k}\Omega$ , and 50 pF scope probe.




图 9. Response Time for Various Overdrives  
(Positive Transition)




图 10. Response Time for Various Overdrives  
(Negative Transition)

## 9 Power Supply Recommendations


For fast response and comparison applications with noisy or AC inputs, it is recommended to use a bypass capacitor on the supply pin to reject any variation on the supply voltage. This variation can eat into the comparator's input common mode range and create an inaccurate comparison.

## 10 Layout

### 10.1 Layout Guidelines

For accurate comparator applications without hysteresis it is important maintain a stable power supply with minimized noise and glitches, which can affect the high level input common mode voltage range. In order to achieve this, it is best to add a bypass capacitor between the supply voltage and ground. This should be implemented on the positive power supply and negative supply (if available). If a negative supply is not being used, do not put a capacitor between the IC's GND pin and system ground.

### 10.2 Layout Example



**11. LM2903Q1 Layout Example**

## 11 器件和文档支持

### 11.1 相关链接

下表列出了快速访问链接。类别包括技术文档、支持与社区资源、工具和软件，以及申请样片或购买产品的快速链接。

表 2. 相关链接

| 器件         | 产品文件夹                 | 样片与购买                 | 技术文档                  | 工具与软件                 | 支持和社区                 |
|------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
| LM2903-Q1  | <a href="#">请单击此处</a> | <a href="#">请单击此处</a> | <a href="#">请单击此处</a> | <a href="#">请单击此处</a> | <a href="#">请单击此处</a> |
| LM2903E-Q1 | <a href="#">请单击此处</a> | <a href="#">请单击此处</a> | <a href="#">请单击此处</a> | <a href="#">请单击此处</a> | <a href="#">请单击此处</a> |

### 11.2 接收文档更新通知

要接收文档更新通知，请导航至 [TI.com.cn](#) 上的器件产品文件夹。单击右上角的 [通知我](#) 进行注册，即可每周接收产品信息更改摘要。有关更改的详细信息，请查看任何已修订文档中包含的修订历史记录。

### 11.3 社区资源

下列链接提供到 TI 社区资源的连接。链接的内容由各个分销商“按照原样”提供。这些内容并不构成 TI 技术规范，并且不一定反映 TI 的观点；请参阅 TI 的 [《使用条款》](#)。

**TI E2E™ 在线社区** [TI 的工程师对工程师 \(E2E\) 社区](#)。此社区的创建目的在于促进工程师之间的协作。在 [e2e.ti.com](#) 中，您可以咨询问题、分享知识、拓展思路并与同行工程师一道帮助解决问题。

**设计支持** [TI 参考设计支持](#) 可帮助您快速查找有帮助的 E2E 论坛、设计支持工具以及技术支持的联系信息。

### 11.4 商标

E2E is a trademark of Texas Instruments.

LM2903-Q1 符合 AEC-Q100 1 级温度范围（-40°C 至 +125°C）标准。LM2903E-Q1 符合 AEC-Q100 0 级温度范围（-40°C 至 +150°C）标准。is a trademark of others.

All other trademarks are the property of their respective owners.

### 11.5 静电放电警告



这些装置包含有限的内置 ESD 保护。存储或装卸时，应将导线一起截短或将装置放置于导电泡棉中，以防止 MOS 门极遭受静电损伤。

### 11.6 术语表

[SLYZ022](#) — *TI* 术语表。

这份术语表列出并解释术语、缩写和定义。

## 12 机械、封装和可订购信息

以下页面包含机械、封装和可订购信息。这些信息是指定器件的最新可用数据。数据如有变更，恕不另行通知，且不会对此文档进行修订。如需获取此数据表的浏览器版本，请查阅左侧的导航栏。

## PACKAGING INFORMATION

| Orderable Device | Status<br>(1) | Package Type | Package<br>Drawing | Pins | Package<br>Qty | Eco Plan<br>(2) | Lead finish/<br>Ball material<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5) | Samples                 |
|------------------|---------------|--------------|--------------------|------|----------------|-----------------|--------------------------------------|----------------------|--------------|-------------------------|-------------------------|
| LM2903AVQDRG4Q1  | ACTIVE        | SOIC         | D                  | 8    | 2500           | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | 2903AVQ                 | <a href="#">Samples</a> |
| LM2903AVQDRQ1    | ACTIVE        | SOIC         | D                  | 8    | 2500           | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | 2903AVQ                 | <a href="#">Samples</a> |
| LM2903AVQPWRG4Q1 | ACTIVE        | TSSOP        | PW                 | 8    | 2000           | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | 2903AVQ                 | <a href="#">Samples</a> |
| LM2903AVQPWRQ1   | ACTIVE        | TSSOP        | PW                 | 8    | 2000           | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | 2903AVQ                 | <a href="#">Samples</a> |
| LM2903EPWRQ1     | ACTIVE        | TSSOP        | PW                 | 8    | 2000           | RoHS & Green    | NIPDAU                               | Level-2-260C-1 YEAR  | -40 to 150   | 2903Q0                  | <a href="#">Samples</a> |
| LM2903QDGKRQ1    | ACTIVE        | VSSOP        | DGK                | 8    | 2500           | RoHS & Green    | NIPDAUAG                             | Level-2-260C-1 YEAR  | -40 to 125   | KACQ                    | <a href="#">Samples</a> |
| LM2903QDRG4Q1    | ACTIVE        | SOIC         | D                  | 8    | 2500           | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | 2903Q1                  | <a href="#">Samples</a> |
| LM2903QDRQ1      | ACTIVE        | SOIC         | D                  | 8    | 2500           | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | 2903Q1                  | <a href="#">Samples</a> |
| LM2903QPWRG4Q1   | ACTIVE        | TSSOP        | PW                 | 8    | 2000           | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | 2903Q1                  | <a href="#">Samples</a> |
| LM2903QPWRQ1     | ACTIVE        | TSSOP        | PW                 | 8    | 2000           | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | 2903Q1                  | <a href="#">Samples</a> |
| LM2903VQDRG4Q1   | ACTIVE        | SOIC         | D                  | 8    | 2500           | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | 2903VQ1                 | <a href="#">Samples</a> |
| LM2903VQDRQ1     | ACTIVE        | SOIC         | D                  | 8    | 2500           | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | 2903VQ1                 | <a href="#">Samples</a> |
| LM2903VQPWRG4Q1  | ACTIVE        | TSSOP        | PW                 | 8    | 2000           | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | 2903VQ                  | <a href="#">Samples</a> |
| LM2903VQPWRQ1    | ACTIVE        | TSSOP        | PW                 | 8    | 2000           | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | 2903VQ                  | <a href="#">Samples</a> |

(1) The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSOLETE:** TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

---

**RoHS Exempt:** TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

**Green:** TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of  $\leq 1000$ ppm threshold. Antimony trioxide based flame retardants must also meet the  $\leq 1000$ ppm threshold requirement.

<sup>(3)</sup> MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

<sup>(4)</sup> There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

<sup>(5)</sup> Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "-" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

<sup>(6)</sup> Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

## TAPE AND REEL INFORMATION



\*All dimensions are nominal

| Device           | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|------------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| LM2903AVQDRQ1    | SOIC         | D               | 8    | 2500 | 330.0              | 12.5               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM2903AVQPWRG4Q1 | TSSOP        | PW              | 8    | 2000 | 330.0              | 12.4               | 7.0     | 3.6     | 1.6     | 8.0     | 12.0   | Q1            |
| LM2903AVQPWRQ1   | TSSOP        | PW              | 8    | 2000 | 330.0              | 12.4               | 7.0     | 3.6     | 1.6     | 8.0     | 12.0   | Q1            |
| LM2903EPWRQ1     | TSSOP        | PW              | 8    | 2000 | 330.0              | 12.4               | 7.0     | 3.6     | 1.6     | 8.0     | 12.0   | Q1            |
| LM2903QDGKRQ1    | VSSOP        | DGK             | 8    | 2500 | 330.0              | 12.4               | 5.3     | 3.4     | 1.4     | 8.0     | 12.0   | Q1            |
| LM2903QPWRG4Q1   | TSSOP        | PW              | 8    | 2000 | 330.0              | 12.4               | 7.0     | 3.6     | 1.6     | 8.0     | 12.0   | Q1            |
| LM2903QPWRQ1     | TSSOP        | PW              | 8    | 2000 | 330.0              | 12.4               | 7.0     | 3.6     | 1.6     | 8.0     | 12.0   | Q1            |
| LM2903VQPWRG4Q1  | TSSOP        | PW              | 8    | 2000 | 330.0              | 12.4               | 7.0     | 3.6     | 1.6     | 8.0     | 12.0   | Q1            |
| LM2903VQPWRQ1    | TSSOP        | PW              | 8    | 2000 | 330.0              | 12.4               | 7.0     | 3.6     | 1.6     | 8.0     | 12.0   | Q1            |

## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal

| Device           | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|------------------|--------------|-----------------|------|------|-------------|------------|-------------|
| LM2903AVQDRQ1    | SOIC         | D               | 8    | 2500 | 340.5       | 336.1      | 25.0        |
| LM2903AVQPWRG4Q1 | TSSOP        | PW              | 8    | 2000 | 367.0       | 367.0      | 35.0        |
| LM2903AVQPWRQ1   | TSSOP        | PW              | 8    | 2000 | 853.0       | 449.0      | 35.0        |
| LM2903EPWRQ1     | TSSOP        | PW              | 8    | 2000 | 853.0       | 449.0      | 35.0        |
| LM2903QDGKRQ1    | VSSOP        | DGK             | 8    | 2500 | 366.0       | 364.0      | 50.0        |
| LM2903QPWRG4Q1   | TSSOP        | PW              | 8    | 2000 | 853.0       | 449.0      | 35.0        |
| LM2903QPWRQ1     | TSSOP        | PW              | 8    | 2000 | 853.0       | 449.0      | 35.0        |
| LM2903VQPWRG4Q1  | TSSOP        | PW              | 8    | 2000 | 367.0       | 367.0      | 35.0        |
| LM2903VQPWRQ1    | TSSOP        | PW              | 8    | 2000 | 853.0       | 449.0      | 35.0        |



## PACKAGE OUTLINE

**SOIC - 1.75 mm max height**

SMALL OUTLINE INTEGRATED CIRCUIT




1. Linear dimensions are in inches [millimeters]. Dimensions in parenthesis are for reference only. Controlling dimensions are in inches. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed .006 [0.15] per side.
4. This dimension does not include interlead flash.
5. Reference JEDEC registration MS-012, variation AA.


**D0008A**

**SOIC - 1.75 mm max height**

SMALL OUTLINE INTEGRATED CIRCUIT



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE:8X



## SOLDER MASK DETAILS

4214825/C 02/2019

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

D0008A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



SOLDER PASTE EXAMPLE  
BASED ON .005 INCH [0.125 MM] THICK STENCIL  
SCALE:8X

4214825/C 02/2019

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

DGK (S-PDSO-G8)

PLASTIC SMALL-OUTLINE PACKAGE




4073329/E 05/06

## NOTES:

- A. All linear dimensions are in millimeters.
- B. This drawing is subject to change without notice.
- C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 per end.
- D. Body width does not include interlead flash. Interlead flash shall not exceed 0.50 per side.
- E. Falls within JEDEC MO-187 variation AA, except interlead flash.

DGK (S-PDSO-G8)

PLASTIC SMALL OUTLINE PACKAGE



- NOTES:
- All linear dimensions are in millimeters.
  - This drawing is subject to change without notice.
  - Publication IPC-7351 is recommended for alternate designs.
  - Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
  - Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.




# EXAMPLE BOARD LAYOUT



PW0008A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



LAND PATTERN EXAMPLE  
SCALE:10X



SOLDER MASK DETAILS  
NOT TO SCALE

4221848/A 02/2015

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

PW0008A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:10X

4221848/A 02/2015

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

## 重要声明和免责声明

TI 提供技术和可靠性数据（包括数据表）、设计资源（包括参考设计）、应用或其他设计建议、网络工具、安全信息和其他资源，不保证没有瑕疵且不做任何明示或暗示的担保，包括但不限于对适销性、某特定用途方面的适用性或不侵犯任何第三方知识产权的暗示担保。

这些资源可供使用 TI 产品进行设计的熟练开发人员使用。您将自行承担以下全部责任：(1) 针对您的应用选择合适的 TI 产品，(2) 设计、验证并测试您的应用，(3) 确保您的应用满足相应标准以及任何其他安全、安保或其他要求。这些资源如有变更，恕不另行通知。TI 授权您仅可将这些资源用于研发本资源所述的 TI 产品的应用。严禁对这些资源进行其他复制或展示。您无权使用任何其他 TI 知识产权或任何第三方知识产权。您应全额赔偿因在这些资源的使用中对 TI 及其代表造成的任何索赔、损害、成本、损失和债务，TI 对此概不负责。

TI 提供的产品受 TI 的销售条款 (<https://www.ti.com.cn/zh-cn/legal/termsofsale.html>) 或 [ti.com.cn](https://www.ti.com.cn) 上其他适用条款/TI 产品随附的其他适用条款的约束。TI 提供这些资源并不会扩展或以其他方式更改 TI 针对 TI 产品发布的适用的担保或担保免责声明。

邮寄地址：上海市浦东新区世纪大道 1568 号中建大厦 32 楼，邮政编码：200122  
Copyright © 2021 德州仪器半导体技术（上海）有限公司