

CSD17551Q3A 30V N 沟道 NexFET™ 功率 MOSFET

1 特性

- 超低 Q_g 和 Q_{gd}
- 低热阻
- 雪崩级
- 无铅
- 符合 RoHS 标准
- 无卤素
- 小外形尺寸无引线 (SON) 3.3mm × 3.3mm 塑料封装


2 应用

- 网络互联、电信和计算系统中的负载点同步降压
- 优化后可适用于控制场效应晶体管 (FET) 应用

3 说明

这款 30V、7.8mΩ、3.3mm × 3.3mm NexFET™ 功率 MOSFET 旨在用于最大程度降低功率转换应用中的损耗。

顶视图



P0093-01

产品概要

$T_A = 25^\circ\text{C}$		典型值	单位
V_{DS}	漏源电压	30	V
Q_g	总栅极电荷 (4.5V)	6.0	nC
Q_{gd}	栅极电荷 (栅极到漏极)	1.5	nC
$R_{DS(on)}$	漏源导通电阻	$V_{GS} = 4.5\text{V}$	9.6 mΩ
		$V_{GS} = 10\text{V}$	7.8 mΩ
$V_{GS(th)}$	阈值电压	1.6	V

订购信息⁽¹⁾

器件	数量	包装介质	封装	发货
CSD17551Q3A	2500	13 英寸卷带	小外形尺寸无引线 (SON) 3.3mm × 3.3mm 塑料封装	卷带封装
CSD17551Q3AT	250	7 英寸卷带		


(1) 如需了解所有可用封装，请参阅产品说明书末尾的可订购产品附录。

绝对最大额定值

$T_A = 25^\circ\text{C}$ 时测得，除非另外注明		值	单位
V_{DS}	漏源电压	30	V
V_{GS}	栅源电压	±20	V
I_D	持续漏极电流， $T_C = 25^\circ\text{C}$ 时	48	A
	持续漏极电流 (受芯片限制)	48	A
	持续漏极电流， $T_A = 25^\circ\text{C}$ 时测得 ⁽¹⁾	12	A
I_{DM}	脉冲漏极电流， $T_A = 25^\circ\text{C}$ 时测得 ⁽²⁾	71	A
P_D	功率耗散 ⁽¹⁾	2.6	W
T_J, T_{stg}	工作结温、储存温度	-55 至 150	°C
E_{AS}	雪崩能量，单一脉冲 $I_D = 25\text{A}$, $L = 0.1\text{mH}$, $R_G = 25\Omega$ 时	31	mJ


(1) $R_{\theta JA} = 48^\circ\text{C/W}$ ，这是在一块厚度为 0.06 英寸 (1.52 mm) 的 FR4 PCB 上的 1 平方英寸 (6.45cm²)，2 盎司覆铜焊盘上测得的典型值。

(2) 脉冲持续时间 ≤ 300μs，占空比 ≤ 2%

 $R_{DS(on)}$ 与 V_{GS} 对比

G001

栅极电荷



G001



目录

1	特性	1	6.1	社区资源	7
2	应用	1	6.2	商标	7
3	说明	1	6.3	静电放电警告	7
4	修订历史记录	2	6.4	Glossary	7
5	Specifications	3	7	机械、封装和可订购信息	8
5.1	Electrical Characteristics	3	7.1	Q3A 封装尺寸	8
5.2	Thermal Information	3	7.2	Q3A 建议的 PCB 布局	9
5.3	Typical MOSFET Characteristics	4	7.3	Q3A 建议的模板布局	9
6	器件和文档支持	7	7.4	Q3A 卷带信息	10

4 修订历史记录

注：之前版本的页码可能与当前版本有所不同。

Changes from Revision A (June 2014) to Revision B	Page
• 改进了 说明 文本。	1
• 已添加 添加了 社区资源 部分	7
• 更新了封装图。	8
• 更新了 PCB 图	9
• 更新了模板布局图	9

Changes from Original (September 2012) to Revision A	Page
• 将“无铅引脚镀层”特性更改成了“无铅”。	1
• 更新了封装尺寸。	8

5 Specifications

5.1 Electrical Characteristics

(T_A = 25°C unless otherwise stated)

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
STATIC CHARACTERISTICS						
BV _{DSS}	Drain-to-source voltage	V _{GS} = 0 V, I _D = 250 μA	30			V
I _{DSS}	Drain-to-source leakage current	V _{GS} = 0 V, V _{DS} = 24 V			1	μA
I _{GSS}	Gate-to-source leakage current	V _{DS} = 0V, V _{GS} = 20 V			100	nA
V _{GS(th)}	Gate-to-source threshold voltage	V _{DS} = V _{GS} , I _D = 250 μA	1.1	1.6	2.1	V
R _{DS(on)}	Drain-to-source on-resistance	V _{GS} = 4.5 V, I _D = 11 A	9.6		11.8	mΩ
		V _{GS} = 10 V, I _D = 11 A	7.8		9	mΩ
g _{fs}	Transconductance	V _{DS} = 15 V, I _D = 11 A	101			S
DYNAMIC CHARACTERISTICS						
C _{iSS}	Input capacitance	V _{GS} = 0 V, V _{DS} = 15 V, f = 1 MHz	1050		1370	pF
C _{oSS}	Output capacitance		244		317	pF
C _{rSS}	Reverse transfer capacitance		24		31	pF
R _G	Series gate resistance		1.5		3	Ω
Q _g	Gate charge total (4.5 V)	V _{DS} = 15 V, I _D = 11 A	6		7.8	nC
Q _{gd}	Gate charge gate to drain		1.5			nC
Q _{gs}	Gate charge gate to source		2.3			nC
Q _{g(th)}	Gate charge at V _{th}		1.4			nC
Q _{oSS}	Output charge	V _{DS} = 15 V, V _{GS} = 0 V	7.4			nC
t _{d(on)}	Turn on delay time	V _{DS} = 15 V, V _{GS} = 4.5 V, I _{DS} = 11 A, R _G = 2 Ω	8			ns
t _r	Rise time		24			ns
t _{d(off)}	Turn off delay time		12			ns
t _f	Fall time		3.4			ns
DIODE CHARACTERISTICS						
V _{SD}	Diode forward voltage	I _{SD} = 11 A, V _{GS} = 0 V	0.8		1	V
Q _{rr}	Reverse recovery charge	V _{DS} = 13.5 V, I _F = 11 A, di/dt = 300 A/μs	13			nC
t _{rr}	Reverse recovery time		14			ns

5.2 Thermal Information

(T_A = 25°C unless otherwise stated)


THERMAL METRIC		MIN	TYP	MAX	UNIT
R _{θJC}	Junction-to-case thermal resistance ⁽¹⁾			3.9	°C/W
R _{θJA}	Junction-to-ambient thermal resistance ⁽¹⁾⁽²⁾			60	°C/W

- (1) R_{θJC} is determined with the device mounted on a 1 inch² (6.45 cm²), 2 oz. (0.071 mm thick) Cu pad on a 1.5 inches × 1.5 inches (3.81 cm × 3.81 cm), 0.06 inch (1.52 mm) thick FR4 PCB. R_{θJC} is specified by design, whereas R_{θJA} is determined by the user's board design.
- (2) Device mounted on FR4 material with 1 inch² (6.45 cm²), 2 oz. (0.071 mm thick) Cu.

CSD17551Q3A


ZHCSAE6B – SEPTEMBER 2012 – REVISED JANUARY 2016

www.ti.com.cn



M0161-01

Max $R_{\theta JA} = 60^{\circ}\text{C/W}$
when mounted on
1 inch² (6.45 cm²) of
2 oz. (0.071 mm thick)
Cu.




M0161-02

Max $R_{\theta JA} = 144^{\circ}\text{C/W}$
when mounted on a
minimum pad area of 2
oz. (0.071 mm thick)
Cu.

5.3 Typical MOSFET Characteristics

($T_A = 25^{\circ}\text{C}$ unless otherwise stated)



Typical MOSFET Characteristics (continued)

($T_A = 25^\circ\text{C}$ unless otherwise stated)




Figure 2. Saturation Characteristics




Figure 3. Transfer Characteristics




Figure 4. Gate Charge




Figure 5. Capacitance




Figure 6. Threshold Voltage vs Temperature




Figure 7. On-State Resistance vs Gate-to-Source Voltage

Typical MOSFET Characteristics (continued)

($T_A = 25^\circ\text{C}$ unless otherwise stated)




Figure 8. Normalized On-State Resistance vs Temperature




Figure 9. Typical Diode Forward Voltage




Figure 10. Maximum Safe Operating Area




Figure 11. Single Pulse Unclamped Inductive Switching




Figure 12. Maximum Drain Current vs Temperature

6 器件和文档支持

6.1 社区资源

下列链接提供到 TI 社区资源的连接。链接的内容由各个分销商“按照原样”提供。这些内容并不构成 TI 技术规范，并且不一定反映 TI 的观点；请参阅 TI 的《使用条款》。

TI E2E™ 在线社区 **TI 的工程师对工程师 (E2E) 社区**。此社区的创建目的在于促进工程师之间的协作。在 e2e.ti.com 中，您可以咨询问题、分享知识、拓展思路并与同行工程师一道帮助解决问题。

设计支持 **TI 参考设计支持** 可帮助您快速查找有帮助的 E2E 论坛、设计支持工具以及技术支持的联系信息。

6.2 商标

NexFET, E2E are trademarks of Texas Instruments.
All other trademarks are the property of their respective owners.

6.3 静电放电警告



这些装置包含有限的内置 ESD 保护。存储或装卸时，应将导线一起截短或将装置放置于导电泡棉中，以防止 MOS 门极遭受静电损伤。

6.4 Glossary


SLYZ022 — *TI Glossary*.

This glossary lists and explains terms, acronyms, and definitions.

7 机械、封装和可订购信息


以下页中包括机械封装、封装和可订购信息。这些信息是针对指定器件可提供的最新数据。数据如有变更，恕不另行通知和修订此文档。如欲获取此产品说明书的浏览器版本，请参阅左侧的导航。

7.1 Q3A 封装尺寸



1. 所有线性尺寸的单位均为毫米。括号中的任何尺寸仅供参考。尺寸和公差值符合 ASME Y14.5M 标准。
2. 本图如有变更，恕不另行通知。
3. 必须在印刷电路板上焊接封装散热焊盘，以获得良好的散热和机械性能。
4. 金属化 特性 为供应商选配特性，因此封装上可能不具备。
5. 所有尺寸不包括模具毛边或突出部分。


7.2 Q3A 建议的 PCB 布局



1. 此封装设计用于焊接到电路板的散热焊盘上。有关更多信息，请参阅《*QFN/SON PCB 连接*》应用报告 (SLUA271)。
2. 根据应用决定是否选用过孔，详情请参见器件产品说明书。如果实现了部分或全部过孔，则会显示建议的过孔位置。


要获得与印刷电路板 (PCB) 设计相关的建议电路布局布线, 请参阅《应用说明》[SLPA005 - 通过 PCB 布局布线技巧来减少振铃](#)。

7.3 Q3A 建议的模板布局



1. 具有漏斗形壁和圆角的激光切割孔可提供更佳的锡膏脱离。IPC-7525 可能提供其他替代性设计建议。

7.4 Q3A 卷带信息



M0144-01

- Notes:
1. 10 链轮孔距累积容差 ± 0.2
 2. 每 100mm 长度的翘曲不能超过 1mm, 在 250mm 长度上不累积
 3. 材料: 黑色抗静电聚苯乙烯
 4. 全部尺寸单位为 mm, 除非另外注明。
 5. 厚度: 0.30 ± 0.05 mm
 6. MSL1 260°C (红外 (IR) 和传导) PbF 回流焊兼容

PACKAGING INFORMATION

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead finish/ Ball material (6)	MSL Peak Temp (3)	Op Temp (°C)	Device Marking (4/5)	Samples
CSD17551Q3A	ACTIVE	VSONP	DNH	8	2500	RoHS & Green	SN	Level-1-260C-UNLIM	-55 to 150	17551	Samples

(1) The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

RoHS Exempt: TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

Green: TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "-" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

重要声明和免责声明

TI 均以“原样”提供技术性 & 可靠性数据（包括数据表）、设计资源（包括参考设计）、应用或其他设计建议、网络工具、安全信息和其他资源，不保证其中不含任何瑕疵，且不做任何明示或暗示的担保，包括但不限于对适销性、适合某特定用途或不侵犯任何第三方知识产权的暗示担保。

所述资源可供专业开发人员应用 TI 产品进行设计使用。您将对以下行为独自承担全部责任：(1) 针对您的应用选择合适的 TI 产品；(2) 设计、验证并测试您的应用；(3) 确保您的应用满足相应标准以及任何其他安全、安保或其他要求。所述资源如有变更，恕不另行通知。TI 对您使用所述资源的授权仅限于开发资源所涉及 TI 产品的相关应用。除此之外不得复制或展示所述资源，也不提供其它 TI 或任何第三方的知识产权授权许可。如因使用所述资源而产生任何索赔、赔偿、成本、损失及债务等，TI 对此概不负责，并且您须赔偿由此对 TI 及其代表造成的损害。

TI 所提供产品均受 TI 的销售条款 (<http://www.ti.com.cn/zh-cn/legal/termsofsale.html>) 以及 [ti.com.cn](http://www.ti.com.cn) 上或随附 TI 产品提供的其他可适用条款的约束。TI 提供所述资源并不扩展或以其他方式更改 TI 针对 TI 产品所发布的可适用的担保范围或担保免责声明。

邮寄地址：上海市浦东新区世纪大道 1568 号中建大厦 32 楼，邮政编码：200122
Copyright © 2020 德州仪器半导体技术（上海）有限公司