


## FEATURES

- Operates From 1.65 V to 3.6 V
- Inputs Accept Voltages to 5.5 V
- Max  $t_{pd}$  of 7.9 ns at 3.3 V
- Typical  $V_{OLP}$  (Output Ground Bounce)  
<0.8 V at  $V_{CC} = 3.3$  V,  $T_A = 25^\circ\text{C}$
- Typical  $V_{OHV}$  (Output  $V_{OH}$  Undershoot)  
>2 V at  $V_{CC} = 3.3$  V,  $T_A = 25^\circ\text{C}$
- Supports Mixed-Mode Signal Operation on All Ports (5-V Input/Output Voltage With 3.3-V  $V_{CC}$ )
- $I_{off}$  Supports Partial-Power-Down Mode Operation
- Latch-Up Performance Exceeds 250 mA Per JESD 17
- ESD Protection Exceeds JESD 22
  - 2000-V Human-Body Model (A114-A)
  - 200-V Machine Model (A115-A)
  - 1000-V Charged-Device Model (C101)

DB, DGV, DW, NS, OR PW PACKAGE  
(TOP VIEW)



## DESCRIPTION/ORDERING INFORMATION

This 9-bit bus-interface flip-flop is designed for 1.65-V to 3.6-V  $V_{CC}$  operation.

The SN74LVC823A is designed specifically for driving highly capacitive or relatively low-impedance loads. It is particularly suitable for implementing wider buffer registers, I/O ports, bidirectional bus drivers with parity, and working registers.

With the clock-enable ( $\overline{\text{CLKEN}}$ ) input low, the nine D-type edge-triggered flip-flops enter data on the low-to-high transitions of the clock. Taking  $\overline{\text{CLKEN}}$  high disables the clock buffer, latching the outputs. This device has noninverting data (D) inputs. Taking the clear ( $\overline{\text{CLR}}$ ) input low causes the nine Q outputs to go low, independently of the clock.

## ORDERING INFORMATION

| $T_A$         | PACKAGE <sup>(1)</sup> |              | ORDERABLE PART NUMBER | TOP-SIDE MARKING |
|---------------|------------------------|--------------|-----------------------|------------------|
| –40°C to 85°C | SOIC – DW              | Tube of 25   | SN74LVC823ADW         | LVC823A          |
|               |                        | Reel of 2000 | SN74LVC823ADWR        |                  |
|               | SOP – NS               | Reel of 2000 | SN74LVC823ANSR        | LVC823A          |
|               | SSOP – DB              | Reel of 2000 | SN74LVC823ADBR        | LC823A           |
|               | TSSOP – PW             | Tube of 60   | SN74LVC823APW         | LC823A           |
|               |                        | Reel of 2000 | SN74LVC823APWR        |                  |
|               |                        | Reel of 250  | SN74LVC823APWT        |                  |
|               | TVSOP – DGV            | Reel of 2000 | SN74LVC823ADGVR       | LC823A           |

(1) Package drawings, standard packing quantities, thermal data, symbolization, and PCB design guidelines are available at [www.ti.com/sc/package](http://www.ti.com/sc/package).



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

# SN74LVC823A

## 9-BIT BUS-INTERFACE FLIP-FLOP WITH 3-STATE OUTPUTS

SCAS305I—MARCH 1993—REVISED FEBRUARY 2005

### DESCRIPTION/ORDERING INFORMATION (CONTINUED)

A buffered output-enable ( $\overline{OE}$ ) input can be used to place the nine outputs in either a normal logic state (high or low logic levels) or the high-impedance state.  $\overline{OE}$  does not affect the internal operations of the latch. Previously stored data can be retained or new data can be entered while the outputs are in the high-impedance state.

Inputs can be driven from either 3.3-V or 5-V devices. This feature allows the use of these devices as translators in a mixed 3.3-V/5-V system environment.


This device is fully specified for partial-power-down applications using  $I_{off}$ . The  $I_{off}$  circuitry disables the outputs, preventing damaging current backflow through the device when it is powered down.

To ensure the high-impedance state during power up or power down,  $\overline{OE}$  should be tied to  $V_{CC}$  through a pullup resistor; the minimum value of the resistor is determined by the current-sinking capability of the driver.

**FUNCTION TABLE  
(EACH FLIP-FLOP)**

| INPUTS          |                  |                    |            |   | OUTPUT<br>Q |
|-----------------|------------------|--------------------|------------|---|-------------|
| $\overline{OE}$ | $\overline{CLR}$ | $\overline{CLKEN}$ | CLK        | D |             |
| L               | L                | X                  | X          | X | L           |
| L               | H                | L                  | $\uparrow$ | H | H           |
| L               | H                | L                  | $\uparrow$ | L | L           |
| L               | H                | H                  | X          | X | $Q_0$       |
| H               | X                | X                  | X          | X | Z           |

**LOGIC DIAGRAM (POSITIVE LOGIC)**



## Absolute Maximum Ratings<sup>(1)</sup>

over operating free-air temperature range (unless otherwise noted)

|                  |                                                                                             | MIN                | MAX                   | UNIT    |
|------------------|---------------------------------------------------------------------------------------------|--------------------|-----------------------|---------|
| V <sub>CC</sub>  | Supply voltage range                                                                        | –0.5               | 6.5                   | V       |
| V <sub>I</sub>   | Input voltage range <sup>(2)</sup>                                                          | –0.5               | 6.5                   | V       |
| V <sub>O</sub>   | Voltage range applied to any output in the high-impedance or power-off state <sup>(2)</sup> | –0.5               | 6.5                   | V       |
| V <sub>O</sub>   | Voltage range applied to any output in the high or low state <sup>(2)(3)</sup>              | –0.5               | V <sub>CC</sub> + 0.5 | V       |
| I <sub>IK</sub>  | Input clamp current                                                                         | V <sub>I</sub> < 0 |                       | –50 mA  |
| I <sub>OK</sub>  | Output clamp current                                                                        | V <sub>O</sub> < 0 |                       | –50 mA  |
| I <sub>O</sub>   | Continuous output current                                                                   |                    | ±50                   | mA      |
|                  | Continuous current through V <sub>CC</sub> or GND                                           |                    | ±100                  | mA      |
| θ <sub>JA</sub>  | Package thermal impedance <sup>(4)</sup>                                                    | DB package         |                       | 63 °C/W |
|                  |                                                                                             | DGV package        |                       | 86      |
|                  |                                                                                             | DW package         |                       | 46      |
|                  |                                                                                             | NS package         |                       | 65      |
|                  |                                                                                             | PW package         |                       | 88      |
| T <sub>stg</sub> | Storage temperature range                                                                   | –65                | 150                   | °C      |

- (1) Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) The input negative-voltage and output voltage ratings may be exceeded if the input and output current ratings are observed.
- (3) The value of V<sub>CC</sub> is provided in the recommended operating conditions table.
- (4) The package thermal impedance is calculated in accordance with JESD 51-7.

## Recommended Operating Conditions<sup>(1)</sup>

|                 |                                    | MIN                                | MAX                    | UNIT            |
|-----------------|------------------------------------|------------------------------------|------------------------|-----------------|
| V <sub>CC</sub> | Supply voltage                     | Operating                          | 1.65                   | 3.6             |
|                 |                                    | Data retention only                | 1.5                    | V               |
| V <sub>IH</sub> | High-level input voltage           | V <sub>CC</sub> = 1.65 V to 1.95 V | 0.65 × V <sub>CC</sub> | V               |
|                 |                                    | V <sub>CC</sub> = 2.3 V to 2.7 V   | 1.7                    |                 |
|                 |                                    | V <sub>CC</sub> = 2.7 V to 3.6 V   | 2                      |                 |
| V <sub>IL</sub> | Low-level input voltage            | V <sub>CC</sub> = 1.65 V to 1.95 V | 0.35 × V <sub>CC</sub> | V               |
|                 |                                    | V <sub>CC</sub> = 2.3 V to 2.7 V   | 0.7                    |                 |
|                 |                                    | V <sub>CC</sub> = 2.7 V to 3.6 V   | 0.8                    |                 |
| V <sub>I</sub>  | Input voltage                      | 0                                  | 5.5                    | V               |
| V <sub>O</sub>  | Output voltage                     | High or low state                  | 0                      | V <sub>CC</sub> |
|                 |                                    | 3-state                            | 0                      | 5.5             |
| I <sub>OH</sub> | High-level output current          | V <sub>CC</sub> = 1.65 V           | –4                     | mA              |
|                 |                                    | V <sub>CC</sub> = 2.3 V            | –8                     |                 |
|                 |                                    | V <sub>CC</sub> = 2.7 V            | –12                    |                 |
|                 |                                    | V <sub>CC</sub> = 3 V              | –24                    |                 |
| I <sub>OL</sub> | Low-level output current           | V <sub>CC</sub> = 1.65 V           | 4                      | mA              |
|                 |                                    | V <sub>CC</sub> = 2.3 V            | 8                      |                 |
|                 |                                    | V <sub>CC</sub> = 2.7 V            | 12                     |                 |
|                 |                                    | V <sub>CC</sub> = 3 V              | 24                     |                 |
| Δt/Δv           | Input transition rise or fall rate |                                    | 10                     | ns/V            |
| T <sub>A</sub>  | Operating free-air temperature     | –40                                | 85                     | °C              |

- (1) All unused inputs of the device must be held at V<sub>CC</sub> or GND to ensure proper device operation. Refer to the TI application report, *Implications of Slow or Floating CMOS Inputs*, literature number SCBA004.

# SN74LVC823A

## 9-BIT BUS-INTERFACE FLIP-FLOP WITH 3-STATE OUTPUTS

SCAS305I–MARCH 1993–REVISED FEBRUARY 2005



### Electrical Characteristics

over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER        |                | TEST CONDITIONS                                                                 |                           | V <sub>CC</sub> | MIN                   | TYP <sup>(1)</sup> | MAX  | UNIT |
|------------------|----------------|---------------------------------------------------------------------------------|---------------------------|-----------------|-----------------------|--------------------|------|------|
| V <sub>OH</sub>  |                |                                                                                 | I <sub>OH</sub> = −100 μA | 1.65 V to 3.6 V | V <sub>CC</sub> − 0.2 |                    |      | V    |
|                  |                |                                                                                 | I <sub>OH</sub> = −4 mA   | 1.65 V          | 1.2                   |                    |      |      |
|                  |                |                                                                                 | I <sub>OH</sub> = −8 mA   | 2.3 V           | 1.7                   |                    |      |      |
|                  |                |                                                                                 | I <sub>OH</sub> = −12 mA  | 2.7 V           | 2.2                   |                    |      |      |
|                  |                |                                                                                 |                           | 3 V             | 2.4                   |                    |      |      |
|                  |                |                                                                                 | I <sub>OH</sub> = −24 mA  | 3 V             | 2.2                   |                    |      |      |
| V <sub>OL</sub>  |                |                                                                                 | I <sub>OL</sub> = 100 μA  | 1.65 V to 3.6 V |                       |                    | 0.2  | V    |
|                  |                |                                                                                 | I <sub>OL</sub> = 4 mA    | 1.65 V          |                       |                    | 0.45 |      |
|                  |                |                                                                                 | I <sub>OL</sub> = 8 mA    | 2.3 V           |                       |                    | 0.7  |      |
|                  |                |                                                                                 | I <sub>OL</sub> = 12 mA   | 2.7 V           |                       |                    | 0.4  |      |
|                  |                |                                                                                 | I <sub>OL</sub> = 24 mA   | 3 V             |                       |                    | 0.55 |      |
| I <sub>I</sub>   |                | V <sub>I</sub> = 0 to 5.5 V                                                     |                           | 3.6 V           |                       |                    | ±5   | μA   |
| I <sub>off</sub> |                | V <sub>I</sub> or V <sub>O</sub> = 5.5 V                                        |                           | 0               |                       |                    | ±10  | μA   |
| I <sub>OZ</sub>  |                | V <sub>O</sub> = 0 to 5.5 V                                                     |                           | 3.6 V           |                       |                    | ±10  | μA   |
| I <sub>CC</sub>  |                | V <sub>I</sub> = V <sub>CC</sub> or GND                                         |                           | 3.6 V           |                       |                    | 10   | μA   |
|                  |                | 3.6 V ≤ V <sub>I</sub> ≤ 5.5 V <sup>(2)</sup>                                   |                           |                 |                       |                    | 10   |      |
| ΔI <sub>CC</sub> |                | One input at V <sub>CC</sub> − 0.6 V,    Other inputs at V <sub>CC</sub> or GND |                           | 2.7 V to 3.6 V  |                       |                    | 500  | μA   |
| C <sub>i</sub>   | Control inputs | V <sub>I</sub> = V <sub>CC</sub> or GND                                         |                           | 3.3 V           |                       |                    | 5    | pF   |
|                  | Data inputs    |                                                                                 |                           |                 |                       |                    | 4    |      |
| C <sub>O</sub>   |                | V <sub>O</sub> = V <sub>CC</sub> or GND                                         |                           | 3.3 V           |                       |                    | 7    | pF   |

(1) All typical values are at V<sub>CC</sub> = 3.3 V, T<sub>A</sub> = 25°C.

(2) This applies in the disabled state only.

### Timing Requirements

over recommended operating free-air temperature range (unless otherwise noted) (see Figure 1)

|                    |                 |                                      | V <sub>CC</sub> = 1.8 V<br>± 0.15 V |     | V <sub>CC</sub> = 2.5 V<br>± 0.2 V |     | V <sub>CC</sub> = 2.7 V |     | V <sub>CC</sub> = 3.3 V<br>± 0.3 V |     | UNIT |
|--------------------|-----------------|--------------------------------------|-------------------------------------|-----|------------------------------------|-----|-------------------------|-----|------------------------------------|-----|------|
|                    |                 |                                      | MIN                                 | MAX | MIN                                | MAX | MIN                     | MAX | MIN                                | MAX |      |
| f <sub>clock</sub> | Clock frequency |                                      | (1)                                 |     | (1)                                |     | 150                     |     | 150                                |     | MHz  |
| t <sub>w</sub>     | Pulse duration  | CL <sub>R</sub> low                  | (1)                                 |     | (1)                                |     | 3.3                     |     | 3.3                                |     | ns   |
|                    |                 | CLK high or low                      | (1)                                 |     | (1)                                |     | 3.3                     |     | 3.3                                |     |      |
| t <sub>su</sub>    | Setup time      | CL <sub>R</sub> inactive before CLK↑ | (1)                                 |     | (1)                                |     | 1                       |     | 1                                  |     | ns   |
|                    |                 | Data before CLK↑                     | (1)                                 |     | (1)                                |     | 1.3                     |     | 1.3                                |     |      |
|                    |                 | CL <sub>KEN</sub> low before CLK↑    | (1)                                 |     | (1)                                |     | 1.8                     |     | 1.8                                |     |      |
| t <sub>h</sub>     | Hold time       | Data after CLK↑                      | (1)                                 |     | (1)                                |     | 2                       |     | 2                                  |     | ns   |
|                    |                 | CL <sub>KEN</sub> low after CLK↑     | (1)                                 |     | (1)                                |     | 1.3                     |     | 1.3                                |     |      |

(1) This information was not available at the time of publication.

## Switching Characteristics

over recommended operating free-air temperature range (unless otherwise noted) (see Figure 1)

| PARAMETER   | FROM<br>(INPUT)         | TO<br>(OUTPUT) | $V_{CC} = 1.8\text{ V}$<br>$\pm 0.15\text{ V}$ |     | $V_{CC} = 2.5\text{ V}$<br>$\pm 0.2\text{ V}$ |     | $V_{CC} = 2.7\text{ V}$ |     | $V_{CC} = 3.3\text{ V}$<br>$\pm 0.3\text{ V}$ |     | UNIT |
|-------------|-------------------------|----------------|------------------------------------------------|-----|-----------------------------------------------|-----|-------------------------|-----|-----------------------------------------------|-----|------|
|             |                         |                | MIN                                            | MAX | MIN                                           | MAX | MIN                     | MAX | MIN                                           | MAX |      |
| $f_{\max}$  |                         |                | (1)                                            |     | (1)                                           |     | 150                     |     | 150                                           |     | MHz  |
| $t_{pd}$    | CLK                     | Q              | (1)                                            | (1) | (1)                                           | (1) | 8.9                     |     | 1.4                                           | 8   | ns   |
|             | $\overline{\text{CLR}}$ |                | (1)                                            | (1) | (1)                                           | (1) | 8.8                     |     | 2.5                                           | 7.9 |      |
| $t_{en}$    | $\overline{\text{OE}}$  | Q              | (1)                                            | (1) | (1)                                           | (1) | 8.3                     |     | 1.6                                           | 7.2 | ns   |
| $t_{dis}$   | $\overline{\text{OE}}$  | Q              | (1)                                            | (1) | (1)                                           | (1) | 7.1                     |     | 1.1                                           | 6   | ns   |
| $t_{sk(o)}$ |                         |                |                                                |     |                                               |     |                         |     | 1                                             |     | ns   |

(1) This information was not available at the time of publication.


## Operating Characteristics

$T_A = 25^\circ\text{C}$

| PARAMETER |                                                |                  | TEST<br>CONDITIONS  | $V_{CC} = 1.8\text{ V}$ | $V_{CC} = 2.5\text{ V}$ | $V_{CC} = 3.3\text{ V}$ | UNIT |
|-----------|------------------------------------------------|------------------|---------------------|-------------------------|-------------------------|-------------------------|------|
|           |                                                |                  |                     | TYP                     | TYP                     | TYP                     |      |
| $C_{pd}$  | Power dissipation capacitance<br>per flip-flop | Outputs enabled  | $f = 10\text{ MHz}$ | (1)                     | (1)                     | 59                      | pF   |
|           |                                                | Outputs disabled |                     | (1)                     | (1)                     | 46                      |      |

(1) This information was not available at the time of publication.


## PARAMETER MEASUREMENT INFORMATION




LOAD CIRCUIT

| TEST              | S1         |
|-------------------|------------|
| $t_{PLH}/t_{PHL}$ | Open       |
| $t_{PLZ}/t_{PZL}$ | $V_{LOAD}$ |
| $t_{PHZ}/t_{PZH}$ | GND        |


| $V_{CC}$                         | INPUTS   |                      | $V_M$      | $V_{LOAD}$        | $C_L$ | $R_L$        | $V_{\Delta}$ |
|----------------------------------|----------|----------------------|------------|-------------------|-------|--------------|--------------|
|                                  | $V_I$    | $t_r/t_f$            |            |                   |       |              |              |
| $1.8\text{ V} \pm 0.15\text{ V}$ | $V_{CC}$ | $\leq 2\text{ ns}$   | $V_{CC}/2$ | $2 \times V_{CC}$ | 30 pF | 1 k $\Omega$ | 0.15 V       |
| $2.5\text{ V} \pm 0.2\text{ V}$  | $V_{CC}$ | $\leq 2\text{ ns}$   | $V_{CC}/2$ | $2 \times V_{CC}$ | 30 pF | 500 $\Omega$ | 0.15 V       |
| 2.7 V                            | 2.7 V    | $\leq 2.5\text{ ns}$ | 1.5 V      | 6 V               | 50 pF | 500 $\Omega$ | 0.3 V        |
| $3.3\text{ V} \pm 0.3\text{ V}$  | 2.7 V    | $\leq 2.5\text{ ns}$ | 1.5 V      | 6 V               | 50 pF | 500 $\Omega$ | 0.3 V        |




VOLTAGE WAVEFORMS  
PULSE DURATION



VOLTAGE WAVEFORMS  
SETUP AND HOLD TIMES



VOLTAGE WAVEFORMS  
PROPAGATION DELAY TIMES  
INVERTING AND NONINVERTING OUTPUTS



VOLTAGE WAVEFORMS  
ENABLE AND DISABLE TIMES  
LOW- AND HIGH-LEVEL ENABLING

- NOTES:
- $C_L$  includes probe and jig capacitance.
  - Waveform 1 is for an output with internal conditions such that the output is low, except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high, except when disabled by the output control.
  - All input pulses are supplied by generators having the following characteristics:  $PRR \leq 10\text{ MHz}$ ,  $Z_O = 50\ \Omega$ .
  - The outputs are measured one at a time, with one transition per measurement.
  - $t_{PLZ}$  and  $t_{PHZ}$  are the same as  $t_{dis}$ .
  - $t_{PZL}$  and  $t_{PZH}$  are the same as  $t_{en}$ .
  - $t_{PLH}$  and  $t_{PHL}$  are the same as  $t_{pd}$ .
  - All parameters and waveforms are not applicable to all devices.

Figure 1. Load Circuit and Voltage Waveforms

## PACKAGING INFORMATION

| Orderable Device | Status<br>(1) | Package Type | Package<br>Drawing | Pins | Package<br>Qty | Eco Plan<br>(2) | Lead finish/<br>Ball material<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5) | Samples                 |
|------------------|---------------|--------------|--------------------|------|----------------|-----------------|--------------------------------------|----------------------|--------------|-------------------------|-------------------------|
| SN74LVC823ADBR   | ACTIVE        | SSOP         | DB                 | 24   | 2000           | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | LC823A                  | <a href="#">Samples</a> |
| SN74LVC823ADGVR  | ACTIVE        | TVSOP        | DGV                | 24   | 2000           | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | LC823A                  | <a href="#">Samples</a> |
| SN74LVC823ADW    | ACTIVE        | SOIC         | DW                 | 24   | 25             | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | LVC823A                 | <a href="#">Samples</a> |
| SN74LVC823APW    | ACTIVE        | TSSOP        | PW                 | 24   | 60             | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | LC823A                  | <a href="#">Samples</a> |
| SN74LVC823APWR   | ACTIVE        | TSSOP        | PW                 | 24   | 2000           | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | LC823A                  | <a href="#">Samples</a> |
| SN74LVC823APWT   | ACTIVE        | TSSOP        | PW                 | 24   | 250            | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | LC823A                  | <a href="#">Samples</a> |

(1) The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBsolete:** TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

**RoHS Exempt:** TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

**Green:** TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.


(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.


## TAPE AND REEL INFORMATION



\*All dimensions are nominal

| Device          | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|-----------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| SN74LVC823ADBR  | SSOP         | DB              | 24   | 2000 | 330.0              | 16.4               | 8.2     | 8.8     | 2.5     | 12.0    | 16.0   | Q1            |
| SN74LVC823ADGVR | TVSOP        | DGV             | 24   | 2000 | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |
| SN74LVC823APWR  | TSSOP        | PW              | 24   | 2000 | 330.0              | 16.4               | 6.95    | 8.3     | 1.6     | 8.0     | 16.0   | Q1            |
| SN74LVC823APWT  | TSSOP        | PW              | 24   | 250  | 330.0              | 16.4               | 6.95    | 8.3     | 1.6     | 8.0     | 16.0   | Q1            |


## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal

| Device          | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|-----------------|--------------|-----------------|------|------|-------------|------------|-------------|
| SN74LVC823ADBR  | SSOP         | DB              | 24   | 2000 | 853.0       | 449.0      | 35.0        |
| SN74LVC823ADGVR | TVSOP        | DGV             | 24   | 2000 | 853.0       | 449.0      | 35.0        |
| SN74LVC823APWR  | TSSOP        | PW              | 24   | 2000 | 853.0       | 449.0      | 35.0        |
| SN74LVC823APWT  | TSSOP        | PW              | 24   | 250  | 853.0       | 449.0      | 35.0        |

## TUBE




\*All dimensions are nominal

| Device        | Package Name | Package Type | Pins | SPQ | L (mm) | W (mm) | T (μm) | B (mm) |
|---------------|--------------|--------------|------|-----|--------|--------|--------|--------|
| SN74LVC823ADW | DW           | SOIC         | 24   | 25  | 506.98 | 12.7   | 4826   | 6.6    |
| SN74LVC823APW | PW           | TSSOP        | 24   | 60  | 530    | 10.2   | 3600   | 3.5    |

## DGV (R-PDSO-G\*\*)

## PLASTIC SMALL-OUTLINE


24 PINS SHOWN



- NOTES: A. All linear dimensions are in millimeters.  
 B. This drawing is subject to change without notice.  
 C. Body dimensions do not include mold flash or protrusion, not to exceed 0,15 per side.  
 D. Falls within JEDEC: 24/48 Pins – MO-153  
 14/16/20/56 Pins – MO-194

DW (R-PDSO-G24)

PLASTIC SMALL OUTLINE




NOTES:

- All linear dimensions are in inches (millimeters). Dimensioning and tolerancing per ASME Y14.5M-1994.
- This drawing is subject to change without notice.
- Body dimensions do not include mold flash or protrusion not to exceed 0.006 (0,15).
- Falls within JEDEC MS-013 variation AD.

DW (R-PDSO-G24)

PLASTIC SMALL OUTLINE




- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Refer to IPC7351 for alternate board design.
  - D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525
  - E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.



## DB (R-PDSO-G\*\*)

## PLASTIC SMALL-OUTLINE

28 PINS SHOWN



- NOTES: A. All linear dimensions are in millimeters.  
 B. This drawing is subject to change without notice.  
 C. Body dimensions do not include mold flash or protrusion not to exceed 0,15.  
 D. Falls within JEDEC MO-150



4220208/A 02/2017

## NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
5. Reference JEDEC registration MO-153.

# EXAMPLE BOARD LAYOUT


PW0024A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE: 10X



4220208/A 02/2017

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

# EXAMPLE STENCIL DESIGN

PW0024A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE: 10X

4220208/A 02/2017

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#) or other applicable terms available either on [ti.com](#) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2022, Texas Instruments Incorporated