# CD54HC174, CD74HC174, CD54HCT174, CD74HCT174

Data sheet acquired from Harris Semiconductor
SCHS159C

## High-Speed CMOS Logic Hex D-Type Flip-Flop with Reset

August 1997 - Revised October 2003

### Features

- **Buffered Positive Edge Triggered Clock**
- **Asynchronous Common Reset**
- **Fanout (Over Temperature Range)**
  - **Standard Outputs . . . . . 10 LSTTL Loads**
  - **Bus Driver Outputs . . . . . 15 LSTTL Loads**
- **Wide Operating Temperature Range . . . -55$^{O}$C to 125$^{O}$C**
- **Balanced Propagation Delay and Transition Times**
- **Significant Power Reduction Compared to LSTTL Logic ICs**
- **HC Types**
  - **2V to 6V Operation**
  - **High Noise Immunity: $N_{IL}$ = 30%, $N_{IH}$ = 30% of $V_{CC}$ at $V_{CC}$ = 5V**
- **HCT Types**
  - **4.5V to 5.5V Operation**
  - **Direct LSTTL Input Logic Compatibility, $V_{IL}$= 0.8V (Max), $V_{IH}$ = 2V (Min)**
  - **CMOS Input Compatibility, $I_I \leq 1\mu A$ at $V_{OL}$, $V_{OH}$**

### Description

The ’HC174 and ’HCT174 are edge triggered flip-flops which utilize silicon gate CMOS circuitry to implement D-type flip-flops. They possess low power and speeds comparable to low power Schottky TTL circuits. The devices contain six master-slave flip-flops with a common clock and common reset. Data on the D input having the specified setup and hold times is transferred to the Q output on the low to high transition of the CLOCK input. The $\overline{MR}$ input, when low, sets all outputs to a low state.

Each output can drive ten low power Schottky TTL equivalent loads. The ’HCT174 is functional as well as, pin compatible to the ’LS174.


### Ordering Information

| PART NUMBER | TEMP. RANGE ($^{O}$C) | PACKAGE |
|---|---|---|
| CD54HC174F3A | -55 to 125 | 16 Ld CERDIP |
| CD54HCT174F3A | -55 to 125 | 16 Ld CERDIP |
| CD74HC174E | -55 to 125 | 16 Ld PDIP |
| CD74HC174M | -55 to 125 | 16 Ld SOIC |
| CD74HC174MT | -55 to 125 | 16 Ld SOIC |
| CD74HC174M96 | -55 to 125 | 16 Ld SOIC |
| CD74HCT174E | -55 to 125 | 16 Ld PDIP |
| CD74HCT174M | -55 to 125 | 16 Ld SOIC |
| CD74HCT174MT | -55 to 125 | 16 Ld SOIC |
| CD74HCT174M96 | -55 to 125 | 16 Ld SOIC |

NOTE: When ordering, use the entire part number. The suffix 96 denotes tape and reel. The suffix T denotes a small-quantity reel of 250.

### Pinout


**CD54HC174, CD54HCT174**
**(CERDIP)**
**CD74HC174, CD74HCT174**
**(PDIP, SOIC)**
TOP VIEW




CAUTION: These devices are sensitive to electrostatic discharge. Users should follow proper IC Handling Procedures.

Copyright © 2003, Texas Instruments Incorporated

## Functional Diagram





**TRUTH TABLE**

| INPUTS | | | OUTPUT |
|---|---|---|---|
| RESET ($\overline{MR}$) | CLOCK CP | DATA $D_n$ | $Q_n$ |
| L | X | X | L |
| H | ↑ | H | H |
| H | ↑ | L | L |
| H | L | X | $Q_0$ |

H = High Voltage Level, L = Low Voltage Level, X = Irrelevant, ↑ = Transition from Low to High Level, $Q_0$ = Level Before the Indicated Steady-State Input Conditions Were Established

## Logic Diagram



## Absolute Maximum Ratings

DC Supply Voltage, $V_{CC}$ . . . . . -0.5V to 7V
DC Input Diode Current, $I_{IK}$
For $V_I$ < -0.5V or $V_I$ > $V_{CC}$ + 0.5V . . . . . ±20mA
DC Output Diode Current, $I_{OK}$
For $V_O$ < -0.5V or $V_O$ > $V_{CC}$ + 0.5V . . . . . ±20mA
DC Output Source or Sink Current per Output Pin, $I_O$
For $V_O$ > -0.5V or $V_O$ < $V_{CC}$ + 0.5V . . . . . ±25mA
DC $V_{CC}$ or Ground Current, $I_{CC}$ or $I_{GND}$ . . . . . ±50mA

## Operating Conditions

Temperature Range ($T_A$) . . . . . -55°C to 125°C
Supply Voltage Range, $V_{CC}$
HC Types . . . . . 2V to 6V
HCT Types . . . . . 4.5V to 5.5V
DC Input or Output Voltage, $V_I$, $V_O$ . . . . . 0V to $V_{CC}$
Input Rise and Fall Time
2V . . . . . 1000ns (Max)
4.5V. . . . . 500ns (Max)
6V . . . . . 400ns (Max)

## Thermal Information

| Thermal Resistance (Typical, Note 1) | $\theta_{JA}$ (°C/W) |
|---|---|
| E (PDIP) Package | 67 |
| M (SOIC) Package | 73 |

Maximum Junction Temperature . . . . . 150°C
Maximum Storage Temperature Range . . . . . -65°C to 150°C
Maximum Lead Temperature (Soldering 10s) . . . . . 300°C
(SOIC - Lead Tips Only)

*CAUTION: Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied.*

NOTE:

1. The package thermal impedance is calculated in accordance with JESD 51-7.

## DC Electrical Specifications

| PARAMETER | SYMBOL | TEST CONDITIONS | | $V_{CC}$ (V) | 25°C | | | -40°C TO +85°C | | -55°C TO 125°C | | UNITS |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | $V_I$ (V) | $I_O$ (mA) | | MIN | TYP | MAX | MIN | MAX | MIN | MAX | |
| **HC TYPES** | | | | | | | | | | | | |
| High Level Input Voltage | $V_{IH}$ | - | - | 2 | 1.5 | - | - | 1.5 | - | 1.5 | - | V |
| | | | | 4.5 | 3.15 | - | - | 3.15 | - | 3.15 | - | V |
| | | | | 6 | 4.2 | - | - | 4.2 | - | 4.2 | - | V |
| Low Level Input Voltage | $V_{IL}$ | - | - | 2 | - | - | 0.5 | - | 0.5 | - | 0.5 | V |
| | | | | 4.5 | - | - | 1.35 | - | 1.35 | - | 1.35 | V |
| | | | | 6 | - | - | 1.8 | - | 1.8 | - | 1.8 | V |
| High Level Output Voltage CMOS Loads | $V_{OH}$ | $V_{IH}$ or $V_{IL}$ | -0.02 | 2 | 1.9 | - | - | 1.9 | - | 1.9 | - | V |
| | | | -0.02 | 4.5 | 4.4 | - | - | 4.4 | - | 4.4 | - | V |
| | | | -0.02 | 6 | 5.9 | - | - | 5.9 | - | 5.9 | - | V |
| High Level Output Voltage TTL Loads | | | -4 | 4.5 | 3.98 | - | - | 3.84 | - | 3.7 | - | V |
| | | | -5.2 | 6 | 5.48 | - | - | 5.34 | - | 5.2 | - | V |
| Low Level Output Voltage CMOS Loads | $V_{OL}$ | $V_{IH}$ or $V_{IL}$ | 0.02 | 2 | - | - | 0.1 | - | 0.1 | - | 0.1 | V |
| | | | 0.02 | 4.5 | - | - | 0.1 | - | 0.1 | - | 0.1 | V |
| | | | 0.02 | 6 | - | - | 0.1 | - | 0.1 | - | 0.1 | V |
| Low Level Output Voltage TTL Loads | | | 4 | 4.5 | - | - | 0.26 | - | 0.33 | - | 0.4 | V |
| | | | 5.2 | 6 | - | - | 0.26 | - | 0.33 | - | 0.4 | V |
| Input Leakage Current | $I_I$ | $V_{CC}$ or GND | - | 6 | - | - | ±0.1 | - | ±1 | - | ±1 | µA |
| Quiescent Device Current | $I_{CC}$ | $V_{CC}$ or GND | 0 | 6 | - | - | 8 | - | 80 | - | 160 | µA |

## DC Electrical Specifications (Continued)

| PARAMETER | SYMBOL | TEST CONDITIONS | | $V_{CC}$ (V) | 25°C | | | -40°C TO +85°C | | -55°C TO 125°C | | UNITS |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | $V_I$ (V) | $I_O$ (mA) | | MIN | TYP | MAX | MIN | MAX | MIN | MAX | |
| **HCT TYPES** | | | | | | | | | | | | |
| High Level Input Voltage | $V_{IH}$ | - | - | 4.5 to 5.5 | 2 | - | - | 2 | - | 2 | - | V |
| Low Level Input Voltage | $V_{IL}$ | - | - | 4.5 to 5.5 | - | - | 0.8 | - | 0.8 | - | 0.8 | V |
| High Level Output Voltage CMOS Loads | $V_{OH}$ | $V_{IH}$ or $V_{IL}$ | -0.02 | 4.5 | 4.4 | - | - | 4.4 | - | 4.4 | - | V |
| High Level Output Voltage TTL Loads | | | -4 | 4.5 | 3.98 | - | - | 3.84 | - | 3.7 | - | V |
| Low Level Output Voltage CMOS Loads | $V_{OL}$ | $V_{IH}$ or $V_{IL}$ | 0.02 | 4.5 | - | - | 0.1 | - | 0.1 | - | 0.1 | V |
| Low Level Output Voltage TTL Loads | | | 4 | 4.5 | - | - | 0.26 | - | 0.33 | - | 0.4 | V |
| Input Leakage Current | $I_I$ | $V_{CC}$ to GND | 0 | 5.5 | - | - | ±0.1 | - | ±1 | - | ±1 | µA |
| Quiescent Device Current | $I_{CC}$ | $V_{CC}$ or GND | 0 | 5.5 | - | - | 8 | - | 80 | - | 160 | µA |
| Additional Quiescent Device Current Per Input Pin: 1 Unit Load | $\Delta I_{CC}$ (Note 2) | $V_{CC}$ -2.1 | - | 4.5 to 5.5 | - | 100 | 360 | - | 450 | - | 490 | µA |

NOTE:

2. For dual-supply systems theoretical worst case ($V_I$ = 2.4V, $V_{CC}$ = 5.5V) specification is 1.8mA.

## HCT Input Loading Table

| INPUT | UNIT LOADS |
|---|---|
| CP | 0.80 |
| $\overline{MR}$ | 0.55 |
| D | 0.15 |

NOTE: Unit Load is $\Delta I_{CC}$ limit specified in DC Electrical Specifications table, e.g. 360µA max at 25°C.

## Prerequisite For Switching Function

| PARAMETER | SYMBOL | TEST CONDITIONS | $V_{CC}$ (V) | 25°C | | -40°C TO 85°C | | -55°C TO 125°C | | UNITS |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | | MIN | MAX | MIN | MAX | MIN | MAX | |
| **HC TYPES** | | | | | | | | | | |
| Clock Pulse Width | $t_w$ | - | 2 | 80 | - | 100 | - | 120 | - | ns |
| | | | 4.5 | 16 | - | 20 | - | 24 | - | ns |
| | | | 6 | 14 | - | 17 | - | 20 | - | ns |
| $\overline{MR}$ Pulse Width | $t_w$ | - | 2 | 80 | - | 100 | - | 120 | - | ns |
| | | | 4.5 | 16 | - | 20 | - | 24 | - | ns |
| | | | 6 | 14 | - | 17 | - | 20 | - | ns |

## Prerequisite For Switching Function (Continued)

| PARAMETER | SYMBOL | TEST CONDITIONS | $V_{CC}$ (V) | 25°C | | -40°C TO 85°C | | -55°C TO 125°C | | UNITS |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | | MIN | MAX | MIN | MAX | MIN | MAX | |
| Setup Time, Data to Clock | $t_{SU}$ | - | 2 | 60 | - | 75 | - | 90 | - | ns |
| | | | 4.5 | 12 | - | 15 | - | 18 | - | ns |
| | | | 6 | 10 | - | 13 | - | 15 | - | ns |
| Hold Time, Data to Clock | $t_H$ | - | 2 | 5 | - | 5 | - | 5 | - | ns |
| | | | 4.5 | 5 | - | 5 | - | 5 | - | ns |
| | | | 6 | 5 | - | 5 | - | 5 | - | ns |
| Removal Time, $\overline{MR}$ to Clock | $t_{REM}$ | - | 2 | 5 | - | 5 | - | 5 | - | ns |
| | | | 4.5 | 5 | - | 5 | - | 5 | - | ns |
| | | | 6 | 5 | - | 5 | - | 5 | - | ns |
| Clock Frequency | $f_{MAX}$ | - | 2 | 6 | - | 5 | - | 4 | - | MHz |
| | | | 4.5 | 30 | - | 24 | - | 20 | - | MHz |
| | | | 6 | 35 | - | 28 | - | 24 | - | MHz |
| **HCT TYPES** | | | | | | | | | | |
| Clock Pulse Width | $t_W$ | - | 4.5 | 20 | - | 25 | - | 30 | - | ns |
| $\overline{MR}$ Pulse Width | $t_W$ | - | 6 | 25 | - | 31 | - | 38 | - | ns |
| Setup Time, Data to Clock | $t_{SU}$ | - | 4.5 | 16 | - | 20 | - | 24 | - | ns |
| Hold Time, Data to Clock | $t_H$ | - | 6 | 5 | - | 5 | - | 5 | - | ns |
| Removal Time, $\overline{MR}$ to Clock | $t_{REM}$ | - | 4.5 | 12 | - | 15 | - | 18 | - | ns |
| Clock Frequency | $f_{MAX}$ | - | 6 | 25 | - | 20 | - | 17 | - | MHz |

## Switching Specifications Input $t_r$, $t_f$ = 6ns

| PARAMETER | SYMBOL | TEST CONDITIONS | $V_{CC}$ (V) | 25°C | | -40°C TO 85°C | -55°C TO 125°C | UNITS |
|---|---|---|---|---|---|---|---|---|
| | | | | TYP | MAX | MAX | MAX | |
| **HC TYPES** | | | | | | | | |
| Propagation Delay, Clock to Q | $t_{PLH}$, $t_{PHL}$ | $C_L$ = 50pF | 2 | - | 165 | 205 | 250 | ns |
| | | | 4.5 | - | 33 | 41 | 50 | ns |
| | | | 6 | - | 28 | 35 | 43 | ns |
| | | $C_L$ = 15pF | 5 | 13 | - | - | - | ns |
| Propagation Delay, $\overline{MR}$ to Q | $t_{PLH}$, $t_{PHL}$ | $C_L$ = 50pF | 2 | - | 150 | 190 | 225 | ns |
| | | | 4.5 | - | 30 | 38 | 45 | ns |
| | | | 6 | - | 26 | 33 | 38 | ns |
| | | $C_L$ = 15pF | 5 | 12 | - | - | - | ns |
| Output Transition Times | $t_{TLH}$, $t_{THL}$ | $C_L$ = 50pF | 2 | - | 75 | 95 | 110 | ns |
| | | | 4.5 | - | 15 | 19 | 22 | ns |
| | | | 6 | - | 13 | 16 | 19 | ns |
| Input Capacitance | $C_{IN}$ | - | - | - | 10 | 10 | 10 | pF |
| Power Dissipation Capacitance (Notes 3, 4) | $C_{PD}$ | - | 5 | 38 | - | - | - | pF |

**Switching Specifications** Input $t_r$, $t_f$ = 6ns **(Continued)**

| PARAMETER | SYMBOL | TEST CONDITIONS | $V_{CC}$ (V) | 25°C | | -40°C TO 85°C | -55°C TO 125°C | UNITS |
|---|---|---|---|---|---|---|---|---|
| | | | | TYP | MAX | MAX | MAX | |
| **HCT TYPES** | | | | | | | | |
| Propagation Delay, Clock to Q | $t_{PLH}$, $t_{PHL}$ | $C_L$ = 50pF | 4.5 | - | 40 | 50 | 60 | ns |
| | | $C_L$ = 15pF | 5 | 17 | - | - | - | ns |
| Propagation Delay, $\overline{MR}$ to Q | $t_{PLH}$, $t_{PHL}$ | $C_L$ = 50pF | 4.5 | - | 44 | 55 | 66 | ns |
| | | $C_L$ = 15pF | 5 | 18 | - | - | - | ns |
| Output Transition Times | $t_{TLH}$, $t_{THL}$ | $C_L$ = 50pF | 4.5 | - | 15 | 19 | 22 | ns |
| Input Capacitance | $C_{IN}$ | - | - | - | 10 | 10 | 10 | pF |
| Power Dissipation Capacitance (Notes 3, 4) | $C_{PD}$ | - | 5 | 44 | - | - | - | pF |

NOTES:

3. $C_{PD}$ is used to determine the dynamic power consumption, per flip-flop.
4. $P_D = V_{CC}^2 f_i + \Sigma (C_L V_{CC}^2 + f_O)$ where $f_i$ = Input Frequency, $f_O$ = Input Frequency, $C_L$ = Output Load Capacitance, $V_{CC}$ = Supply Voltage.

## Test Circuits and Waveforms





**FIGURE 1. HC SETUP TIMES, HOLD TIMES, REMOVAL TIME, AND PROPAGATION DELAY TIMES FOR EDGE TRIGGERED SEQUENTIAL LOGIC CIRCUITS**





**FIGURE 2. HCT SETUP TIMES, HOLD TIMES, REMOVAL TIME, AND PROPAGATION DELAY TIMES FOR EDGE TRIGGERED SEQUENTIAL LOGIC CIRCUITS**

## PACKAGING INFORMATION

| Orderable Device | Status (1) | Package Type | Package Drawing | Pins | Package Qty | Eco Plan (2) | Lead finish/ Ball material (6) | MSL Peak Temp (3) | Op Temp (°C) | Device Marking (4/5) | Samples |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 5962-8974301EA | ACTIVE | CDIP | J | 16 | 1 | Non-RoHS & Green | SNPB | N / A for Pkg Type | -55 to 125 | 5962-8974301EA CD54HCT174F3A | Samples |
| CD54HC174F | ACTIVE | CDIP | J | 16 | 1 | Non-RoHS & Green | SNPB | N / A for Pkg Type | -55 to 125 | CD54HC174F | Samples |
| CD54HC174F3A | ACTIVE | CDIP | J | 16 | 1 | Non-RoHS & Green | SNPB | N / A for Pkg Type | -55 to 125 | 8407301EA CD54HC174F3A | Samples |
| CD54HCT174F | ACTIVE | CDIP | J | 16 | 1 | Non-RoHS & Green | SNPB | N / A for Pkg Type | -55 to 125 | CD54HCT174F | Samples |
| CD54HCT174F3A | ACTIVE | CDIP | J | 16 | 1 | Non-RoHS & Green | SNPB | N / A for Pkg Type | -55 to 125 | 5962-8974301EA CD54HCT174F3A | Samples |
| CD74HC174E | ACTIVE | PDIP | N | 16 | 25 | RoHS & Green | NIPDAU | N / A for Pkg Type | -55 to 125 | CD74HC174E | Samples |
| CD74HC174M | ACTIVE | SOIC | D | 16 | 40 | RoHS & Green | NIPDAU | Level-1-260C-UNLIM | -55 to 125 | HC174M | Samples |
| CD74HC174M96 | ACTIVE | SOIC | D | 16 | 2500 | RoHS & Green | NIPDAU | Level-1-260C-UNLIM | -55 to 125 | HC174M | Samples |
| CD74HC174M96E4 | ACTIVE | SOIC | D | 16 | 2500 | RoHS & Green | NIPDAU | Level-1-260C-UNLIM | -55 to 125 | HC174M | Samples |
| CD74HC174MG4 | ACTIVE | SOIC | D | 16 | 40 | RoHS & Green | NIPDAU | Level-1-260C-UNLIM | -55 to 125 | HC174M | Samples |
| CD74HCT174E | ACTIVE | PDIP | N | 16 | 25 | RoHS & Green | NIPDAU | N / A for Pkg Type | -55 to 125 | CD74HCT174E | Samples |
| CD74HCT174EE4 | ACTIVE | PDIP | N | 16 | 25 | RoHS & Green | NIPDAU | N / A for Pkg Type | -55 to 125 | CD74HCT174E | Samples |
| CD74HCT174M | ACTIVE | SOIC | D | 16 | 40 | RoHS & Green | NIPDAU | Level-1-260C-UNLIM | -55 to 125 | HCT174M | Samples |
| CD74HCT174M96 | ACTIVE | SOIC | D | 16 | 2500 | RoHS & Green | NIPDAU | Level-1-260C-UNLIM | -55 to 125 | HCT174M | Samples |
| CD74HCT174M96G4 | ACTIVE | SOIC | D | 16 | 2500 | RoHS & Green | NIPDAU | Level-1-260C-UNLIM | -55 to 125 | HCT174M | Samples |
| CD74HCT174MG4 | ACTIVE | SOIC | D | 16 | 40 | RoHS & Green | NIPDAU | Level-1-260C-UNLIM | -55 to 125 | HCT174M | Samples |
| CD74HCT174MT | ACTIVE | SOIC | D | 16 | 250 | RoHS & Green | NIPDAU | Level-1-260C-UNLIM | -55 to 125 | HCT174M | Samples |

(1) The marketing status values are defined as follows:
**ACTIVE:** Product device recommended for new designs.
**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.
**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.
**OBSOLETE:** TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".
**RoHS Exempt:** TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.
**Green:** TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:**The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**OTHER QUALIFIED VERSIONS OF CD54HC174, CD54HCT174, CD74HC174, CD74HCT174 :**

- Catalog : CD74HC174, CD74HCT174
- Military : CD54HC174, CD54HCT174


NOTE: Qualified Version Definitions:

- Catalog - TI's standard catalog product


- Military - QML certified for Military and Defense Applications

## TAPE AND REEL INFORMATION

**REEL DIMENSIONS**





**TAPE DIMENSIONS**




| | |
|---|---|
| A0 | Dimension designed to accommodate the component width |
| B0 | Dimension designed to accommodate the component length |
| K0 | Dimension designed to accommodate the component thickness |
| W | Overall width of the carrier tape |
| P1 | Pitch between successive cavity centers |


**QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE**




*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| CD74HC174M96 | SOIC | D | 16 | 2500 | 330.0 | 16.4 | 6.5 | 10.3 | 2.1 | 8.0 | 16.0 | Q1 |
| CD74HCT174M96 | SOIC | D | 16 | 2500 | 330.0 | 16.4 | 6.5 | 10.3 | 2.1 | 8.0 | 16.0 | Q1 |


TAPE AND REEL BOX DIMENSIONS




*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Length (mm) | Width (mm) | Height (mm) |
|---|---|---|---|---|---|---|---|
| CD74HC174M96 | SOIC | D | 16 | 2500 | 340.5 | 336.1 | 32.0 |
| CD74HCT174M96 | SOIC | D | 16 | 2500 | 340.5 | 336.1 | 32.0 |


## TUBE




*All dimensions are nominal


| Device | Package Name | Package Type | Pins | SPQ | L (mm) | W (mm) | T (µm) | B (mm) |
|---|---|---|---|---|---|---|---|---|
| CD74HC174E | N | PDIP | 16 | 25 | 506 | 13.97 | 11230 | 4.32 |
| CD74HC174E | N | PDIP | 16 | 25 | 506 | 13.97 | 11230 | 4.32 |
| CD74HC174M | D | SOIC | 16 | 40 | 507 | 8 | 3940 | 4.32 |
| CD74HC174MG4 | D | SOIC | 16 | 40 | 507 | 8 | 3940 | 4.32 |
| CD74HCT174E | N | PDIP | 16 | 25 | 506 | 13.97 | 11230 | 4.32 |
| CD74HCT174E | N | PDIP | 16 | 25 | 506 | 13.97 | 11230 | 4.32 |
| CD74HCT174EE4 | N | PDIP | 16 | 25 | 506 | 13.97 | 11230 | 4.32 |
| CD74HCT174EE4 | N | PDIP | 16 | 25 | 506 | 13.97 | 11230 | 4.32 |
| CD74HCT174M | D | SOIC | 16 | 40 | 507 | 8 | 3940 | 4.32 |
| CD74HCT174MG4 | D | SOIC | 16 | 40 | 507 | 8 | 3940 | 4.32 |

D (R–PDSO–G16) PLASTIC SMALL OUTLINE




NOTES:
A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.006 (0,15) each side.
D. Body width does not include interlead flash. Interlead flash shall not exceed 0.017 (0,43) each side.
E. Reference JEDEC MS–012 variation AC.

D (R–PDSO–G16) PLASTIC SMALL OUTLINE





NOTES:
A. All linear dimensions are in millimeters.
B. This drawing is subject to change without notice.
C. Publication IPC–7351 is recommended for alternate designs.
D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC–7525 for other stencil recommendations.
E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.


J (R–GDIP–T**)

14 LEADS SHOWN

# CERAMIC DUAL IN–LINE PACKAGE




| DIM \ PINS ** | 14 | 16 | 18 | 20 |
|---|---|---|---|---|
| A | 0.300 (7,62) BSC | 0.300 (7,62) BSC | 0.300 (7,62) BSC | 0.300 (7,62) BSC |
| B MAX | 0.785 (19,94) | .840 (21,34) | 0.960 (24,38) | 1.060 (26,92) |
| B MIN | — | — | — | — |
| C MAX | 0.300 (7,62) | 0.300 (7,62) | 0.310 (7,87) | 0.300 (7,62) |
| C MIN | 0.245 (6,22) | 0.245 (6,22) | 0.220 (5,59) | 0.245 (6,22) |





4040083/F 03/03

NOTES:
A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. This package is hermetically sealed with a ceramic lid using glass frit.
D. Index point is provided on cap for terminal identification only on press ceramic glass frit seal only.
E. Falls within MIL STD 1835 GDIP1–T14, GDIP1–T16, GDIP1–T18 and GDIP1–T20.


## N (R–PDIP–T**)

## PLASTIC DUAL–IN–LINE PACKAGE

16 PINS SHOWN




| DIM \ PINS ** | 14 | 16 | 18 | 20 |
|---|---|---|---|---|
| A MAX | 0.775 (19,69) | 0.775 (19,69) | 0.920 (23,37) | 1.060 (26,92) |
| A MIN | 0.745 (18,92) | 0.745 (18,92) | 0.850 (21,59) | 0.940 (23,88) |
| MS–001 VARIATION (C) | AA | BB | AC | AD |




4040049/E 12/2002

NOTES:
A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Falls within JEDEC MS–001, except 18 and 20 pin minimum body length (Dim A).
D. The 20 pin end lead shoulder width is a vendor option, either half or full width.

# IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES “AS IS” AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI’s products are provided subject to TI’s Terms of Sale or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI’s provision of these resources does not expand or otherwise alter TI’s applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2022, Texas Instruments Incorporated