

# TMCS1107 3% 精度、基本型隔离霍尔效应电流传感器，具有 $\pm 420\text{V}$ 工作电压

## 1 特性

- 总体误差：典型值  $\pm 1\%$ ，最大值  $\pm 3\%$ ， $-40^{\circ}\text{C}$  至  $125^{\circ}\text{C}$ 
  - 灵敏度误差： $\pm 0.9\%$
  - 失调电压误差：40mV
  - 温漂  $0.2\text{mV}/^{\circ}\text{C}$
  - 线性误差：0.5%
- 多个灵敏度选项：
  - TMCS1107A1B/U：50mV/A
  - TMCS1107A2B/U：100mV/A
  - TMCS1107A3B/U：200mV/A
  - TMCS1107A4B/U：400mV/A
- 零漂移内部基准
- 双向和单向电流感应
- 工作电源电压范围：3V 至 5.5V
- 信号带宽：80kHz
- $3\text{kV}_{\text{RMS}}$  隔离额定值
- 稳健的 420V 使用寿命内工作电压
- 安全相关认证
  - UL 1577 组件认证计划
  - IEC/CB 62368-1

## 2 应用

- 电机和负载控制
- 逆变器和 H 桥电流测量
- 功率因数校正
- 过流保护
- 直流和交流电源监控

## 3 说明

TMCS1107 是一款电隔离霍尔效应电流传感器，能够测量直流或交流电流，并具有高精度、出色的线性和温度稳定性。低漂移、温度补偿信号链可以在器件的温度范围内实现  $<3\%$  的满量程误差。

输入电流流经内部  $1.8\text{m}\Omega$  导体时，此导体产生的磁场可由集成式霍尔效应传感器进行测量。这种结构省去了外部集中器并简化了设计。低导体电阻可更大限度减少功率损耗和热耗散。固有的电镀绝缘在电流路径与电路之间提供了 420V 使用寿命内工作电压和  $3\text{kV}_{\text{RMS}}$  基本型隔离。集成式电气屏蔽可提供出色的共模抑制和瞬态抗扰度。


输出电压与输入电流成正比，并具有多个灵敏度选项。固定的灵敏度允许 TMCS1107 使用单个 3V 至 5.5V 的电源运行，因此消除了比例式误差并提高了电源噪声抑制能力。当电流流入到正输入引脚时，电流极性被视为正极。可提供单向和双向感应型号。

TMCS1107 消耗的最大电源电流为 6mA，所有灵敏度选项的额定工作温度范围均为  $-40^{\circ}\text{C}$  至  $+125^{\circ}\text{C}$ 。

### 器件信息(1)

| 器件型号     | 封装       | 封装尺寸 (标称值)      |
|----------|----------|-----------------|
| TMCS1107 | SOIC (8) | 4.90mm × 3.90mm |

(1) 如需了解所有可用封装，请参阅数据表末尾的封装选项附录。



典型应用



## Table of Contents

|                                                  |           |                                                                  |           |
|--------------------------------------------------|-----------|------------------------------------------------------------------|-----------|
| <b>1 特性</b> .....                                | <b>1</b>  | 9.1 Overview.....                                                | <b>21</b> |
| <b>2 应用</b> .....                                | <b>1</b>  | 9.2 Functional Block Diagram.....                                | <b>21</b> |
| <b>3 说明</b> .....                                | <b>1</b>  | 9.3 Feature Description.....                                     | <b>21</b> |
| <b>4 Revision History</b> .....                  | <b>2</b>  | 9.4 Device Functional Modes.....                                 | <b>25</b> |
| <b>5 Device Comparison</b> .....                 | <b>3</b>  | <b>10 Application and Implementation</b> .....                   | <b>26</b> |
| <b>6 Pin Configuration and Functions</b> .....   | <b>3</b>  | 10.1 Application Information.....                                | <b>26</b> |
| <b>7 Specifications</b> .....                    | <b>4</b>  | 10.2 Typical Application.....                                    | <b>29</b> |
| 7.1 Absolute Maximum Ratings .....               | <b>4</b>  | <b>11 Power Supply Recommendations</b> .....                     | <b>31</b> |
| 7.2 ESD Ratings .....                            | <b>4</b>  | <b>12 Layout</b> .....                                           | <b>32</b> |
| 7.3 Recommended Operating Conditions .....       | <b>4</b>  | 12.1 Layout Guidelines.....                                      | <b>32</b> |
| 7.4 Thermal Information .....                    | <b>5</b>  | 12.2 Layout Example.....                                         | <b>33</b> |
| 7.5 Power Ratings .....                          | <b>5</b>  | <b>13 Device and Documentation Support</b> .....                 | <b>34</b> |
| 7.6 Insulation Specifications .....              | <b>6</b>  | 13.1 Device Support.....                                         | <b>34</b> |
| 7.7 Safety-Related Certifications .....          | <b>6</b>  | 13.2 Documentation Support.....                                  | <b>34</b> |
| 7.8 Safety Limiting Values .....                 | <b>7</b>  | 13.3 接收文档更新通知.....                                               | <b>34</b> |
| 7.9 Electrical Characteristics .....             | <b>8</b>  | 13.4 支持资源.....                                                   | <b>34</b> |
| 7.10 Typical Characteristics.....                | <b>11</b> | 13.5 Trademarks.....                                             | <b>34</b> |
| <b>8 Parameter Measurement Information</b> ..... | <b>14</b> | 13.6 Electrostatic Discharge Caution.....                        | <b>34</b> |
| 8.1 Accuracy Parameters.....                     | <b>14</b> | 13.7 术语表.....                                                    | <b>34</b> |
| 8.2 Transient Response Parameters.....           | <b>17</b> | <b>14 Mechanical, Packaging, and Orderable Information</b> ..... | <b>34</b> |
| 8.3 Safe Operating Area.....                     | <b>18</b> |                                                                  |           |
| <b>9 Detailed Description</b> .....              | <b>21</b> |                                                                  |           |

## 4 Revision History

注：以前版本的页码可能与当前版本的页码不同

| Changes from Revision * (January 2021) to Revision A (July 2021) | Page     |
|------------------------------------------------------------------|----------|
| • 更新了整个文档中的表格、图和交叉参考的编号格式.....                                   | <b>1</b> |

## 5 Device Comparison

表 5-1. Device Comparison

| PRODUCT     | SENSITIVITY                                | ZERO CURRENT OUTPUT VOLTAGE, | I <sub>IN</sub> LINEAR MEASUREMENT RANGE <sup>(1)</sup> |                                 |
|-------------|--------------------------------------------|------------------------------|---------------------------------------------------------|---------------------------------|
|             | $\Delta V_{OUT} / \Delta I_{IN+},$<br>IN - | V <sub>OUT,0A</sub>          | V <sub>S</sub> = 5 V                                    | V <sub>S</sub> = 3.3 V          |
| TMCS1107A1B | 50 mV/A                                    | 0.5 × V <sub>S</sub>         | ±46 A <sup>(2)</sup>                                    | ±29 A <sup>(2)</sup>            |
| TMCS1107A2B | 100 mV/A                                   |                              | ±23 A <sup>(2)</sup>                                    | ±14.5 A                         |
| TMCS1107A3B | 200 mV/A                                   |                              | ±11.5 A                                                 | ±7.25 A                         |
| TMCS1107A4B | 400 mV/A                                   |                              | ±5.75 A                                                 | --                              |
| TMCS1107A1U | 50 mV/A                                    | 0.1 × V <sub>S</sub>         | - 9 A → 86 A <sup>(2)</sup>                             | - 5.6 A → 55.4A <sup>(2)</sup>  |
| TMCS1107A2U | 100 mV/A                                   |                              | - 4.5 A → 43A <sup>(2)</sup>                            | - 2.8 A → 27.7 A <sup>(2)</sup> |
| TMCS1107A3U | 200 mV/A                                   |                              | - 2.25 A → 21.5 A <sup>(2)</sup>                        | - 1.4 A → 13.85 A               |
| TMCS1107A4U | 400 mV/A                                   |                              | - 1.12 A → 10.75 A                                      | --                              |

(1) Linear range limited by swing to supply and ground.

(2) Current levels must remain below both allowable continuous DC/RMS and transient peak current safe operating areas to not exceed device thermal limits. See [Safe Operating Area](#) section.

## 6 Pin Configuration and Functions




图 6-1. D Package 8-Pin SOIC Top View

表 6-1. Pin Functions

| PIN |      | I/O           | DESCRIPTION                                                                                                            |
|-----|------|---------------|------------------------------------------------------------------------------------------------------------------------|
| NO. | NAME |               |                                                                                                                        |
| 1   | IN+  | Analog input  | Input current positive pin                                                                                             |
| 2   | IN+  | Analog input  | Input current positive pin                                                                                             |
| 3   | IN - | Analog input  | Input current negative pin                                                                                             |
| 4   | IN - | Analog input  | Input current negative pin                                                                                             |
| 5   | GND  | Analog        | Ground                                                                                                                 |
| 6   | NC   | No Connect    | No connect. Pin can tolerate a capacitive or resistive connection to GND or VS (recommend short to GND if acceptable). |
| 7   | VOUT | Analog output | Output voltage                                                                                                         |
| 8   | VS   | Analog        | Power supply                                                                                                           |

## 7 Specifications

### 7.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted)<sup>(1)</sup>

|                  |                      | MIN       | MAX                     | UNIT |
|------------------|----------------------|-----------|-------------------------|------|
| V <sub>S</sub>   | Supply voltage       | GND - 0.3 | 6                       | V    |
|                  | NC Input             | GND - 0.3 | (V <sub>S</sub> ) + 0.3 | V    |
|                  | Analog output        | GND - 0.3 | (V <sub>S</sub> ) + 0.3 | V    |
| T <sub>J</sub>   | Junction temperature | - 65      | 150                     | °C   |
| T <sub>stg</sub> | Storage temperature  | - 65      | 150                     | °C   |

- (1) Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions*. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

### 7.2 ESD Ratings

|                    |                         |                                                                                | VALUE | UNIT |
|--------------------|-------------------------|--------------------------------------------------------------------------------|-------|------|
| V <sub>(ESD)</sub> | Electrostatic discharge | Human-body model (HBM), per ANSI/ESDA/JEDEC JS-001 <sup>(1)</sup>              | ±2000 | V    |
|                    |                         | Charged-device model (CDM), per JEDEC specification JESD22-C101 <sup>(2)</sup> | ±1000 |      |

- (1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.

- (2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

### 7.3 Recommended Operating Conditions

over operating free-air temperature range (unless otherwise noted)

|                                                    |                                               | MIN   | NOM | MAX | UNIT            |
|----------------------------------------------------|-----------------------------------------------|-------|-----|-----|-----------------|
| V <sub>IN+</sub> , V <sub>IN-</sub> <sup>(1)</sup> | Input voltage                                 | - 420 |     | 420 | V <sub>PK</sub> |
| V <sub>S</sub>                                     | Operating supply voltage, TMCS1107A1B/U-A3B/U | 3     | 5   | 5.5 | V               |
| V <sub>S</sub>                                     | Operating supply voltage, TMCS1107A4B/U       | 4.5   | 5   | 5.5 | V               |
| T <sub>A</sub> <sup>(2)</sup>                      | Operating free-air temperature                | - 40  |     | 125 | °C              |

- (1) V<sub>IN+</sub> and V<sub>IN-</sub> refer to the voltage at input current pins IN+ and IN-, relative to pin 5 (GND).

- (2) Input current safe operating area is constrained by junction temperature. Recommended condition based on the [TMCS1107EVM](#). Input current rating is derated for elevated ambient temperatures.

## 7.4 Thermal Information

| THERMAL METRIC <sup>(1)</sup> |                                              | TMCS1107 <sup>(2)</sup> | UNIT |
|-------------------------------|----------------------------------------------|-------------------------|------|
|                               |                                              | D (SOIC)                |      |
|                               |                                              | 8 PINS                  |      |
| $R_{\theta JA}$               | Junction-to-ambient thermal resistance       | 36.6                    | °C/W |
| $R_{\theta JC(top)}$          | Junction-to-case (top) thermal resistance    | 50.7                    | °C/W |
| $R_{\theta JB}$               | Junction-to-board thermal resistance         | 9.6                     | °C/W |
| $\Psi_{JT}$                   | Junction-to-top characterization parameter   | - 0.1                   | °C/W |
| $\Psi_{JB}$                   | Junction-to-board characterization parameter | 11.7                    | °C/W |
| $R_{\theta JC(bot)}$          | Junction-to-case (bottom) thermal resistance | N/A                     | °C/W |

- (1) For more information about traditional and new thermal metrics, see the [Semiconductor and IC Package Thermal Metrics](#) application report.
- (2) Applies when device mounted on [TMCS1107EVM](#). For more details, see the [Safe Operating Area](#) section.

## 7.5 Power Ratings

$V_S = 5.5\text{ V}$ ,  $T_A = 125^\circ\text{C}$ ,  $T_J = 150^\circ\text{C}$ , device soldered on [TMCS1107EVM](#).

| PARAMETER |                                                   | TEST CONDITIONS                                           | MIN | TYP | MAX | UNIT |
|-----------|---------------------------------------------------|-----------------------------------------------------------|-----|-----|-----|------|
| $P_D$     | Maximum power dissipation (both sides)            |                                                           |     |     | 673 | mW   |
| $P_{D1}$  | Maximum power dissipation (current input, side-1) | $I_{IN} = 16\text{ A}$                                    |     |     | 640 | mW   |
| $P_{D2}$  | Maximum power dissipation by (side-2)             | $V_S = 5.5\text{ V}$ , $I_Q = 6\text{ mA}$ , no VOUT load |     |     | 33  | mW   |

## 7.6 Insulation Specifications

| PARAMETER      |                                                      | TEST CONDITIONS                                                                                                                                                                                                 | VALUE      | UNIT      |
|----------------|------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|-----------|
| <b>GENERAL</b> |                                                      |                                                                                                                                                                                                                 |            |           |
| CLR            | External clearance <sup>(1)</sup>                    | Shortest terminal-to-terminal distance through air                                                                                                                                                              | 4          | mm        |
| CPG            | External creepage <sup>(1)</sup>                     | Shortest terminal-to-terminal distance across the package surface                                                                                                                                               | 4          | mm        |
| DTI            | Distance through the insulation                      | Minimum internal gap (internal clearance)                                                                                                                                                                       | 60         | μm        |
| CTI            | Comparative tracking index                           | DIN EN 60112; IEC 60112                                                                                                                                                                                         | >400       | V         |
|                | Material group                                       |                                                                                                                                                                                                                 | II         |           |
|                | Overvoltage category                                 | Rated mains voltage $\leq 150 V_{RMS}$                                                                                                                                                                          | I-IV       |           |
|                |                                                      | Rated mains voltage $\leq 300 V_{RMS}$                                                                                                                                                                          | I-III      |           |
| $V_{IORM}$     | Maximum repetitive peak isolation voltage            | AC voltage (bipolar)                                                                                                                                                                                            | 420        | $V_{PK}$  |
| $V_{IOWM}$     | Maximum working isolation voltage                    | AC voltage (sine wave); Time Dependent Dielectric Breakdown test, see                                                                                                                                           | 297        | $V_{RMS}$ |
|                |                                                      | DC voltage                                                                                                                                                                                                      | 420        | $V_{DC}$  |
| $V_{IOTM}$     | Maximum transient isolation voltage                  | $V_{TEST} = V_{IOTM} = 4242V_{PK}$ , $t = 60$ s (qualification);<br>$V_{TEST} = 1.2 \times V_{IOTM} = 5090V_{PK}$ , $t = 1$ s (100% production)                                                                 | 4242       | $V_{PK}$  |
| $V_{IOSM}$     | Maximum surge isolation voltage <sup>(2)</sup>       | Test method per IEC 62368-1, 1.2/50 μs waveform,<br>$V_{TEST} = 1.3 \times V_{IOSM} = 7800V_{PK}$ (qualification)                                                                                               | 6000       | $V_{PK}$  |
| $q_{pd}$       | Apparent charge <sup>(3)</sup>                       | Method a: After I/O safety test subgroup 2/3,<br>$V_{ini} = V_{IOTM} = 4242V_{PK}$ , $t_{ini} = 60$ s;<br>$V_{pd(m)} = 1.2 \times V_{IORM} = 700V_{PK}$ , $t_m = 10$ s                                          | $\leq 5$   | pC        |
|                |                                                      | Method a: After environmental tests subgroup 1,<br>$V_{ini} = V_{IOTM} = 4242V_{PK}$ , $t_{ini} = 60$ s;<br>$V_{pd(m)} = 1.2 \times V_{IORM} = 700V_{PK}$ , $t_m = 10$ s                                        | $\leq 5$   |           |
|                |                                                      | Method b3: At routine test (100% production) and preconditioning (type test)<br>$V_{ini} = 1.2 \times V_{IOTM} = 5090V_{PK}$ , $t_{ini} = 1$ s;<br>$V_{pd(m)} = 1.2 \times V_{IOTM} = 5090V_{PK}$ , $t_m = 1$ s | $\leq 5$   |           |
| $C_{IO}$       | Barrier capacitance, input to output <sup>(4)</sup>  | $V_{IO} = 0.4 \sin(2\pi ft)$ , $f = 1$ MHz                                                                                                                                                                      | 0.6        | pF        |
| $R_{IO}$       | Isolation resistance, input to output <sup>(4)</sup> | $V_{IO} = 500$ V, $T_A = 25^\circ\text{C}$                                                                                                                                                                      | $>10^{12}$ | $\Omega$  |
|                |                                                      | $V_{IO} = 500$ V, $100^\circ\text{C} \leq T_A \leq 125^\circ\text{C}$                                                                                                                                           | $>10^{11}$ | $\Omega$  |
|                |                                                      | $V_{IO} = 500$ V at $T_S = 150^\circ\text{C}$                                                                                                                                                                   | $>10^9$    | $\Omega$  |
|                | Pollution degree                                     |                                                                                                                                                                                                                 | 2          |           |
| <b>UL 1577</b> |                                                      |                                                                                                                                                                                                                 |            |           |
| $V_{ISO}$      | Withstand isolation voltage                          | $V_{TEST} = V_{ISO}$ , $t = 60$ s (qualification); $V_{TEST} = 1.2 \times V_{ISO}$ ,<br>$t = 1$ s (100% production)                                                                                             | 3000       | $V_{RMS}$ |

- (1) Apply creepage and clearance requirements according to the specific equipment isolation standards of an application. Take care to maintain the creepage and clearance distance of the board design to make sure that the mounting pads of the isolator on the printed-circuit board do not reduce this distance. Creepage and clearance on a printed-circuit board become equal in certain cases. Techniques such as inserting grooves, ribs, or both on a printed circuit board are used to help increase these specifications.
- (2) Testing is carried out in air or oil to determine the intrinsic surge immunity of the isolation barrier.
- (3) Apparent charge is electrical discharge caused by a partial discharge (pd).
- (4) All pins on each side of the barrier tied together creating a two-terminal device

## 7.7 Safety-Related Certifications

| UL                                    |                                       |
|---------------------------------------|---------------------------------------|
| UL 1577 Component Recognition Program | Certified according to IEC 62368-1 CB |
| File number: E181974                  | Certificate number: US-36733-UL       |

## 7.8 Safety Limiting Values

Safety limiting intends to minimize potential damage to the isolation barrier upon failure of input or output circuitry.

| PARAMETER |                                                                 | TEST CONDITIONS                                                                                                                                 | MIN | TYP | MAX  | UNIT             |
|-----------|-----------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|-----|-----|------|------------------|
| $I_S$     | Safety input current (side 1) <sup>(1)</sup>                    | $R_{\theta JA} = 36.6^\circ\text{C/W}$ , $T_J = 150^\circ\text{C}$ , $T_A = 25^\circ\text{C}$ , see <a href="#">图 7-14</a>                      |     |     | 30   | A                |
| $I_S$     | Safety input, output, or supply current (side 2) <sup>(1)</sup> | $R_{\theta JA} = 36.6^\circ\text{C/W}$ , $V_I = 5\text{ V}$ , $T_J = 150^\circ\text{C}$ , $T_A = 25^\circ\text{C}$ , see <a href="#">图 7-15</a> |     |     | 0.68 |                  |
| $P_S$     | Safety input, output, or total power <sup>(1)</sup>             | $R_{\theta JA} = 36.6^\circ\text{C/W}$ , $T_J = 150^\circ\text{C}$ , $T_A = 25^\circ\text{C}$ , see <a href="#">图 7-16</a>                      |     |     | 3.4  | W                |
| $T_S$     | Safety temperature <sup>(1)</sup>                               |                                                                                                                                                 |     |     | 150  | $^\circ\text{C}$ |

- (1) The maximum safety temperature,  $T_S$ , has the same value as the maximum junction temperature,  $T_J$ , specified for the device. The  $I_S$  and  $P_S$  parameters represent the safety current and safety power respectively. The maximum limits of  $I_S$  and  $P_S$  should not be exceeded. These limits vary with the ambient temperature,  $T_A$ .  
The junction-to-air thermal resistance,  $R_{\theta JA}$ , in the [Thermal Information](#) table is that of a device installed on the [TMCS1107EVM](#). Use these equations to calculate the value for each parameter:  
 $T_J = T_A + R_{\theta JA} \times P$ , where  $P$  is the power dissipated in the device.  
 $T_{J(max)} = T_S = T_A + R_{\theta JA} \times P_S$ , where  $T_{J(max)}$  is the maximum allowed junction temperature.  
 $P_S = I_S \times V_I$ , where  $V_I$  is the maximum input voltage.

## 7.9 Electrical Characteristics

at  $T_A = 25^\circ\text{C}$ ,  $V_S = 5\text{ V}$  (unless otherwise noted)

| PARAMETERS      |                                                                              | TEST CONDITIONS                                                                                                      | MIN | TYP         | MAX          | UNIT                         |
|-----------------|------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-----|-------------|--------------|------------------------------|
| <b>OUTPUT</b>   |                                                                              |                                                                                                                      |     |             |              |                              |
|                 | Sensitivity <sup>(7)</sup>                                                   | TMCS1107A1B                                                                                                          |     | 50          |              | mV/A                         |
|                 |                                                                              | TMCS1107A2B                                                                                                          |     | 100         |              | mV/A                         |
|                 |                                                                              | TMCS1107A3B                                                                                                          |     | 200         |              | mV/A                         |
|                 |                                                                              | TMCS1107A4B                                                                                                          |     | 400         |              | mV/A                         |
|                 |                                                                              | TMCS1107A1U                                                                                                          |     | 50          |              | mV/A                         |
|                 |                                                                              | TMCS1107A2U                                                                                                          |     | 100         |              | mV/A                         |
|                 |                                                                              | TMCS1107A3U                                                                                                          |     | 200         |              | mV/A                         |
|                 |                                                                              | TMCS1107A4U                                                                                                          |     | 400         |              | mV/A                         |
|                 | Sensitivity error                                                            | $0.05\text{ V} \leq V_{\text{OUT}} \leq V_S - 0.2\text{ V}$ , $T_A = 25^\circ\text{C}$                               |     | $\pm 0.4\%$ | $\pm 1.2\%$  |                              |
|                 |                                                                              | TMCS1107A1U, $0.05\text{ V} \leq V_{\text{OUT}} \leq 3\text{ V}$ , $T_A = 25^\circ\text{C}$                          |     | $\pm 0.4\%$ | $\pm 1.2\%$  |                              |
|                 | Sensitivity error, including lifetime and environmental drift <sup>(5)</sup> | $0.05\text{ V} \leq V_{\text{OUT}} \leq V_S - 0.2\text{ V}$ , $T_A = 25^\circ\text{C}$                               |     | $\pm 0.7\%$ | $\pm 1.8\%$  |                              |
|                 | Sensitivity error                                                            | $0.05\text{ V} \leq V_{\text{OUT}} \leq V_S - 0.2\text{ V}$ , $T_A = -40^\circ\text{C}$ to $+85^\circ\text{C}$       |     | $\pm 0.7\%$ | $\pm 1.8\%$  |                              |
|                 |                                                                              | TMCS1107A1U, $0.05\text{ V} \leq V_{\text{OUT}} \leq 3\text{ V}$ , $T_A = -40^\circ\text{C}$ to $+85^\circ\text{C}$  |     | $\pm 0.7\%$ | $\pm 1.8\%$  |                              |
|                 |                                                                              | $0.05\text{ V} \leq V_{\text{OUT}} \leq V_S - 0.2\text{ V}$ , $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$      |     | $\pm 0.9\%$ | $\pm 2.25\%$ |                              |
|                 |                                                                              | TMCS1107A1U, $0.05\text{ V} \leq V_{\text{OUT}} \leq 3\text{ V}$ , $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$ |     | $\pm 0.9\%$ | $\pm 2.25\%$ |                              |
|                 | Nonlinearity error                                                           | $V_{\text{OUT}} = 0.5\text{ V}$ to $V_S - 0.5\text{ V}$                                                              |     | $\pm 0.5\%$ |              |                              |
|                 |                                                                              | TMCS1107A1U, $V_{\text{OUT}} = 0.5\text{ V}$ to $3\text{ V}$                                                         |     | $\pm 0.5\%$ |              |                              |
| $V_{\text{OE}}$ | Output voltage offset error <sup>(1)</sup>                                   | TMCS1107A1B                                                                                                          |     | $\pm 2$     | $\pm 8$      | mV                           |
|                 |                                                                              | TMCS1107A2B                                                                                                          |     | $\pm 2$     | $\pm 10$     | mV                           |
|                 |                                                                              | TMCS1107A3B                                                                                                          |     | $\pm 3$     | $\pm 12$     | mV                           |
|                 |                                                                              | TMCS1107A4B                                                                                                          |     | $\pm 5$     | $\pm 30$     | mV                           |
|                 |                                                                              | TMCS1107A1U                                                                                                          |     | $\pm 2$     | $\pm 8$      | mV                           |
|                 |                                                                              | TMCS1107A2U                                                                                                          |     | $\pm 2$     | $\pm 10$     | mV                           |
|                 |                                                                              | TMCS1107A3U                                                                                                          |     | $\pm 5$     | $\pm 12$     | mV                           |
|                 |                                                                              | TMCS1107A4U                                                                                                          |     | $\pm 15$    | $\pm 30$     | mV                           |
|                 | Output voltage offset drift                                                  | TMCS1107A1B, $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$                                                       |     | $\pm 10$    | $\pm 30$     | $\mu\text{V}/^\circ\text{C}$ |
|                 |                                                                              | TMCS1107A2B, $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$                                                       |     | $\pm 10$    | $\pm 40$     | $\mu\text{V}/^\circ\text{C}$ |
|                 |                                                                              | TMCS1107A3B, $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$                                                       |     | $\pm 15$    | $\pm 80$     | $\mu\text{V}/^\circ\text{C}$ |
|                 |                                                                              | TMCS1107A4B, $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$                                                       |     | $\pm 40$    | $\pm 170$    | $\mu\text{V}/^\circ\text{C}$ |
|                 |                                                                              | TMCS1107A1U, $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$                                                       |     | $\pm 10$    | $\pm 30$     | $\mu\text{V}/^\circ\text{C}$ |
|                 |                                                                              | TMCS1107A2U, $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$                                                       |     | $\pm 10$    | $\pm 40$     | $\mu\text{V}/^\circ\text{C}$ |
|                 |                                                                              | TMCS1107A3U, $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$                                                       |     | $\pm 20$    | $\pm 80$     | $\mu\text{V}/^\circ\text{C}$ |
|                 |                                                                              | TMCS1107A4U, $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$                                                       |     | $\pm 50$    | $\pm 170$    | $\mu\text{V}/^\circ\text{C}$ |

at  $T_A = 25^\circ\text{C}$ ,  $V_S = 5\text{ V}$  (unless otherwise noted)

| PARAMETERS          |                                                    | TEST CONDITIONS                                                                   | MIN | TYP                | MAX  | UNIT      |
|---------------------|----------------------------------------------------|-----------------------------------------------------------------------------------|-----|--------------------|------|-----------|
| I <sub>OS</sub>     | Offset error, RTI <sup>(1) (3)</sup>               | TMCS1107A1B                                                                       |     | ±40                | ±160 | mA        |
|                     |                                                    | TMCS1107A2B                                                                       |     | ±20                | ±100 | mA        |
|                     |                                                    | TMCS1107A3B                                                                       |     | ±15                | ±60  | mA        |
|                     |                                                    | TMCS1107A4B                                                                       |     | ±12.5              | ±75  | mA        |
|                     |                                                    | TMCS1107A1U                                                                       |     | ±40                | ±160 | mA        |
|                     |                                                    | TMCS1107A2U                                                                       |     | ±20                | ±100 | mA        |
|                     |                                                    | TMCS1107A3U                                                                       |     | ±25                | ±60  | mA        |
|                     |                                                    | TMCS1107A4U                                                                       |     | ±37.5              | ±75  | mA        |
|                     | Offset error temperature drift, RTI <sup>(3)</sup> | TMCS1107A1B, T <sub>A</sub> = - 40°C to +125°C                                    |     | ±200               | ±600 | µA/°C     |
|                     |                                                    | TMCS1107A2B, T <sub>A</sub> = - 40°C to +125°C                                    |     | ±100               | ±400 | µA/°C     |
|                     |                                                    | TMCS1107A3B, T <sub>A</sub> = - 40°C to +125°C                                    |     | ±75                | ±400 | µA/°C     |
|                     |                                                    | TMCS1107A4B, T <sub>A</sub> = - 40°C to +125°C                                    |     | ±100               | ±425 | µA/°C     |
|                     |                                                    | TMCS1107A1U, T <sub>A</sub> = - 40°C to +125°C                                    |     | ±200               | ±600 | µA/°C     |
|                     |                                                    | TMCS1107A2U, T <sub>A</sub> = - 40°C to +125°C                                    |     | ±100               | ±400 | µA/°C     |
|                     |                                                    | TMCS1107A3U, T <sub>A</sub> = - 40°C to +125°C                                    |     | ±100               | ±400 | µA/°C     |
|                     |                                                    | TMCS1107A4U, T <sub>A</sub> = - 40°C to +125°C                                    |     | ±125               | ±425 | µA/°C     |
| PSRR                | Power-supply rejection ratio                       | V <sub>S</sub> = 3 V to 5.5 V, T <sub>A</sub> = - 40°C to +125°C                  |     | ±1                 | ±6.5 | mV/V      |
|                     |                                                    | TMCS1107A4B/U, V <sub>S</sub> = 4.5 V to 5.5 V, T <sub>A</sub> = - 40°C to +125°C |     | ±1                 | ±6.5 | mV/V      |
| CMTI                | Common mode transient immunity                     |                                                                                   |     | 50                 |      | kV/µs     |
| CMRR                | Common mode rejection ratio, RTI <sup>(3)</sup>    | DC to 60Hz                                                                        |     | 5                  |      | uA/V      |
|                     | Zero current V <sub>OUT</sub> <sup>(1)</sup>       | TMCS1107AxU                                                                       |     | 0.1*V <sub>S</sub> |      | V/V       |
|                     |                                                    | TMCS1107AxB                                                                       |     | 0.5*V <sub>S</sub> |      | V/V       |
|                     | Noise density, RTI <sup>(3)</sup>                  | TMCS1107A1B                                                                       |     | 380                |      | µ A/ √ Hz |
|                     |                                                    | TMCS1107A2B                                                                       |     | 330                |      | µ A/ √ Hz |
|                     |                                                    | TMCS1107A3B                                                                       |     | 300                |      | µ A/ √ Hz |
|                     |                                                    | TMCS1107A4B                                                                       |     | 225                |      | µ A/ √ Hz |
|                     |                                                    | TMCS1107A1U                                                                       |     | 380                |      | µ A/ √ Hz |
|                     |                                                    | TMCS1107A2U                                                                       |     | 330                |      | µ A/ √ Hz |
|                     |                                                    | TMCS1107A3U                                                                       |     | 300                |      | µ A/ √ Hz |
|                     |                                                    | TMCS1107A4U                                                                       |     | 225                |      | µ A/ √ Hz |
| INPUT               |                                                    |                                                                                   |     |                    |      |           |
| R <sub>IN</sub>     | Input conductor resistance                         | IN+ to IN -                                                                       |     | 1.8                |      | mΩ        |
|                     | Input conductor resistance temperature drift       | T <sub>A</sub> = - 40°C to +125°C                                                 |     | 4.4                |      | µ Ω/°C    |
| G                   | Magnetic coupling factor                           | T <sub>A</sub> = 25°C                                                             |     | 1.1                |      | mT/A      |
| I <sub>IN,max</sub> | Allowable continuous RMS current <sup>(4)</sup>    | T <sub>A</sub> = 25°C                                                             |     | 30                 |      | A         |
|                     |                                                    | T <sub>A</sub> = 85°C                                                             |     | 25                 |      | A         |
|                     |                                                    | T <sub>A</sub> = 105°C                                                            |     | 22.5               |      | A         |
|                     |                                                    | T <sub>A</sub> = 125°C                                                            |     | 16                 |      | A         |
|                     | NC (Pin 6) input impedance                         | Over allowable range, GND < V <sub>NC</sub> < V <sub>S</sub>                      | 1   |                    |      | MΩ        |
| VOLTAGE OUTPUT      |                                                    |                                                                                   |     |                    |      |           |
| Z <sub>OUT</sub>    | Closed loop output impedance                       | f = 1 Hz to 1 kHz                                                                 |     | 0.2                |      | Ω         |
|                     |                                                    | f = 10 kHz                                                                        |     | 2                  |      | Ω         |
|                     | Maximum capacitive load                            | No sustained oscillation                                                          |     | 1                  |      | nF        |

at  $T_A = 25^\circ\text{C}$ ,  $V_S = 5\text{ V}$  (unless otherwise noted)

| PARAMETERS                |                                                   | TEST CONDITIONS                                                                                                                                                                      | MIN                  | TYP          | MAX                   | UNIT             |
|---------------------------|---------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|--------------|-----------------------|------------------|
|                           | Short circuit output current                      | VOOUT short to ground, short to $V_S$                                                                                                                                                |                      | 90           |                       | mA               |
|                           | Swing to $V_S$ power-supply rail                  | $R_L = 10\text{ k}\Omega$ to GND, $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$                                                                                                  |                      | $V_S - 0.02$ | $V_S - 0.1$           | V                |
|                           | Swing to GND                                      | $R_L = 10\text{ k}\Omega$ to GND, $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$                                                                                                  | $V_{\text{GND}} + 5$ |              | $V_{\text{GND}} + 10$ | mV               |
| <b>FREQUENCY RESPONSE</b> |                                                   |                                                                                                                                                                                      |                      |              |                       |                  |
| BW                        | Bandwidth <sup>(6)</sup>                          | - 3-dB Bandwidth                                                                                                                                                                     |                      | 80           |                       | kHz              |
| SR                        | Slew rate <sup>(6)</sup>                          | Slew rate of output amplifier during single transient step.                                                                                                                          |                      | 1.5          |                       | V/ $\mu\text{s}$ |
| $t_r$                     | Response time <sup>(6)</sup>                      | Time between the input current step reaching 90% of final value to the sensor output reaching 90% of its final value, for a 1V output transition.                                    |                      | 6.5          |                       | $\mu\text{s}$    |
| $t_p$                     | Propagation delay <sup>(6)</sup>                  | Time between the input current step reaching 10% of final value to the sensor output reaching 10% of its final value, for a 1V output transition.                                    |                      | 4            |                       | $\mu\text{s}$    |
| $t_{r,SC}$                | Current overload response time <sup>(6)</sup>     | Time between the input current step reaching 90% of final value to the sensor output reaching 90% of its final value. Input current step amplitude is twice full scale output range. |                      | 5            |                       | $\mu\text{s}$    |
| $t_{p,SC}$                | Current overload propagation delay <sup>(6)</sup> | Time between the input current step reaching 10% of final value to the sensor output reaching 10% of its final value. Input current step amplitude is twice full scale output range. |                      | 3            |                       | $\mu\text{s}$    |
|                           | Current overload recovery time                    | Time from end of current causing output saturation condition to valid output                                                                                                         |                      | 15           |                       | $\mu\text{s}$    |
| <b>POWER SUPPLY</b>       |                                                   |                                                                                                                                                                                      |                      |              |                       |                  |
| $I_Q$                     | Quiescent current                                 | $T_A = 25^\circ\text{C}$                                                                                                                                                             |                      | 4.5          | 5.5                   | mA               |
|                           |                                                   | $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$                                                                                                                                    |                      |              | 6                     | mA               |
|                           | Power on time                                     | Time from $V_S > 3\text{ V}$ to valid output                                                                                                                                         |                      | 25           |                       | ms               |

- (1) Excludes effect of external magnetic fields. See the [Accuracy Parameters](#) section for details to calculate error due to external magnetic fields.
- (2) Excluding magnetic coupling from layout deviation from recommended layout. See the [Layout](#) section for more information.
- (3) RTI = referred-to-input. Output voltage is divided by device sensitivity to refer signal to input current. See the [Parameter Measurement Information](#) section.
- (4) Thermally limited by junction temperature. Applies when device mounted on [TMCS1107EVM](#). For more details, see the [Safe Operating Area](#) section.
- (5) Lifetime and environmental drift specifications based on three lot AEC-Q100 qualification stress test results. Typical values are population mean  $\pm 1\sigma$  from worst case stress test condition. Min/max are tested device population mean  $\pm 6\sigma$ ; devices tested in AEC-Q100 qualification stayed within min/max limits for all stress conditions. See [Lifetime and Environmental Stability](#) section for more details.
- (6) Refer to the [Transient Response](#) section for details of frequency and transient response of the device.
- (7) Centered parameter based on [TMCS1107EVM](#) PCB layout. See [Layout](#) section. Device must be operated below maximum junction temperature.

## 7.10 Typical Characteristics




图 7-1. TMCS1107 Sensitivity Error vs. Temperature




图 7-2. TMCS1107 Input Offset Current vs. Temperature




图 7-3. Sensitivity vs. Frequency, All Gains Normalized to 1 Hz




图 7-4. Phase vs. Frequency, All Gains




图 7-5. Output Swing vs. Output Current




图 7-6. Output Impedance vs. Frequency

## 7.10 Typical Characteristics (continued)




图 7-7. Quiescent Current vs. Temperature




图 7-8. Input-Referred Noise vs. Frequency




图 7-9. Voltage Output Step, Rising




图 7-10. Voltage Output Step, Falling




图 7-11. Current Overload Response




图 7-12. Startup Transient Response

## 7.10 Typical Characteristics (continued)




图 7-13. Input Conductor Resistance vs. Temperature

### 7.10.1 Insulation Characteristics Curves




图 7-14. Thermal Derating Curve for Safety-Limiting Current, Side 1




图 7-15. Thermal Derating Curve for Safety-Limiting Current, Side 2




图 7-16. Thermal Derating Curve for Safety-Limiting Power

## 8 Parameter Measurement Information

### 8.1 Accuracy Parameters

The ideal first-order transfer function of the TMCS1107 is given by 方程式 1, where the output voltage is a linear function of input current. The accuracy of the device is quantified both by the error terms in the transfer function parameters, as well as by nonidealities that introduce additional error terms not in the simplified linear model. See [Total Error Calculation Examples](#) for example calculations of total error, including all device error terms.

$$V_{OUT} = S \times I_{IN} + V_{OUT,0A} \quad (1)$$

where

- $V_{OUT}$  is the analog output voltage.
- $S$  is the ideal sensitivity of the device.
- $I_{IN}$  is the isolated input current.
- $V_{OUT,0A}$  is the zero current output voltage for the device variant.

#### 8.1.1 Sensitivity Error

Sensitivity is the proportional change in the sensor output voltage due to a change in the input conductor current. This sensitivity is the slope of the first-order transfer function of the sensor, as shown in 图 8-1. The sensitivity of the TMCS1107 is tested and calibrated at the factory for high accuracy.




图 8-1. Sensitivity, Offset, and Nonlinearity Error

Deviation from ideal sensitivity is quantified by sensitivity error, defined as the percent variation of the best-fit measured sensitivity from the ideal sensitivity. When specified over a temperature range, this is the worst-case sensitivity error at any temperature within the range.

$$e_S = [(S_{fit} - S_{ideal}) / S_{ideal}] \times 100\% \quad (2)$$

where

- $e_S$  is the sensitivity error.
- $S_{fit}$  is the best fit sensitivity.
- $S_{ideal}$  is the ideal sensitivity.

#### 8.1.2 Offset Error and Offset Error Drift

Offset error is the deviation from the ideal output voltage with zero input current through the device. Offset error can be referred to the output as a voltage error  $V_{OE}$  or referred to the input as a current offset error  $I_{OS}$ . Offset error is a single error source, however, and must only be included once in error calculations.

The output voltage offset error of the TMCS1107 is the deviation of the measured  $V_{OUT}$  with zero input current from the ideal value of the zero current output voltage. This ideal voltage is either 10% of  $V_S$  for unidirectional devices (AxU) or 50% of  $V_S$  for bidirectional devices (AxB), as shown in 方程式 3 and 方程式 4, respectively.

$$V_{OE} = V_{OUT,0A} - V_S * 0.1 \quad (3)$$

$$V_{OE} = V_{OUT,0A} - V_S * 0.5 \quad (4)$$

where

- $V_{OUT,0A}$  is the device output voltage with zero input current.

The offset error includes errors in the internal reference, the magnetic offset of the Hall sensor and any offset voltage errors of the signal chain.

The input referred (RTI) offset error is the output voltage offset error divided by the sensitivity of the device, shown in 方程式 5. Refer the offset error to the input of the device to allow for easier total error calculations and direct comparison to input current levels. No matter how the calculations are done, the error sources quantified by  $V_{OE}$  and  $I_{OS}$  are the same, and should only be included once for error calculations.

$$I_{OS} = V_{OE} / S \quad (5)$$

Offset error drift is the change in the input-referred offset error per degree Celsius change in ambient temperature. This parameter is reported in  $\mu A/^{\circ}C$ . To convert offset drift to an absolute offset for a given change in temperature, multiply the drift by the change in temperature and convert to percentage, as in 方程式 6.

$$e_{I_{OS},\Delta T} (\%) = \frac{I_{OS,25^{\circ}C} + I_{OS,drift} \left( \frac{\mu A}{^{\circ}C} \right) \times \Delta T}{I_{IN}} \quad (6)$$

where

- $I_{OS,drift}$  is the specified input-referred device offset drift.
- $\Delta T$  is the temperature range from  $25^{\circ}C$ .

### 8.1.3 Nonlinearity Error

Nonlinearity is the deviation of the output voltage from a linear relationship to the input current. Nonlinearity voltage, as shown in 图 8-1, is the maximum voltage deviation from the best-fit line based on measured parameters, calculated by 方程式 7.

$$V_{NL} = V_{OUT,MEAS} - (I_{MEAS} \times S_{fit} + V_{OUT,0A}) \quad (7)$$

where

- $V_{OUT,MEAS}$  is the voltage output at maximum deviation from best fit.
- $I_{MEAS}$  is the input current at maximum deviation from best fit.
- $S_{fit}$  is the best-fit sensitivity of the device.
- $V_{OUT,0A}$  is the device zero current output voltage.

Nonlinearity error ( $e_{NL}$ ) for the TMCS1107 is the nonlinearity voltage specified as a percentage of the full-scale output range ( $V_{FS}$ ), as shown in 方程式 8.

$$e_{NL} = 100\% * \frac{V_{NL}}{V_{FS}} \quad (8)$$

### 8.1.4 Power Supply Rejection Ratio

Power supply rejection ratio (PSRR) is the change in device offset due to variation of supply voltage from the nominal 5 V. The error contribution at the input current of interest can be calculated by [方程式 9](#).

$$e_{\text{PSRR}}(\%) = \left| \frac{\text{PSRR} * (V_S - 5)}{S} \right| \frac{1}{I_{\text{IN}}} \quad (9)$$

where

- $V_S$  is the operational supply voltage.
- $S$  is the device sensitivity.

### 8.1.5 Common-Mode Rejection Ratio

Common-mode rejection ratio (CMRR) quantifies the effective input current error due to a varying voltage on the isolated input of the device. Due to magnetic coupling and galvanic isolation of the current signal, the TMCS1107 has very high rejection of input common-mode voltage. Percent error contribution from input common-mode variation can be calculated by [方程式 10](#).

$$e_{\text{CMRR}}(\%) = \left| \frac{\text{CMRR} * V_{\text{CM}}}{I_{\text{IN}}} \right| \quad (10)$$

where

- $V_{\text{CM}}$  is the maximum operational AC or DC voltage on the input of the device.

### 8.1.6 External Magnetic Field Errors

The TMCS1107 does not have stray field-rejection capabilities, so external magnetic fields from adjacent high-current traces or nearby magnets can impact the output measurement. The total sensitivity ( $S$ ) of the device is comprised of the initial transformation of input current to magnetic field quantified as the magnetic coupling factor ( $G$ ), as well as the sensitivity of the Hall element and the analog circuitry that is factory calibrated to provide a final sensitivity. The output voltage is proportional to the input current by the device sensitivity, as defined in [方程式 11](#).

$$S = G * S_{\text{Hall}} * A_V \quad (11)$$

where

- $S$  is the TMCS1107 sensitivity in mV/A.
- $G$  is the magnetic coupling factor in mT/A.
- $S_{\text{Hall}}$  is the sensitivity of the Hall plate in mV/mT.
- $A_V$  is the calibrated analog circuitry gain in V/V.

An external field,  $B_{\text{EXT}}$ , is measured by the Hall sensor and signal chain, in addition to the field generated by the leadframe current, and is added as an extra input term in the total output voltage function:

$$V_{\text{OUT}} = B_{\text{EXT}} * S_{\text{Hall}} * A_V + I_{\text{IN}} * G * S_{\text{Hall}} * A_V + V_{\text{OUT},0A} \quad (12)$$

Observable from [方程式 12](#) is that the impact of an external field is an additional equivalent input current signal,  $I_{\text{BEXT}}$ , shown in [方程式 13](#). This effective additional input current has no dependence on Hall or analog circuitry sensitivity, so all gain variants have equivalent input-referred current error due to external magnetic fields.

$$I_{B\_EXT} = \frac{B_{EXT}}{G} \quad (13)$$

This additional current error generates a percentage error defined by 方程式 14.

$$e_{B\_EXT}(\%) = \frac{\left| \frac{B_{EXT}}{G} \right|}{I_{IN}} \quad (14)$$

## 8.2 Transient Response Parameters

The transient response of the TMCS1107 is impacted by the 250 kHz sampling rate as defined in [Transient Response](#). 图 8-2 shows the TMCS1107 response to an input current step sufficient to generate a 1-V output change. The typical 4-μs sampling window can be observed as a periodic step. This sampling window dominates the response of the device, and the response will have some probabilistic nature due to alignment of the input step and the sampling window interval.




图 8-2. Transient Step Response

### 8.2.1 Slew Rate

Slew rate (SR) is defined as the  $V_{OUT}$  rate of change for a single integration step's output transition, as shown in 图 8-3. Because the device often requires two sampling windows to reach a full 90% settling of its final value, this slew rate is not equal to the 10%-90% transition time for the full output swing.




图 8-3. Small Current Input Step Transient Response

### 8.2.2 Propagation Delay and Response Time

Propagation delay is the time period between the input current waveform reaching 10% of its final value and  $V_{OUT}$  reaching 10% of its final value. This propagation delay is heavily dependent upon the alignment of the input current step and the sampling period of the TMCS1107, as shown for several different sampling window cases in 图 8-3.

Response time is the time period between the input current reaching 90% of its final value and the output reaching 90% of its final value, for an input current step sufficient to cause a 1-V transition on the output. 图 8-3

shows the response time of the TMCS1107 under three different time cases. Unless a step input occurs directly during the beginning of one sampling window the response time will include two sampling intervals.

### 8.2.3 Current Overload Parameters

Current overload response parameters are the transient behavior of the TMCS1107 to an input current step consistent with a short circuit or fault event. Tested amplitude is twice the full scale range of the device, or 10V / Sensitivity in V/A. Under these conditions, the TMCS1107 output will respond faster than in the case of a small input current step due to the higher input amplitude signal. Response time and propagation delay are measured in a similar manner to the case of a small input current step, as shown in 图 8-4.




图 8-4. Current Overload Transient Response

Current overload recovery time is the required time for the device output to exit a saturated condition and return to normal operation. The transient response of the device during this recovery period from a current overload is shown in 图 7-11.

### 8.2.4 CMTI, Common-Mode Transient Immunity

CMTI is the capability of the device to tolerate a rising/falling voltage step on the input without disturbance on the output signal. The device is specified for the maximum common-mode transition rate under which the output signal will not experience a greater than 200-mV disturbance that lasts longer than 1 μs. Higher edge rates than the specified CMTI can be supported with sufficient filtering or blanking time after common-mode transitions.


## 8.3 Safe Operating Area

The isolated input current safe operating area (SOA) of the TMCS1107 is constrained by self-heating due to power dissipation in the input conductor. Depending upon use case, the SOA is constrained by multiple conditions, including exceeding maximum junction temperature, Joule heating in the leadframe, or leadframe fusing under extremely high currents. These mechanisms depend on pulse duration, amplitude, and device thermal states.

Current SOA strongly depends on the thermal environment and design of the system-level board. Multiple thermal variables control the transfer of heat from the device to the surrounding environment, including air flow, ambient temperature, and PCB construction and design. All ratings are for a single TMCS1107 device on the [TMCS1107EVM](#), with no air flow in the specified ambient temperature conditions. Device use profiles must satisfy both continuous conduction and short-duration transient SOA capabilities for the thermal environment under which the system will be operated.

### 8.3.1 Continuous DC or Sinusoidal AC Current

The longest thermal time constants of device packaging and PCB are on the order of seconds; therefore, any continuous DC or sinusoidal AC periodic waveform with a frequency higher than 1 Hz can be evaluated based on the rms continuous-current level. The continuous-current capability has a strong dependence upon the operating ambient temperature range expected in operation. 图 8-5 shows the maximum continuous current-handling capability of the device on the [TMCS1107EVM](#). Current capability falls off at higher ambient temperatures because of the reduced thermal transfer from junction-to-ambient and increased power dissipation in the leadframe. By improving the thermal design of an application the SOA can be extended to higher currents at elevated temperatures. Using larger and heavier copper power planes, providing air flow over the board, or adding heat sinking structures to the area of the device can all improve thermal performance.



**图 8-5. Maximum Continuous RMS Current vs Ambient Temperature**


### 8.3.2 Repetitive Pulsed Current SOA

For applications where current is pulsed between a high current and no current, the allowable capabilities are limited by short-duration heating in the leadframe. The TMCS1107 can tolerate higher current ranges under some conditions, however, for repetitive pulsed events, the current levels must satisfy both the pulsed current SOA and the rms continuous current constraint. Pulse duration, duty cycle, and ambient temperature all impact the SOA for repetitive pulsed events. 图 8-6, 图 8-7, 图 8-8, and 图 8-9 illustrate repetitive stress levels based on test results from the TMCS1107EVM under which parametric performance and isolation integrity was not impacted post-stress for multiple ambient temperatures. At high duty cycles or long pulse durations, this limit approaches the continuous current SOA for a rms value defined by 方程式 15.


$$I_{IN,RMS} = I_{IN,P} * \sqrt{D} \quad (15)$$

where

- $I_{IN,RMS}$  is the RMS input current level
- $I_{IN,P}$  is the pulse peak input current
- $D$  is the pulse duty cycle



**图 8-6. Maximum Repetitive Pulsed Current vs Pulse Duration**



**图 8-7. Maximum Repetitive Pulsed Current vs Pulse Duration**




图 8-8. Maximum Repetitive Pulsed Current vs Pulse Duration




图 8-9. Maximum Repetitive Pulsed Current vs Pulse Duration

### 8.3.3 Single Event Current Capability

Single higher-current events that are shorter duration can be tolerated by the TMCS1107, because the junction temperature does not reach thermal equilibrium within the pulse duration. 图 8-10 shows the short-circuit duration curve for the device for single current-pulse events, where the leadframe resistance changes after stress. This level is reached before a leadframe fusing event, but should be considered a upper limit for short duration SOA. For long-duration pulses, the current capability approaches the continuous rms limit at the given ambient temperature.





图 8-10. Single-Pulse Leadframe Capability

## 9 Detailed Description

### 9.1 Overview

The TMCS1107 is a precision Hall-effect current sensor, featuring a 420-V basic isolation working voltage, < 3% full-scale error across temperature, and device options providing both unidirectional and bidirectional current sensing. Input current flows through a conductor between the isolated input current pins. The conductor has a 1.8-m $\Omega$  resistance at room temperature for low power dissipation and a 20-A RMS continuous current handling capability up to 105°C ambient temperature on the [TMCS1107EVM](#). The low-ohmic leadframe path reduces power dissipation compared to alternative current measurement methodologies, and does not require any external passive components, isolated supplies, or control signals on the high-voltage side. The magnetic field generated by the input current is sensed by a Hall sensor and amplified by a precision signal chain. The device can be used for both AC and DC current measurements and has a bandwidth of 80 kHz. There are multiple fixed-sensitivity device variants for a wide option of linear sensing ranges, and the TMCS1107 can operate with a low voltage supply from 3 V to 5.5 V. The TMCS1107 is optimized for high accuracy and temperature stability, with both offset and sensitivity compensated across the entire operating temperature range.

### 9.2 Functional Block Diagram



### 9.3 Feature Description

#### 9.3.1 Current Input

Input current to the TMCS1107 passes through the isolated side of the package leadframe through the IN+ and IN- pins. The current flow through the package generates a magnetic field that is proportional to the input current, and measured by a galvanically isolated, precision, Hall sensor IC. As a result of the electrostatic shielding on the Hall sensor die, only the magnetic field generated by the input current is measured, thus limiting input voltage switching pass-through to the circuitry. This configuration allows for direct measurement of currents with high-voltage transients without signal distortion on the current-sensor output. The leadframe conductor has a nominal resistance of 1.8 m $\Omega$  at 25°C, and has a typical positive temperature coefficient as defined in [Electrical Characteristics](#).

#### 9.3.2 Input Isolation

The separation between the input conductor and the Hall sensor die due to the TMCS1107 construction provides inherent galvanic isolation between high-voltage package pins 1-4 and low-voltage package pins 5-8. Insulation capability is defined according to certification agency definitions using industry-standard test methods as defined in the [Insulation Specifications](#) table. Assessment of device lifetime working voltages follow the VDE 0884-11 standard for basic insulation, requiring time-dependent dielectric breakdown (TDDB) data-projection failure rates of less than 1000 part per million (ppm), and a minimum insulation lifetime of 20 years. Based on TDDB data, the intrinsic capability of the isolation barrier to withstand high-voltage stress indicate lifetime of the TMCS1107 is >

100 years at 297 V<sub>RMS</sub>. Other factors such as operating environment and pollution degree can further limit the working voltage of the component in an end system.

### 9.3.3 High-Precision Signal Chain

The TMCS1107 uses a precision, low-drift signal chain with proprietary sensor linearization techniques to provide a highly accurate and stable current measurement across the full temperature range of the device. The device is fully tested and calibrated at the factory to account for any variations in either silicon or packaging process variations. The full signal chain provides a fixed sensitivity voltage output that is proportional to the current through the leadframe of the isolated input.

#### 9.3.3.1 Lifetime and Environmental Stability

The same compensation techniques utilized in the TMCS1107 to reduce temperature drift also greatly reduce lifetime drift due to aging, stress, and environmental conditions. Typical magnetic sensors suffer from up to 2% to 3% of sensitivity drift due to aging at high operating temperatures. The TMCS1107 has greatly improved lifetime drift, as defined in the [Electrical Characteristics](#) table for total sensitivity error measured after the worst-case stress test during a three lot AEC-Q100 qualification. All other stress tests prescribed by an AEC-Q100 qualification caused lower than the specified sensitivity error, and were within the bounds specified within the [Electrical Characteristics](#) table. 图 9-1 shows the total sensitivity error after the worst case stress test, a Highly Accelerated Stress Test (HAST) at 130°C and 85% relative humidity (RH), while 图 9-2 and 图 9-3 show the sensitivity and offset error drift after a 1000 hour, 125°C high temperature operating life stress test as specified by AEC-Q100. This test mimics typical device lifetime operation, and shows the likely device performance variation due to aging is vastly improved compared to typical magnetic sensors.




图 9-1. Sensitivity Error After 130°C, 85% RH HAST




图 9-2. Sensitivity Error Drift After AEC-Q100 High Temperature Operating Life Stress Test






图 9-3. Input-Referred Offset Drift After AEC-Q100 High Temperature Operating Life Stress Test

#### 9.3.3.2 Frequency Response

The TMCS1107 signal chain has a spectral response atypical of a linear analog system due to its discrete time sampling. The 250-kHz sampling interval implies an effective Nyquist frequency of 125 kHz, which limits spectral

response to below this frequency. Higher frequency content than this frequency will be aliased down to lower spectrums.

The TMCS1107 bandwidth is defined by the  $-3\text{-dB}$  spectral response of the entire signal chain which is constrained by the sampling frequency. Normalized gain and phase plots across frequency are shown below in 图 9-4 and 图 9-5, all variants have the same bandwidth and phase response. Signal content beyond the  $-3\text{-dB}$  bandwidth level will still have significant fundamental frequency transmission through the signal chain, but at increasing distortion levels.



### 9.3.3.3 Transient Response

The TMCS1107 signal chain includes a precision analog front end followed by a sampled integrator. At the end of each integration cycle, the signal propagates to the output. Depending on the alignment of a change in input current relative to the sampling window, the output might not settle to the final signal until the second integration cycle. 图 9-6 shows a typical output waveform response to a 10-kHz sine wave input current. For a slowly varying input current signal, the output is a discrete time representation with a phase delay of the integration sampling window. Adding a first order filter of 100 kHz effectively smooths the output waveform with minimal impact to phase response.




图 9-6. Response Behavior to 10-kHz Sine Wave Input Current

图 9-7 shows two transient waveforms to an input-current step event, but occurring at different times during the sampling interval. In both cases, the full transition of the output takes two sampling intervals to reach the final output value. The timing of the current event relative to the sampling window determines the proportional amplitude of the first and second sampling intervals.




图 9-7. Transient Response to Input-Current Step Sufficient for 1-V Output Swing

The output value is effectively an average over the sampling window; therefore, a large-enough current transient can drive the output voltage to near the full scale range in the first sample response. This condition is likely to be true in the case of a short-circuit or fault event. 图 9-8 shows an input-current step twice the full scale measurable range with two output voltage responses illustrating the effect of the sampling window. The relative timing and size of the input current transition determines both the time and amplitude of the first output transition. In either case, the total response time is slightly longer than one integration period.




图 9-8. Transient Response to a Large Input Current Step


### 9.3.4 Internal Reference Voltage

The device has an internal resistor divider from the analog supply  $V_S$  that determines the zero-current output voltage,  $V_{OUT,0A}$ . This zero-current output level, along with sensitivity, determines the measurable input current range of the device and allows for unidirectional or bidirectional sensing as described in [Absolute Maximum Ratings](#). The TMCS1107AxB variants have a zero-current output set by 方程式 16, while the TMCS1107AxU devices have a zero-current output voltage set by 方程式 17.

$$V_{OUT,0A} = V_S \times 0.5 \quad (16)$$

$$V_{OUT,0A} = V_S \times 0.1 \quad (17)$$

These respective reference voltages enable a bidirectional measurable current range for the TMCS1107A2B devices and a unidirectional measurement range for the TMCS1107A2U devices, as shown in 图 9-9.



**图 9-9. Output Voltage Relationship to Input Current for TMCS1107A2B and TMCS1107A2U**

### 9.3.5 Current-Sensing Measurable Ranges

The TMCS1107 measurable input current range depends on the device variant, as well as the analog supply  $V_S$ . The output voltage is limited by  $V_{OUT}$  swing to either supply or ground. The linear output swing range to both  $V_S$  and GND is calculated by [方程式 18](#) and [方程式 19](#).

$$V_{OUT,max} = V_S - \text{Swing}_{VS} \quad (18)$$

$$V_{OUT,min} = \text{Swing}_{GND} \quad (19)$$

Rearranging the transfer function of the device to solve for input current and substituting  $V_{OUT,max}$  and  $V_{OUT,min}$  yields maximum and minimum measurable input current ranges described by [方程式 20](#) and [方程式 21](#).

$$I_{IN,MAX+} = (V_{OUT,max} - V_{OUT,0A}) / S \quad (20)$$

$$I_{IN,MAX-} = (V_{OUT,0A} - V_{OUT,min}) / S \quad (21)$$

where

- $I_{IN,MAX+}$  is the maximum linear measurable positive input current.
- $I_{IN,MAX-}$  is the maximum linear measurable negative input current.
- $S$  is the sensitivity of the device variant.
- $V_{OUT,0A}$  is the appropriate zero current output voltage.

TMCS1107AxB variants accommodate bidirectional current sensing by creating zero-current output voltage equal to half of the supply ( $V_S$ ) potential, while TMCS1107AxU variants provide most of the measurable range for positive currents.

## 9.4 Device Functional Modes

### 9.4.1 Power-Down Behavior

As a result of the inherent galvanic isolation of the device, very little consideration must be paid to powering down the device, as long as the limits in the [Absolute Maximum Ratings](#) table are not exceeded on any pins. The isolated current input and the low-voltage signal chain can be decoupled in operational behavior, as either can be energized with the other shut down, as long as the isolation barrier capabilities are not exceeded. The low-voltage power supply can be powered down while the isolated input is still connected to an active high-voltage signal or system.

## 10 Application and Implementation

### Note

以下应用部分中的信息不属于 TI 器件规格的范围，TI 不担保其准确性和完整性。TI 的客户应负责确定器件是否适用于其应用。客户应验证并测试其设计，以确保系统功能。

### 10.1 Application Information

The key feature sets of the TMCS1107 provide significant advantages in any application where an isolated current measurement is required.

- Galvanic isolation provides a high isolated working voltage and excellent immunity to input voltage transients.
- Hall based measurement simplifies system level solution without the need for a power supply on the high voltage (HV) side.
- An input current path through the low impedance conductor minimizes power dissipation.
- Excellent accuracy and low temperature drift eliminate the need for multipoint calibrations without sacrificing system performance.
- A wide operating supply range enables a single device to function across a wide range of voltage levels.

These advantages increase system-level performance while minimizing complexity for any application where precision current measurements must be made on isolated currents. Specific examples and design requirements are detailed in the following section.

#### 10.1.1 Total Error Calculation Examples

Total error can be calculated for any arbitrary device condition and current level. Error sources considered should include input-referred offset current, power-supply rejection, input common-mode rejection, sensitivity error, nonlinearity, and the error caused by any external fields. Compare each of these error sources in percentage terms, as some are significant drivers of error and some have inconsequential impact to current error. Offset (方程式 22), PSRR (方程式 23), CMRR (方程式 24), and external field error (方程式 25) are all referred to the input, and so, are divided by the actual input current  $I_{IN}$  to calculate percentage errors. For calculations of sensitivity error and nonlinearity error, the percentage limits explicitly specified in the [Electrical Characteristics](#) table can be used.

$$e_{I_{OS}}(\%) = \frac{I_{OS}}{I_{IN}} \quad (22)$$

$$e_{PSRR}(\%) = \left| \frac{\frac{PSRR * (V_S - 5)}{S}}{I_{IN}} \right| \quad (23)$$

$$e_{CMRR}(\%) = \left| \frac{CMRR * V_{CM}}{I_{IN}} \right| \quad (24)$$

$$e_{B_{EXT}}(\%) = \frac{\left| \frac{B_{EXT}}{G} \right|}{I_{IN}} \quad (25)$$

When calculating error contributions across temperature, only the input offset current and sensitivity error contributions vary significantly. For determining offset error over a given temperature range ( $\Delta T$ ), use 方程式 26 to calculate total offset error current. Sensitivity error is specified for both  $-40^{\circ}\text{C}$  to  $85^{\circ}\text{C}$  and  $-40^{\circ}\text{C}$  to  $125^{\circ}\text{C}$ . The appropriate specification should be used based on application operating ambient temperature range.

$$e_{I_{OS},\Delta T}(\%) = \frac{I_{OS,25^{\circ}\text{C}} + I_{OS,\text{drift}}\left(\frac{\mu\text{A}}{^{\circ}\text{C}}\right) \times \Delta T}{I_{IN}} \quad (26)$$

To accurately calculate the total expected error of the device, the contributions from each of the individual components above must be understood in reference to operating conditions. To account for the individual error sources that are statistically uncorrelated, a root sum square (RSS) error calculation should be used to calculate total error. For the TMCS1107, only the input referred offset current ( $I_{OS}$ ), CMRR, and PSRR are statistically correlated. These error terms are lumped in an RSS calculation to reflect this nature, as shown in 方程式 27 for room temperature and 方程式 28 for across a given temperature range. The same methodology can be applied for calculating typical total error by using the appropriate error term specification.

$$e_{RSS}(\%) = \sqrt{(e_{I_{OS}} + e_{PSRR} + e_{CMRR})^2 + e_{B_{EXT}}^2 + e_S^2 + e_{NL}^2} \quad (27)$$

$$e_{RSS,\Delta T}(\%) = \sqrt{(e_{I_{OS},\Delta T} + e_{PSRR} + e_{CMRR})^2 + e_{B_{EXT}}^2 + e_{S,\Delta T}^2 + e_{NL}^2} \quad (28)$$

The total error calculation has a strong dependence on the actual input current; therefore, always calculate total error across the dynamic range that is required. These curves asymptotically approach the sensitivity and nonlinearity error at high current levels, and approach infinity at low current levels due to offset error terms with input current in the denominator. Key figures of merit for any current-measurement system include the total error percentage at full-scale current, as well as the dynamic range of input current over which the error remains below some key level. 图 10-1 illustrates the RSS maximum total error as a function of input current for a TMCS1107A2B at room temperature and across the full temperature range with  $V_S$  of 5 V.




图 10-1. RSS Error vs Input Current

#### 10.1.1.1 Room Temperature Error Calculations

For room-temperature total-error calculations, specifications across temperature and drift are ignored. As an example, consider a TMCS1107A1B with a supply voltage ( $V_S$ ) of 3.3 V and a worst-case common-mode excursion of 420 V to calculate operating-point-specific parameters. Consider a measurement error due to an external magnetic field of 30  $\mu\text{T}$ , roughly the Earth's magnetic field strength. The full-scale current range of the device in specified conditions is slightly greater than 28 A; therefore, calculate error at both 25 A and 12.5 A to highlight error dependence on the input-current level. 表 10-1 shows the individual error components and RSS maximum total error calculations at room temperature under the conditions specified. Relative to other errors, the additional error from CMRR is negligible, and can typically be ignored for total error calculations.

表 10-1. Total Error Calculation: Room Temperature Example

| ERROR COMPONENT      | SYMBOL        | EQUATION                                                                                       | % MAX TOTAL ERROR AT $I_{IN} = 25\text{ A}$ | % MAX TOTAL ERROR AT $I_{IN} = 12.5\text{ A}$ |
|----------------------|---------------|------------------------------------------------------------------------------------------------|---------------------------------------------|-----------------------------------------------|
| Input offset error   | $e_{I_{OS}}$  | $e_{I_{OS}}(\%) = \frac{I_{OS}}{I_{IN}}$                                                       | 0.64%                                       | 1.28%                                         |
| PSRR error           | $e_{PSRR}$    | $e_{PSRR}(\%) = \left  \frac{\frac{PSRR * (V_S - 5)}{S}}{I_{IN}} \right $                      | 0.88%                                       | 1.77%                                         |
| CMRR error           | $e_{CMRR}$    | $e_{CMRR}(\%) = \left  \frac{CMRR * V_{CM}}{I_{IN}} \right $                                   | 0.01%                                       | 0.02%                                         |
| External Field error | $e_{B_{EXT}}$ | $e_{B_{EXT}}(\%) = \frac{\left  \frac{B_{EXT}}{G} \right }{I_{IN}}$                            | 0.11%                                       | 0.22%                                         |
| Sensitivity error    | $e_S$         | Specified in <a href="#">Electrical Characteristics</a>                                        | 1.2%                                        | 1.2%                                          |
| Nonlinearity error   | $e_{NL}$      | Specified in <a href="#">Electrical Characteristics</a>                                        | 0.5%                                        | 0.5%                                          |
| RSS total error      | $e_{RSS}$     | $e_{RSS}(\%) = \sqrt{(e_{I_{OS}} + e_{PSRR} + e_{CMRR})^2 + e_{B_{EXT}}^2 + e_S^2 + e_{NL}^2}$ | 2.01%                                       | 3.34%                                         |

## 10.1.1.2 Full Temperature Range Error Calculations

To calculate total error across any specific temperature range, [方程式 27](#) and [方程式 28](#) should be used for RSS maximum total errors, similar to the example for room temperatures. Conditions from the example in [Room Temperature Error Calculations](#) have been replaced with their respective equations and error components for a -40°C to 85°C temperature range below in [表 10-2](#).

表 10-2. Total Error Calculation: -40°C to 85°C Example

| ERROR COMPONENT      | SYMBOL                 | EQUATION                                                                                                                             | % MAX TOTAL ERROR AT $I_{IN} = 25\text{ A}$ | % MAX TOTAL ERROR AT $I_{IN} = 12.5\text{ A}$ |
|----------------------|------------------------|--------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------|-----------------------------------------------|
| Input offset error   | $e_{I_{OS}, \Delta T}$ | $e_{I_{OS}, \Delta T}(\%) = \frac{I_{OS, 25^\circ C} + I_{OS, drift} \left( \frac{\mu A}{^\circ C} \right) \times \Delta T}{I_{IN}}$ | 0.80%                                       | 1.59%                                         |
| PSRR error           | $e_{PSRR}$             | $e_{PSRR}(\%) = \left  \frac{\frac{PSRR * (V_S - 5)}{S}}{I_{IN}} \right $                                                            | 0.88%                                       | 1.77%                                         |
| CMRR error           | $e_{CMRR}$             | $e_{CMRR}(\%) = \left  \frac{CMRR * V_{CM}}{I_{IN}} \right $                                                                         | 0.01%                                       | 0.02%                                         |
| External Field error | $e_{B_{EXT}}$          | $e_{B_{EXT}}(\%) = \frac{\left  \frac{B_{EXT}}{G} \right }{I_{IN}}$                                                                  | 0.11%                                       | 0.22%                                         |
| Sensitivity error    | $e_{S, \Delta T}$      | Specified in <a href="#">Electrical Characteristics</a>                                                                              | 1.8%                                        | 1.8%                                          |
| Nonlinearity error   | $e_{NL}$               | Specified in <a href="#">Electrical Characteristics</a>                                                                              | 0.5%                                        | 0.5%                                          |
| RSS total error      | $e_{RSS, \Delta T}$    | $e_{RSS, \Delta T}(\%) = \sqrt{(e_{I_{OS}, \Delta T} + e_{PSRR} + e_{CMRR})^2 + e_{B_{EXT}}^2 + e_{S, \Delta T}^2 + e_{NL}^2}$       | 2.51%                                       | 3.84%                                         |

## 10.2 Typical Application

Inline sensing of inductive load currents, such as motor phases, provides significant benefits to the performance of a control systems, allowing advanced control algorithms and diagnostics with minimal postprocessing. A primary challenge to inline sensing is that the current sensor is subjected to full HV supply-level PWM transients driving the load. The inherent isolation of an in-package Hall-effect current sensor topology helps overcome this challenge, providing high common-mode immunity, as well as isolation between the high-voltage motor drive levels and the low-voltage control circuitry. 图 10-2 illustrates the use of the TMCS1107 in such an application, driving the inductive load presented by a three phase motor.




图 10-2. Inline Motor Phase Current Sensing

### 10.2.1 Design Requirements

For current sensing of a three-phase motor application, make sure to provide linear sensing across the expected current range, and make sure that the device remains within working thermal constraints. A single TMCS1107 for each phase can be used, or two phases can be measured, and the third phase calculated on the motor-controller host processor. For this example, consider a nominal supply of 5 V but a minimum of 4.9 V to include for some supply variation. Maximum output swings are defined according to TMCS1107 specifications, and a full-scale current measurement of  $\pm 20$  A is required.

表 10-3. Example Application Design Requirements

| DESIGN PARAMETER | EXAMPLE VALUE |
|------------------|---------------|
| $V_{S,nom}$      | 5 V           |
| $V_{S,min}$      | 4.9 V         |
| $I_{IN,FS}$      | $\pm 20$ A    |

### 10.2.2 Detailed Design Procedure

The primary design parameter for using the TMCS1107 is selecting the correct sensitivity variant, and because positive and negative current must be measured a bidirectional variant should be selected (A1B-A4B). Further consideration of noise and integration with an ADC can be explored, but is beyond the scope of this application design example. The TMCS1107AxB transfer function is effectively a transimpedance with a variable offset set by  $V_{OUT,0A}$ , which is internally set to half of the analog supply as defined by 方程式 29.

$$V_{OUT} = I_{IN} \times S + V_{OUT,0A} = I_{IN} \times S + V_S \times .05 \quad (29)$$

Design of the sensing solution focuses on maximizing the sensitivity of the device while maintaining linear measurement over the expected current input range. The TMCS1107 has a slightly smaller linear output range to

the supply than to ground; therefore, the measurable current range is always constrained by the positive swing to supply,  $\text{Swing}_{VS}$ . To account for the operating margin, consider the minimum possible supply voltage  $V_{S,\min}$ . With the previous parameters, the maximum linear output voltage range is the range between  $V_{OUT,\max}$  and  $V_{OUT,0A}$ , as defined by [方程式 30](#).

$$V_{OUT,\max} - V_{OUT,0A} = V_{S,\min} - \text{Swing}_{VS} - 0.5 \times V_{S,\min} \quad (30)$$

Design parameters for this example application are shown in [表 10-4](#) along with the calculated output range.

**表 10-4. Example Application Design Parameters**

| DESIGN PARAMETER             | EXAMPLE VALUE |
|------------------------------|---------------|
| $\text{Swing}_{VS}$          | 0.2 V         |
| $V_{OUT,\max}$               | 4.7 V         |
| $V_{OUT,0A}$ at $V_{S,\min}$ | 2.45 V        |
| $V_{OUT,\max} - V_{OUT,0A}$  | 2.25 V        |

These design parameters result in a maximum positive linear output voltage swing of 2.25 V. To determine which sensitivity variant of the TMCS1107 most fully uses this linear range, calculate the maximum current range by [方程式 31](#) for a bidirectional current ( $I_{B,\max}$ ).

$$I_{B,\max} = (V_{OUT,\max} - V_{OUT,0A}) / S_{A<x>} \quad (31)$$

where

- $S_{A<x>}$  is the sensitivity of the relevant A1-A4 variant.

[表 10-5](#) shows such calculation for each gain variant of the TMCS1107 with the appropriate sensitivities.


**表 10-5. Maximum Full-Scale Current Ranges With 2.25-V Positive Output Swing**

| SENSITIVITY VARIANT | SENSITIVITY | $I_{B,\max}$ |
|---------------------|-------------|--------------|
| TMCS1107A1B         | 50 mV/A     | ±45 A        |
| TMCS1107A2B         | 100 mV/A    | ±22.5 A      |
| TMCS1107A3B         | 200 mV/A    | ±11.25 A     |
| TMCS1107A4B         | 400 mV/A    | ±5.6 A       |

In general, the highest sensitivity variant that provides for the desired full-scale current range is selected. For the design parameters in this example, the TMCS1107A2B with a sensitivity of 0.1 V/A is the proper selection because the maximum calculated ±22.5-A linear measurable range is sufficient for the desired ±20-A full-scale current.

### 10.2.3 Application Curve

The transfer function of the TMCS1107 linear sensing range for the nominal design parameters is shown in [Figure 10-3](#).



**图 10-3. Application Example Design Transfer Curve**

## 11 Power Supply Recommendations

The TMCS1107 only requires a power supply ( $V_S$ ) on the low-voltage isolated side, which powers the analog circuitry independent of the isolated current input.  $V_S$  determines the full-scale output range of the analog output  $V_{OUT}$ , and can be supplied with any voltage between 3 V and 5.5 V. To filter noise in the power-supply path, place a low-ESR decoupling capacitor of 0.1  $\mu$ F between  $V_S$  and GND pins as close as possible to the supply and ground pins of the device. To compensate for noisy or high-impedance power supplies, add more decoupling capacitance.

The TMCS1107 power supply  $V_S$  can be sequenced independently of current flowing through the input. However, there is a typical 25 ms delay between  $V_S$  reaching the recommended operating voltage and the analog output being valid. Within this delay  $V_{OUT}$  transfers from a high impedance state to the active drive state, during which time the output voltage could transition between GND and  $V_S$ . If this behavior must be avoided, a stable supply voltage to  $V_S$  should be provided for longer than 25 ms prior to applying input current.

## 12 Layout

### 12.1 Layout Guidelines

The TMCS1107 is specified for a continuous current handling capability on the [TMCS1107EVM](#), which uses 3-oz copper pour planes. This current capability is fundamentally limited by the maximum device junction temperature and the thermal environment, primarily the PCB layout and design. To maximize current-handling capability and thermal stability of the device, take care with PCB layout and construction to optimize the thermal capability. Efforts to improve the thermal performance beyond the design and construction of the [TMCS1107EVM](#) can result in increased continuous-current capability due to higher heat transfer to the ambient environment. Keys to improving thermal performance of the PCB include:

- Use large copper planes for both input current path and isolated power planes and signals.
- Use heavier copper PCB construction.
- Place thermal via *farms* around the isolated current input.
- Provide airflow across the surface of the PCB.

The TMCS1107 senses external magnetic fields, so make sure to minimize adjacent high-current traces in close proximity to the device. The input current trace can contribute additional magnetic field to the sensor if the input current traces are routed parallel to the vertical axis of the package. [图 12-1](#) illustrates the most optimal input current routing into the TMCS1107. As the angle that the current approaches the device deviates from 0° to the horizontal axis, the current trace contributes some additional magnetic field to the sensor, increasing the effective sensitivity of the device. If current must be routed parallel to the package vertical axis, move the routing away from the package to minimize the impact to the sensitivity of the device. Terminate the input current path directly underneath the package lead footprint, and use a merged copper input trace for both the IN+ and IN- inputs.




图 12-1. Magnetic Field Generated by Input Current Trace

In addition to thermal and magnetic optimization, make sure to consider the PCB design required creepage and clearance for system-level isolation requirements. Maintain required creepage between solder stencils, as shown in 图 12-2, if possible. If not possible to maintain required PCB creepage between the two isolated sides at board level, add additional slots or grooves to the board. If more creepage and clearance is required for system isolation levels than is provided by the package, the entire device and solder mask can be encapsulated with an overmold compound to meet system-level requirements.




图 12-2. Layout for System Creepage Requirements

## 12.2 Layout Example

An example layout, shown in 图 12-3, is from the [TMCS1107EVM](#). Device performance is targeted for thermal and magnetic characteristics of this layout, which provides optimal current flow from the terminal connectors to the device input pins while large copper planes enhance thermal performance.




图 12-3. Recommended Board Top (Left) and Bottom (Right) Plane Layout

## 13 Device and Documentation Support

### 13.1 Device Support

#### 13.1.1 Development Support

For development tool support see the following:

- [TMCS1107EVM](#)
- [TMCS1107 TI-TINA Model](#)
- [TMCS1107 TINA-TI Reference Design](#)

### 13.2 Documentation Support

#### 13.2.1 Related Documentation

For related documentation see the following:

- Texas Instruments, [TMCS1107EVM users's guide](#)
- Texas Instruments, [Enabling Precision Current Sensing Designs with Nonratiometric Magnetic Current Sensors](#)
- Texas Instruments, [Low-Drift, Precision, In-Line Isolated Magnetic Motor Current Measurements](#)
- Texas Instruments, [Isolation Glossary](#)

### 13.3 接收文档更新通知

要接收文档更新通知，请导航至 [ti.com](http://ti.com) 上的器件产品文件夹。点击 [订阅更新](#) 进行注册，即可每周接收产品信息更改摘要。有关更改的详细信息，请查看任何已修订文档中包含的修订历史记录。

### 13.4 支持资源

**TI E2E™ 支持论坛** 是工程师的重要参考资料，可直接从专家获得快速、经过验证的解答和设计帮助。搜索现有解答或提出自己的问题可获得所需的快速设计帮助。

链接的内容由各个贡献者“按原样”提供。这些内容并不构成 TI 技术规范，并且不一定反映 TI 的观点；请参阅 TI 的《使用条款》。

### 13.5 Trademarks

TI E2E™ is a trademark of Texas Instruments.

所有商标均为其各自所有者的财产。

### 13.6 Electrostatic Discharge Caution



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

### 13.7 术语表

**TI 术语表** 本术语表列出并解释了术语、首字母缩略词和定义。

## 14 Mechanical, Packaging, and Orderable Information


The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.



**D0008B**

**PACKAGE OUTLINE**  
**SOIC - 1.75 mm max height**

SMALL OUTLINE INTEGRATED CIRCUIT




NOTES:

1. Linear dimensions are in inches [millimeters]. Dimensions in parenthesis are for reference only. Controlling dimensions are in inches. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed .006 [0.15], per side.
4. This dimension does not include interlead flash.
5. Reference JEDEC registration MS-012, variation AA.

**EXAMPLE BOARD LAYOUT****D0008B****SOIC - 1.75 mm max height**

SMALL OUTLINE INTEGRATED CIRCUIT



NOTES: (continued)


6. Publication IPC-7351 may have alternate designs.  
7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

**D0008B**

**SOIC - 1.75 mm max height**

SMALL OUTLINE INTEGRATED CIRCUIT



NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

## 重要声明和免责声明

TI 提供技术和可靠性数据 ( 包括数据表 ) 、设计资源 ( 包括参考设计 ) 、应用或其他设计建议、网络工具、安全信息和其他资源，不保证没有瑕疵且不做任何明示或暗示的担保，包括但不限于对适销性、某特定用途方面的适用性或不侵犯任何第三方知识产权的暗示担保。

这些资源可供使用 TI 产品进行设计的熟练开发人员使用。您将自行承担以下全部责任：(1) 针对您的应用选择合适的 TI 产品，(2) 设计、验证并测试您的应用，(3) 确保您的应用满足相应标准以及任何其他安全、安保或其他要求。这些资源如有变更，恕不另行通知。TI 授权您仅可将这些资源用于研发本资源所述的 TI 产品的应用。严禁对这些资源进行其他复制或展示。您无权使用任何其他 TI 知识产权或任何第三方知识产权。您应全额赔偿因在这些资源的使用中对 TI 及其代表造成的任何索赔、损害、成本、损失和债务，TI 对此概不负责。

TI 提供的产品受 TI 的销售条款 (<https://www.ti.com/legal/termsofsale.html>) 或 [ti.com](https://www.ti.com) 上其他适用条款/TI 产品随附的其他适用条款的约束。TI 提供这些资源并不会扩展或以其他方式更改 TI 针对 TI 产品发布的适用的担保或担保免责声明。

邮寄地址：Texas Instruments, Post Office Box 655303, Dallas, Texas 75265

Copyright © 2021，德州仪器 (TI) 公司

## PACKAGING INFORMATION

| Orderable Device | Status<br>(1) | Package Type | Package<br>Drawing | Pins | Package<br>Qty | Eco Plan<br>(2) | Lead finish/<br>Ball material<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5) | Samples                 |
|------------------|---------------|--------------|--------------------|------|----------------|-----------------|--------------------------------------|----------------------|--------------|-------------------------|-------------------------|
| TMCS1107A1BQDR   | ACTIVE        | SOIC         | D                  | 8    | 2500           | RoHS & Green    | SN                                   | Level-2-260C-1 YEAR  | -40 to 85    | M07A1B                  | <a href="#">Samples</a> |
| TMCS1107A1BQDT   | ACTIVE        | SOIC         | D                  | 8    | 250            | RoHS & Green    | SN                                   | Level-2-260C-1 YEAR  | -40 to 85    | M07A1B                  | <a href="#">Samples</a> |
| TMCS1107A1UQDR   | ACTIVE        | SOIC         | D                  | 8    | 2500           | RoHS & Green    | SN                                   | Level-2-260C-1 YEAR  | -40 to 85    | M07A1U                  | <a href="#">Samples</a> |
| TMCS1107A1UQDT   | ACTIVE        | SOIC         | D                  | 8    | 250            | RoHS & Green    | SN                                   | Level-2-260C-1 YEAR  | -40 to 85    | M07A1U                  | <a href="#">Samples</a> |
| TMCS1107A2BQDR   | ACTIVE        | SOIC         | D                  | 8    | 2500           | RoHS & Green    | SN                                   | Level-2-260C-1 YEAR  | -40 to 85    | M07A2B                  | <a href="#">Samples</a> |
| TMCS1107A2BQDT   | ACTIVE        | SOIC         | D                  | 8    | 250            | RoHS & Green    | SN                                   | Level-2-260C-1 YEAR  | -40 to 85    | M07A2B                  | <a href="#">Samples</a> |
| TMCS1107A2UQDR   | ACTIVE        | SOIC         | D                  | 8    | 2500           | RoHS & Green    | SN                                   | Level-2-260C-1 YEAR  | -40 to 85    | M07A2U                  | <a href="#">Samples</a> |
| TMCS1107A2UQDT   | ACTIVE        | SOIC         | D                  | 8    | 250            | RoHS & Green    | SN                                   | Level-2-260C-1 YEAR  | -40 to 85    | M07A2U                  | <a href="#">Samples</a> |
| TMCS1107A3BQDR   | ACTIVE        | SOIC         | D                  | 8    | 2500           | RoHS & Green    | SN                                   | Level-2-260C-1 YEAR  | -40 to 85    | M07A3B                  | <a href="#">Samples</a> |
| TMCS1107A3BQDT   | ACTIVE        | SOIC         | D                  | 8    | 250            | RoHS & Green    | SN                                   | Level-2-260C-1 YEAR  | -40 to 85    | M07A3B                  | <a href="#">Samples</a> |
| TMCS1107A3UQDR   | ACTIVE        | SOIC         | D                  | 8    | 2500           | RoHS & Green    | SN                                   | Level-2-260C-1 YEAR  | -40 to 85    | M07A3U                  | <a href="#">Samples</a> |
| TMCS1107A3UQDT   | ACTIVE        | SOIC         | D                  | 8    | 250            | RoHS & Green    | SN                                   | Level-2-260C-1 YEAR  | -40 to 85    | M07A3U                  | <a href="#">Samples</a> |
| TMCS1107A4BQDR   | ACTIVE        | SOIC         | D                  | 8    | 2500           | RoHS & Green    | SN                                   | Level-2-260C-1 YEAR  | -40 to 85    | M07A4B                  | <a href="#">Samples</a> |
| TMCS1107A4BQDT   | ACTIVE        | SOIC         | D                  | 8    | 250            | RoHS & Green    | SN                                   | Level-2-260C-1 YEAR  | -40 to 85    | M07A4B                  | <a href="#">Samples</a> |
| TMCS1107A4UQDR   | ACTIVE        | SOIC         | D                  | 8    | 2500           | RoHS & Green    | SN                                   | Level-2-260C-1 YEAR  | -40 to 85    | M07A4U                  | <a href="#">Samples</a> |
| TMCS1107A4UQDT   | ACTIVE        | SOIC         | D                  | 8    | 250            | RoHS & Green    | SN                                   | Level-2-260C-1 YEAR  | -40 to 85    | M07A4U                  | <a href="#">Samples</a> |

(1) The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSOLETE:** TI has discontinued the production of the device.

<sup>(2)</sup> **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

**RoHS Exempt:** TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

**Green:** TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of  $\leq 1000$ ppm threshold. Antimony trioxide based flame retardants must also meet the  $\leq 1000$ ppm threshold requirement.

<sup>(3)</sup> MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

<sup>(4)</sup> There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

<sup>(5)</sup> Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

<sup>(6)</sup> Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.


In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**TAPE AND REEL INFORMATION**


\*All dimensions are nominal

| Device         | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|----------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| TMCS1107A1BQDR | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| TMCS1107A1BQDT | SOIC         | D               | 8    | 250  | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| TMCS1107A1UQDR | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| TMCS1107A1UQDT | SOIC         | D               | 8    | 250  | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| TMCS1107A2BQDR | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| TMCS1107A2BQDT | SOIC         | D               | 8    | 250  | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| TMCS1107A2UQDR | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| TMCS1107A2UQDT | SOIC         | D               | 8    | 250  | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| TMCS1107A3BQDR | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| TMCS1107A3BQDT | SOIC         | D               | 8    | 250  | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| TMCS1107A3UQDR | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| TMCS1107A3UQDT | SOIC         | D               | 8    | 250  | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| TMCS1107A4BQDR | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| TMCS1107A4BQDT | SOIC         | D               | 8    | 250  | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| TMCS1107A4UQDR | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| TMCS1107A4UQDT | SOIC         | D               | 8    | 250  | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |

## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal

| Device         | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|----------------|--------------|-----------------|------|------|-------------|------------|-------------|
| TMCS1107A1BQDR | SOIC         | D               | 8    | 2500 | 350.0       | 350.0      | 43.0        |
| TMCS1107A1BQDT | SOIC         | D               | 8    | 250  | 350.0       | 350.0      | 43.0        |
| TMCS1107A1UQDR | SOIC         | D               | 8    | 2500 | 350.0       | 350.0      | 43.0        |
| TMCS1107A1UQDT | SOIC         | D               | 8    | 250  | 350.0       | 350.0      | 43.0        |
| TMCS1107A2BQDR | SOIC         | D               | 8    | 2500 | 350.0       | 350.0      | 43.0        |
| TMCS1107A2BQDT | SOIC         | D               | 8    | 250  | 350.0       | 350.0      | 43.0        |
| TMCS1107A2UQDR | SOIC         | D               | 8    | 2500 | 350.0       | 350.0      | 43.0        |
| TMCS1107A2UQDT | SOIC         | D               | 8    | 250  | 350.0       | 350.0      | 43.0        |
| TMCS1107A3BQDR | SOIC         | D               | 8    | 2500 | 350.0       | 350.0      | 43.0        |
| TMCS1107A3BQDT | SOIC         | D               | 8    | 250  | 350.0       | 350.0      | 43.0        |
| TMCS1107A3UQDR | SOIC         | D               | 8    | 2500 | 350.0       | 350.0      | 43.0        |
| TMCS1107A3UQDT | SOIC         | D               | 8    | 250  | 350.0       | 350.0      | 43.0        |
| TMCS1107A4BQDR | SOIC         | D               | 8    | 2500 | 350.0       | 350.0      | 43.0        |
| TMCS1107A4BQDT | SOIC         | D               | 8    | 250  | 350.0       | 350.0      | 43.0        |
| TMCS1107A4UQDR | SOIC         | D               | 8    | 2500 | 350.0       | 350.0      | 43.0        |
| TMCS1107A4UQDT | SOIC         | D               | 8    | 250  | 350.0       | 350.0      | 43.0        |



## PACKAGE OUTLINE

**SOIC - 1.75 mm max height**

SMALL OUTLINE INTEGRATED CIRCUIT



1. Linear dimensions are in inches [millimeters]. Dimensions in parenthesis are for reference only. Controlling dimensions are in inches. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed .006 [0.15] per side.
4. This dimension does not include interlead flash.
5. Reference JEDEC registration MS-012, variation AA.

# EXAMPLE BOARD LAYOUT


D0008A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE:8X



SOLDER MASK DETAILS

4214825/C 02/2019

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.

7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

D0008A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



SOLDER PASTE EXAMPLE  
BASED ON .005 INCH [0.125 MM] THICK STENCIL  
SCALE:8X

4214825/C 02/2019

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

## 重要声明和免责声明

TI“按原样”提供技术和可靠性数据（包括数据表）、设计资源（包括参考设计）、应用或其他设计建议、网络工具、安全信息和其他资源，不保证没有瑕疵且不做任何明示或暗示的担保，包括但不限于对适销性、某特定用途方面的适用性或不侵犯任何第三方知识产权的暗示担保。

这些资源可供使用 TI 产品进行设计的熟练开发人员使用。您将自行承担以下全部责任：(1) 针对您的应用选择合适的 TI 产品，(2) 设计、验证并测试您的应用，(3) 确保您的应用满足相应标准以及任何其他功能安全、信息安全、监管或其他要求。

这些资源如有变更，恕不另行通知。TI 授权您仅可将这些资源用于研发本资源所述的 TI 产品的应用。严禁对这些资源进行其他复制或展示。您无权使用任何其他 TI 知识产权或任何第三方知识产权。您应全额赔偿因在这些资源的使用中对 TI 及其代表造成的任何索赔、损害、成本、损失和债务，TI 对此概不负责。

TI 提供的产品受 [TI 的销售条款](#) 或 [ti.com](#) 上其他适用条款/TI 产品随附的其他适用条款的约束。TI 提供这些资源并不会扩展或以其他方式更改 TI 针对 TI 产品发布的适用的担保或担保免责声明。

TI 反对并拒绝您可能提出的任何其他或不同的条款。

邮寄地址：Texas Instruments, Post Office Box 655303, Dallas, Texas 75265

Copyright © 2022，德州仪器 (TI) 公司