

## SNx4HC14 具有施密特触发输入的六路反相器

### 1 特性

- 缓冲输入
- 宽工作电压范围：2V 至 6V
- 宽工作温度范围：-40°C 至 +85°C
- 支持多达 10 个 LSTTL 负载的扇出
- 与 LSTTL 逻辑 IC 相比，可显著降低功耗

### 2 应用

- 同步反相时钟输入
- 对开关进行去抖
- 对数字信号进行反相


### 3 说明

此器件包含六个具有施密特触发输入的独立反相器。每个逻辑门以正逻辑执行布尔函数  $Y = \overline{A}$ 。

#### 器件信息<sup>(1)</sup>

| 器件型号        | 封装         | 封装尺寸 (标称值)        |
|-------------|------------|-------------------|
| SN74HC14DR  | SOIC (14)  | 8.70mm × 3.90mm   |
| SN74HC14DBR | SSOP (14)  | 6.40 mm × 5.30 mm |
| SN74HC14NR  | PDIP (14)  | 19.30mm × 6.40mm  |
| SN74HC14NSR | SO (14)    | 10.20mm × 5.30mm  |
| SN74HC14PWR | TSSOP (14) | 5.00mm × 4.40mm   |
| SN54HC14JR  | CDIP (14)  | 21.30mm × 7.60mm  |
| SN54HC14WR  | CFP (14)   | 9.20mm × 6.29mm   |
| SN54HC14FKR | LCCC (20)  | 8.90mm × 8.90mm   |

(1) 如需了解所有可用封装，请参阅数据表末尾的可订购产品附录。



功能引脚分配

## Table of Contents

|                                                  |          |                                                                  |           |
|--------------------------------------------------|----------|------------------------------------------------------------------|-----------|
| <b>1 特性</b> .....                                | <b>1</b> | 8.2 Functional Block Diagram.....                                | <b>9</b>  |
| <b>2 应用</b> .....                                | <b>1</b> | 8.3 Feature Description.....                                     | <b>9</b>  |
| <b>3 说明</b> .....                                | <b>1</b> | 8.4 Device Functional Modes.....                                 | <b>10</b> |
| <b>4 Revision History</b> .....                  | <b>2</b> | <b>9 Application and Implementation</b> .....                    | <b>11</b> |
| <b>5 Pin Configuration and Functions</b> .....   | <b>3</b> | 9.1 Application Information.....                                 | <b>11</b> |
| <b>6 Specifications</b> .....                    | <b>4</b> | 9.2 Typical Application.....                                     | <b>11</b> |
| 6.1 Absolute Maximum Ratings.....                | <b>4</b> | <b>10 Power Supply Recommendations</b> .....                     | <b>13</b> |
| 6.2 ESD Ratings.....                             | <b>4</b> | <b>11 Layout</b> .....                                           | <b>13</b> |
| 6.3 Recommended Operating Conditions.....        | <b>4</b> | 11.1 Layout Guidelines.....                                      | <b>13</b> |
| 6.4 Thermal Information.....                     | <b>4</b> | 11.2 Layout Example.....                                         | <b>13</b> |
| 6.5 Electrical Characteristics - 74.....         | <b>5</b> | <b>12 Device and Documentation Support</b> .....                 | <b>14</b> |
| 6.6 Electrical Characteristics - 54.....         | <b>5</b> | 12.1 Documentation Support.....                                  | <b>14</b> |
| 6.7 Switching Characteristics - 74.....          | <b>6</b> | 12.2 Support Resources.....                                      | <b>14</b> |
| 6.8 Switching Characteristics - 54.....          | <b>7</b> | 12.3 Trademarks.....                                             | <b>14</b> |
| 6.9 Operating Characteristics.....               | <b>7</b> | 12.4 Electrostatic Discharge Caution.....                        | <b>14</b> |
| 6.10 Typical Characteristics.....                | <b>7</b> | 12.5 Glossary.....                                               | <b>14</b> |
| <b>7 Parameter Measurement Information</b> ..... | <b>8</b> | <b>13 Mechanical, Packaging, and Orderable Information</b> ..... | <b>14</b> |
| <b>8 Detailed Description</b> .....              | <b>9</b> |                                                                  |           |
| 8.1 Overview.....                                | <b>9</b> |                                                                  |           |

## 4 Revision History

注：以前版本的页码可能与当前版本的页码不同

|                                                                                                                            |             |
|----------------------------------------------------------------------------------------------------------------------------|-------------|
| <b>Changes from Revision J (October 2016) to Revision K (June 2021)</b> .....                                              | <b>Page</b> |
| • 更新了整个文档中的表格、图和交叉参考的编号格式.....                                                                                             | <b>1</b>    |
| • 更新至全新的数据表标准.....                                                                                                         | <b>1</b>    |
| • 更新了器件信息表中 DB 封装的封装尺寸.....                                                                                                | <b>1</b>    |
| • Increased D (86 to 133.6), DB (96 to 114.8), NS (76 to 122.6), and PW (113 to 151.7); decreased N (80 to 60.7) °C/W..... | <b>4</b>    |
| <b>Changes from Revision I (February 2016) to Revision J (October 2016)</b> .....                                          | <b>Page</b> |
| • 通篇将 “Y = A” 更改为 “Y = $\overline{A}$ ” .....                                                                              | <b>1</b>    |
| • 向说明部分添加了 SNx4HC14.....                                                                                                   | <b>1</b>    |
| • 删除了器件比较表部分.....                                                                                                          | <b>1</b>    |
| • Added <i>Receiving Notification of Documentation Updates</i> section.....                                                | <b>14</b>   |
| <b>Changes from Revision H (September 2015) to Revision I (February 2016)</b> .....                                        | <b>Page</b> |
| • Changed part number from SN54HC08 to SN54HC14 in <i>Switching Characteristics</i> table.....                             | <b>6</b>    |
| • Changed part number from SN54HC08 to SN54HC14 in <i>Switching Characteristics</i> table.....                             | <b>7</b>    |
| <b>Changes from Revision G (January 2014) to Revision H (September 2015)</b> .....                                         | <b>Page</b> |
| • 添加了应用 .....                                                                                                              | <b>1</b>    |
| • 向特性列表中添加了“军用免责声明”。.....                                                                                                  | <b>1</b>    |
| • 添加了引脚配置和功能部分、ESD 等级表、特性说明部分、器件功能模式、应用和实施部分、电源相关建议部分、布局部分、器件和文档支持部分以及机械、封装和可订购信息部分.....                                   | <b>1</b>    |
| <b>Changes from Revision F (December 2010) to Revision G (January 2014)</b> .....                                          | <b>Page</b> |
| • 将文档更新为新的 TI 数据表格式 - 无规格变化.....                                                                                           | <b>1</b>    |

## 5 Pin Configuration and Functions




图 5-1. D, DB, N, NS, PW, J, or W Package 14-Pin SOIC, SSOP, PDIP, SO, TSSOP, CDIP, or CFP Top View




图 5-2. FK Package 20-Pin LCCC Top View

### Pin Functions

| PIN             |                           |                     | I/O    | DESCRIPTION              |
|-----------------|---------------------------|---------------------|--------|--------------------------|
| NAME            | D, DB, N, NS, PW, J, or W | FK                  |        |                          |
| 1A              | 1                         | 2                   | Input  | Channel 1, Input A       |
| 1Y              | 2                         | 3                   | Output | Channel 1, Output Y      |
| 2A              | 3                         | 4                   | Input  | Channel 2, Input A       |
| 2Y              | 4                         | 6                   | Output | Channel 2, Output Y      |
| 3A              | 5                         | 8                   | Input  | Channel 3, Input A       |
| 3Y              | 6                         | 9                   | Output | Channel 3, Output Y      |
| GND             | 7                         | 10                  | —      | Ground                   |
| 4Y              | 8                         | 12                  | Output | Channel 4, Output Y      |
| 4A              | 9                         | 13                  | Input  | Channel 4, Input A       |
| 5Y              | 10                        | 14                  | Output | Channel 5, Output Y      |
| 5A              | 11                        | 16                  | Input  | Channel 5, Input A       |
| 6Y              | 12                        | 18                  | Output | Channel 6, Output Y      |
| 6A              | 13                        | 19                  | Input  | Channel 6, Input A       |
| V <sub>CC</sub> | 14                        | 20                  | —      | Positive Supply          |
| NC              |                           | 1, 5, 7, 11, 15, 17 | —      | Not internally connected |

## 6 Specifications

### 6.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted)<sup>(1)</sup>

|                  |                                                   |                                                        | MIN   | MAX | UNIT |
|------------------|---------------------------------------------------|--------------------------------------------------------|-------|-----|------|
| V <sub>CC</sub>  | Supply voltage                                    |                                                        | – 0.5 | 7   | V    |
| I <sub>IK</sub>  | Input clamp current <sup>(2)</sup>                | V <sub>I</sub> < 0 or V <sub>I</sub> > V <sub>CC</sub> |       | ±20 | mA   |
| I <sub>OK</sub>  | Output clamp current <sup>(2)</sup>               | V <sub>O</sub> < 0                                     |       | ±20 | mA   |
| I <sub>O</sub>   | Continuous output current                         | V <sub>O</sub> = 0 to V <sub>CC</sub>                  |       | ±25 | mA   |
|                  | Continuous current through V <sub>CC</sub> or GND |                                                        |       | ±50 | mA   |
| T <sub>J</sub>   | Junction temperature <sup>(3)</sup>               |                                                        |       | 150 | °C   |
| T <sub>stg</sub> | Storage temperature                               |                                                        | – 60  | 150 | °C   |

(1) Stresses beyond those listed under *Absolute Maximum Rating* may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Condition*. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

(2) The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

(3) Guaranteed by design.

### 6.2 ESD Ratings

|                    |                         |                                                                                | VALUE | UNIT |
|--------------------|-------------------------|--------------------------------------------------------------------------------|-------|------|
| V <sub>(ESD)</sub> | Electrostatic discharge | Human-body model (HBM), per ANSI/ESDA/ JEDEC JS-001 <sup>(1)</sup>             | ±2000 | V    |
|                    |                         | Charged-device model (CDM), per JEDEC specification JESD22-C101 <sup>(2)</sup> | ±1500 |      |

(1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.

(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

### 6.3 Recommended Operating Conditions

over operating free-air temperature range (unless otherwise noted)

|                 |                                |          | MIN  | NOM | MAX             | UNIT |
|-----------------|--------------------------------|----------|------|-----|-----------------|------|
| V <sub>CC</sub> | Supply voltage                 |          | 2    | 5   | 6               | V    |
| V <sub>I</sub>  | Input voltage                  |          | 0    |     | V <sub>CC</sub> | V    |
| V <sub>O</sub>  | Output voltage                 |          | 0    |     | V <sub>CC</sub> | V    |
| T <sub>A</sub>  | Operating free-air temperature | SN54HC04 | – 55 |     | 125             | °C   |
|                 |                                | SN74HC04 | – 40 |     | 85              |      |

### 6.4 Thermal Information

| THERMAL METRIC <sup>(1)</sup> |                                              | SN74HC14 |           |          |         |            | UNIT |
|-------------------------------|----------------------------------------------|----------|-----------|----------|---------|------------|------|
|                               |                                              | D (SOIC) | DB (SSOP) | N (PDIP) | NS (SO) | PW (TSSOP) |      |
|                               |                                              | 14 PINS  | 14 PINS   | 14 PINS  | 14 PINS | 14 PINS    |      |
| R <sub>θJA</sub>              | Junction-to-ambient thermal resistance       | 133.6    | 114.8     | 60.7     | 122.6   | 151.7      | °C/W |
| R <sub>θJC(top)</sub>         | Junction-to-case (top) thermal resistance    | 89       | 64.5      | 47.8     | 81.8    | 79.4       | °C/W |
| R <sub>θJB</sub>              | Junction-to-board thermal resistance         | 89.5     | 65.1      | 40.6     | 83.8    | 94.7       | °C/W |
| Ψ <sub>JT</sub>               | Junction-to-top characterization parameter   | 45.5     | 23.7      | 26.9     | 45.4    | 25.2       | °C/W |
| Ψ <sub>JB</sub>               | Junction-to-board characterization parameter | 89.1     | 64.4      | 40.3     | 83.4    | 94.1       | °C/W |

| THERMAL METRIC <sup>(1)</sup> |                                              | SN74HC14 |           |          |         |            | UNIT |
|-------------------------------|----------------------------------------------|----------|-----------|----------|---------|------------|------|
|                               |                                              | D (SOIC) | DB (SSOP) | N (PDIP) | NS (SO) | PW (TSSOP) |      |
|                               |                                              | 14 PINS  | 14 PINS   | 14 PINS  | 14 PINS | 14 PINS    |      |
| $R_{\theta_{JC(bot)}}$        | Junction-to-case (bottom) thermal resistance | N/A      | N/A       | N/A      | N/A     | N/A        | °C/W |

(1) For more information about traditional and new thermal metrics, see the [Semiconductor and IC Package Thermal Metrics](#) application report.

## 6.5 Electrical Characteristics - 74

over operating free-air temperature range; typical values measured at  $T_A = 25^\circ\text{C}$  (unless otherwise noted).

| PARAMETER        |                                                 | TEST CONDITIONS                                     |                            | V <sub>CC</sub> | Operating free-air temperature (T <sub>A</sub> ) |       |      |               |     |      | UNIT |
|------------------|-------------------------------------------------|-----------------------------------------------------|----------------------------|-----------------|--------------------------------------------------|-------|------|---------------|-----|------|------|
|                  |                                                 |                                                     |                            |                 | 25°C                                             |       |      | -40°C to 85°C |     |      |      |
|                  |                                                 |                                                     |                            |                 | MIN                                              | TYP   | MAX  | MIN           | TYP | MAX  |      |
| V <sub>T+</sub>  | Positive switching threshold                    |                                                     |                            | 2 V             | 0.7                                              | 1.2   | 1.5  | 0.7           |     | 1.5  | V    |
|                  |                                                 |                                                     |                            | 4.5 V           | 1.55                                             | 2.5   | 3.13 | 1.55          |     | 3.13 |      |
|                  |                                                 |                                                     |                            | 6 V             | 2.1                                              | 3.3   | 4.2  | 2.1           |     | 4.2  |      |
| V <sub>T-</sub>  | Negative switching threshold                    |                                                     |                            | 2 V             | 0.3                                              | 0.6   | 1    | 0.3           |     | 1    | V    |
|                  |                                                 |                                                     |                            | 4.5 V           | 0.9                                              | 1.6   | 2.45 | 0.9           |     | 2.45 |      |
|                  |                                                 |                                                     |                            | 6 V             | 1.2                                              | 2     | 3.2  | 1.2           |     | 3.2  |      |
| Δ V <sub>T</sub> | Hysteresis (V <sub>T+</sub> - V <sub>T-</sub> ) |                                                     |                            | 2 V             | 0.2                                              | 0.6   | 1.2  | 0.2           |     | 1.2  | V    |
|                  |                                                 |                                                     |                            | 4.5 V           | 0.4                                              | 0.9   | 2.1  | 0.4           |     | 2.1  |      |
|                  |                                                 |                                                     |                            | 6 V             | 0.5                                              | 1.3   | 2.5  | 0.5           |     | 2.5  |      |
| V <sub>OH</sub>  | High-level output voltage                       | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> | I <sub>OH</sub> = - 20 μA  | 2 V             | 1.9                                              | 1.998 |      | 1.9           |     |      | V    |
|                  |                                                 |                                                     |                            | 4.5 V           | 4.4                                              | 4.499 |      | 4.4           |     |      |      |
|                  |                                                 |                                                     |                            | 6 V             | 5.9                                              | 5.999 |      | 5.9           |     |      |      |
|                  |                                                 |                                                     | I <sub>OH</sub> = - 4 mA   | 4.5 V           | 3.98                                             | 4.3   |      | 3.84          |     |      |      |
|                  |                                                 |                                                     | I <sub>OH</sub> = - 5.2 mA | 6 V             | 5.48                                             | 5.8   |      | 5.34          |     |      |      |
| V <sub>OL</sub>  | Low-level output voltage                        | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> | I <sub>OL</sub> = 20 μA    | 2 V             |                                                  | 0.002 | 0.1  |               |     | 0.1  | V    |
|                  |                                                 |                                                     |                            | 4.5 V           |                                                  | 0.001 | 0.1  |               |     | 0.1  |      |
|                  |                                                 |                                                     |                            | 6 V             |                                                  | 0.001 | 0.1  |               |     | 0.1  |      |
|                  |                                                 |                                                     | I <sub>OL</sub> = 4 mA     | 4.5 V           |                                                  | 0.17  | 0.26 |               |     | 0.33 |      |
|                  |                                                 |                                                     | I <sub>OL</sub> = 5.2 mA   | 6 V             |                                                  | 0.15  | 0.26 |               |     | 0.33 |      |
| I <sub>I</sub>   | Input leakage current                           | V <sub>I</sub> = V <sub>CC</sub> or 0               |                            | 6 V             |                                                  |       | ±0.1 |               |     | ±1   | μA   |
| I <sub>CC</sub>  | Supply current                                  | V <sub>I</sub> = V <sub>CC</sub> or 0               | I <sub>O</sub> = 0         | 6 V             |                                                  |       | 2    |               |     | 20   | μA   |
| C <sub>i</sub>   | Input capacitance                               |                                                     |                            | 5 V             |                                                  | 3     | 10   |               |     | 10   | pF   |

## 6.6 Electrical Characteristics - 54

over operating free-air temperature range; typical values measured at  $T_A = 25^\circ\text{C}$  (unless otherwise noted).

| PARAMETER       |                              | TEST CONDITIONS |  | V <sub>CC</sub> | Operating free-air temperature (T <sub>A</sub> ) |     |      |                |     |      |                 |     |      | UNIT |
|-----------------|------------------------------|-----------------|--|-----------------|--------------------------------------------------|-----|------|----------------|-----|------|-----------------|-----|------|------|
|                 |                              |                 |  |                 | 25°C                                             |     |      | – 40°C to 85°C |     |      | – 55°C to 125°C |     |      |      |
|                 |                              |                 |  |                 | MIN                                              | TYP | MAX  | MIN            | TYP | MAX  | MIN             | TYP | MAX  |      |
| V <sub>T+</sub> | Positive switching threshold |                 |  | 2 V             | 0.7                                              | 1.2 | 1.5  | 0.7            |     | 1.5  | 0.7             |     | 1.5  | V    |
|                 |                              |                 |  | 4.5 V           | 1.55                                             | 2.5 | 3.13 | 1.55           |     | 3.13 | 1.55            |     | 3.13 |      |
|                 |                              |                 |  | 6 V             | 2.1                                              | 3.3 | 4.2  | 2.1            |     | 4.2  | 2.1             |     | 4.2  |      |

over operating free-air temperature range; typical values measured at  $T_A = 25^\circ\text{C}$  (unless otherwise noted).

| PARAMETER        |                                                 | TEST CONDITIONS                                     |                           | V <sub>CC</sub> | Operating free-air temperature (T <sub>A</sub> ) |       |      |                |     |      |                 |     |      | UNIT |
|------------------|-------------------------------------------------|-----------------------------------------------------|---------------------------|-----------------|--------------------------------------------------|-------|------|----------------|-----|------|-----------------|-----|------|------|
|                  |                                                 |                                                     |                           |                 | 25°C                                             |       |      | - 40°C to 85°C |     |      | - 55°C to 125°C |     |      |      |
|                  |                                                 |                                                     |                           |                 | MIN                                              | TYP   | MAX  | MIN            | TYP | MAX  | MIN             | TYP | MAX  |      |
| V <sub>T-</sub>  | Negative switching threshold                    |                                                     |                           | 2 V             | 0.3                                              | 0.6   | 1    | 0.3            |     | 1    | 0.3             |     | 1    | V    |
|                  |                                                 |                                                     |                           | 4.5 V           | 0.9                                              | 1.6   | 2.45 | 0.9            |     | 2.45 | 0.9             |     | 2.45 |      |
|                  |                                                 |                                                     |                           | 6 V             | 1.2                                              | 2     | 3.2  | 1.2            |     | 3.2  | 1.2             |     | 3.2  |      |
| Δ V <sub>T</sub> | Hysteresis (V <sub>T+</sub> - V <sub>T-</sub> ) |                                                     |                           | 2 V             | 0.2                                              | 0.6   | 1.2  | 0.2            |     | 1.2  | 0.2             |     | 1.2  | V    |
|                  |                                                 |                                                     |                           | 4.5 V           | 0.4                                              | 0.9   | 2.1  | 0.4            |     | 2.1  | 0.4             |     | 2.1  |      |
|                  |                                                 |                                                     |                           | 6 V             | 0.5                                              | 1.3   | 2.5  | 0.5            |     | 2.5  | 0.5             |     | 2.5  |      |
| V <sub>OH</sub>  | High-level output voltage                       | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> | I <sub>OH</sub> = - 20 μA | 2 V             | 1.9                                              | 1.998 |      | 1.9            |     |      | 1.9             |     |      | V    |
|                  |                                                 |                                                     |                           | 4.5 V           | 4.4                                              | 4.499 |      | 4.4            |     |      | 4.4             |     |      |      |
|                  |                                                 |                                                     |                           | 6 V             | 5.9                                              | 5.999 |      | 5.9            |     |      | 5.9             |     |      |      |
|                  |                                                 |                                                     | I <sub>OH</sub> = - 4 mA  | 4.5 V           | 3.98                                             | 4.3   |      | 3.84           |     |      | 3.7             |     |      |      |
|                  |                                                 |                                                     |                           | 6 V             | 5.48                                             | 5.8   |      | 5.34           |     |      | 5.2             |     |      |      |
| V <sub>OL</sub>  | Low-level output voltage                        | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> | I <sub>OL</sub> = 20 μA   | 2 V             |                                                  | 0.002 | 0.1  |                |     | 0.1  |                 |     | 0.1  | V    |
|                  |                                                 |                                                     |                           | 4.5 V           |                                                  | 0.001 | 0.1  |                |     | 0.1  |                 |     | 0.1  |      |
|                  |                                                 |                                                     |                           | 6 V             |                                                  | 0.001 | 0.1  |                |     | 0.1  |                 |     | 0.1  |      |
|                  |                                                 |                                                     | I <sub>OL</sub> = 4 mA    | 4.5 V           |                                                  | 0.17  | 0.26 |                |     | 0.33 |                 |     | 0.33 |      |
|                  |                                                 |                                                     |                           | 6 V             |                                                  | 0.15  | 0.26 |                |     | 0.33 |                 |     | 0.33 |      |
| I <sub>I</sub>   | Input leakage current                           | V <sub>I</sub> = V <sub>CC</sub> or 0               |                           | 6 V             |                                                  |       | ±0.1 |                |     | ±1   |                 |     | ±1   | μA   |
| I <sub>CC</sub>  | Supply current                                  | V <sub>I</sub> = V <sub>CC</sub> or 0               | I <sub>O</sub> = 0        | 6 V             |                                                  |       | 2    |                |     | 20   |                 |     | 40   | μA   |
| C <sub>i</sub>   | Input capacitance                               |                                                     |                           | 2 V to 6 V      |                                                  | 3     | 10   |                |     | 10   |                 |     | 10   | pF   |

## 6.7 Switching Characteristics - 74

over operating free-air temperature range (unless otherwise noted)

| PARAMETER       |                   | FROM | TO | V <sub>CC</sub> | Operating free-air temperature (T <sub>A</sub> ) |     |     |                |     |     | UNIT |
|-----------------|-------------------|------|----|-----------------|--------------------------------------------------|-----|-----|----------------|-----|-----|------|
|                 |                   |      |    |                 | 25°C                                             |     |     | – 40°C to 85°C |     |     |      |
|                 |                   |      |    |                 | MIN                                              | TYP | MAX | MIN            | TYP | MAX |      |
| t <sub>pd</sub> | Propagation delay | A    | Y  | 2 V             | 55                                               | 125 | 155 |                |     | ns  |      |
|                 |                   |      |    | 4.5 V           | 12                                               | 25  | 31  |                |     |     |      |
|                 |                   |      |    | 6 V             | 11                                               | 21  | 26  |                |     |     |      |
| t <sub>t</sub>  | Transition-time   |      | Y  | 2 V             | 38                                               | 75  | 95  |                |     | ns  |      |
|                 |                   |      |    | 4.5 V           | 8                                                | 15  | 19  |                |     |     |      |
|                 |                   |      |    | 6 V             | 6                                                | 13  | 16  |                |     |     |      |

## 6.8 Switching Characteristics - 54

over operating free-air temperature range; typical values measured at  $T_A = 25^\circ\text{C}$  (unless otherwise noted).

| PARAMETER       |                   | FROM | TO | V <sub>CC</sub> | Operating free-air temperature (T <sub>A</sub> ) |     |     |                |     |     |                 |     |     | UNIT |
|-----------------|-------------------|------|----|-----------------|--------------------------------------------------|-----|-----|----------------|-----|-----|-----------------|-----|-----|------|
|                 |                   |      |    |                 | 25°C                                             |     |     | – 40°C to 85°C |     |     | – 55°C to 125°C |     |     |      |
|                 |                   |      |    |                 | MIN                                              | TYP | MAX | MIN            | TYP | MAX | MIN             | TYP | MAX |      |
| t <sub>pd</sub> | Propagation delay | A    | Y  | 2 V             | 55                                               | 125 | 155 |                |     | 190 |                 |     | ns  |      |
|                 |                   |      |    | 4.5 V           | 12                                               | 25  | 31  |                |     | 38  |                 |     |     |      |
|                 |                   |      |    | 6 V             | 11                                               | 21  | 26  |                |     | 22  |                 |     |     |      |
| t <sub>t</sub>  | Transition-time   |      | Y  | 2 V             | 38                                               | 75  | 95  |                |     | 110 |                 |     | ns  |      |
|                 |                   |      |    | 4.5 V           | 8                                                | 15  | 19  |                |     | 22  |                 |     |     |      |
|                 |                   |      |    | 6 V             | 6                                                | 13  | 16  |                |     | 19  |                 |     |     |      |

## 6.9 Operating Characteristics

over operating free-air temperature range; typical values measured at  $T_A = 25^\circ\text{C}$  (unless otherwise noted).

| PARAMETER | TEST CONDITIONS                                   | $V_{CC}$   | MIN | TYP | MAX | UNIT |
|-----------|---------------------------------------------------|------------|-----|-----|-----|------|
| $C_{pd}$  | Power dissipation capacitance per gate<br>No load | 2 V to 6 V |     | 20  |     | pF   |

## 6.10 Typical Characteristics

$T_A = 25^\circ\text{C}$




图 6-1. Typical output voltage in the high state ( $V_{OH}$ )





图 6-2. Typical output voltage in the low state ( $V_{OL}$ )

## 7 Parameter Measurement Information

- Phase relationships between waveforms were chosen arbitrarily. All input pulses are supplied by generators having the following characteristics:  $PRR \leq 1 \text{ MHz}$ ,  $Z_O = 50 \Omega$ ,  $t_t < 6 \text{ ns}$ .
- The outputs are measured one at a time, with one input transition per measurement.




## 8 Detailed Description

### 8.1 Overview

This device contains six independent inverters with Schmitt-trigger inputs. Each gate performs the Boolean function  $Y = \bar{A}$  in positive logic.

### 8.2 Functional Block Diagram



### 8.3 Feature Description

#### 8.3.1 Balanced CMOS Push-Pull Outputs

A balanced output allows the device to sink and source similar currents. The drive capability of this device may create fast edges into light loads so routing and load conditions should be considered to prevent ringing. Additionally, the outputs of this device are capable of driving larger currents than the device can sustain without being damaged. It is important for the output power of the device to be limited to avoid damage due to over-current. The electrical and thermal limits defined in the [Absolute Maximum Ratings](#) must be followed at all times.

The SN74HC14 can drive a load with a total capacitance less than or equal to the maximum load listed in the [Switching Characteristics - 74](#) connected to a high-impedance CMOS input while still meeting all of the datasheet specifications. Larger capacitive loads can be applied, however it is not recommended to exceed the provided load value. If larger capacitive loads are required, it is recommended to add a series resistor between the output and the capacitor to limit output current to the values given in the [Absolute Maximum Ratings](#).

#### 8.3.2 CMOS Schmitt-Trigger Inputs

Standard CMOS inputs are high impedance and are typically modeled as a resistor from the input to ground in parallel with the input capacitance given in the [Electrical Characteristics - 74](#). The worst case resistance is calculated with the maximum input voltage, given in the [Absolute Maximum Ratings](#), and the maximum input leakage current, given in the [Electrical Characteristics - 74](#), using ohm's law ( $R = V \div I$ ).

The Schmitt-trigger input architecture provides hysteresis as defined by  $\Delta V_T$  in the [Electrical Characteristics - 74](#), which makes this device extremely tolerant to slow or noisy inputs. While the inputs can be driven much slower than standard CMOS inputs, it is still recommended to properly terminate unused inputs. Driving the inputs slowly will also increase dynamic current consumption of the device. For additional information regarding Schmitt-trigger inputs, please see [Understanding Schmitt Triggers](#).

### 8.3.3 Clamp Diode Structure

The inputs and outputs to this device have both positive and negative clamping diodes as depicted in 图 8-1.

#### CAUTION

Voltages beyond the values specified in the [Absolute Maximum Ratings](#) table can cause damage to the device. The recommended input and output voltage ratings may be exceeded if the input and output clamp-current ratings are observed.




图 8-1. Electrical Placement of Clamping Diodes for Each Input and Output

### 8.4 Device Functional Modes

表 8-1. Function Table

| INPUT | OUTPUT |
|-------|--------|
| A     | Y      |
| L     | H      |
| H     | L      |

## 9 Application and Implementation

### 备注

以下应用部分的信息不属于 TI 组件规范，TI 不担保其准确性和完整性。客户应负责确定 TI 组件是否适用于其应用。客户应验证并测试其设计，以确保系统功能。

### 9.1 Application Information

This device can be used to add an additional stage to a counter with an external flip-flop. Because counters use a negative edge trigger, the flip-flop's clock input must be inverted to provide this function. This function only requires one of the six available inverters in the device, so the remaining channels can be used for other applications needing an inverted signal or improved signal integrity. Unused inputs must be terminated at  $V_{CC}$  or GND. Unused outputs can be left floating.

### 9.2 Typical Application




图 9-1. Typical application schematic

#### 9.2.1 Design Requirements

##### 9.2.1.1 Power Considerations

Ensure the desired supply voltage is within the range specified in the [Recommended Operating Conditions](#). The supply voltage sets the device's electrical characteristics as described in the [Electrical Characteristics - 74](#).

The supply must be capable of sourcing current equal to the total current to be sourced by all outputs of the SN74HC14 plus the maximum supply current,  $I_{CC}$ , listed in the [Electrical Characteristics - 74](#). The logic device can only source or sink as much current as it is provided at the supply and ground pins, respectively. Be sure not to exceed the maximum total current through GND or  $V_{CC}$  listed in the [Absolute Maximum Ratings](#).

Total power consumption can be calculated using the information provided in [CMOS Power Consumption and  \$C\_{pd}\$  Calculation](#).

Thermal increase can be calculated using the information provided in [Thermal Characteristics of Standard Linear and Logic \(SLL\) Packages and Devices](#).

#### CAUTION

The maximum junction temperature,  $T_J(\max)$  listed in the [Absolute Maximum Ratings](#), is an *additional limitation* to prevent damage to the device. Do not violate any values listed in the [Absolute Maximum Ratings](#). These limits are provided to prevent damage to the device.

### 9.2.1.2 Input Considerations

Input signals must cross  $V_{L(min)}$  to be considered a logic LOW, and  $V_{H(max)}$  to be considered a logic HIGH. Do not exceed the maximum input voltage range found in the [Absolute Maximum Ratings](#).

Unused inputs must be terminated to either  $V_{CC}$  or ground. These can be directly terminated if the input is completely unused, or they can be connected with a pull-up or pull-down resistor if the input is to be used sometimes, but not always. A pull-up resistor is used for a default state of HIGH, and a pull-down resistor is used for a default state of LOW. The resistor size is limited by drive current of the controller, leakage current into the SN74HC14, as specified in the [Electrical Characteristics - 74](#), and the desired input transition rate. A 10-k $\Omega$  resistor value is often used due to these factors.

The SN74HC14 has no input signal transition rate requirements because it has Schmitt-trigger inputs.

Another benefit to having Schmitt-trigger inputs is the ability to reject noise. Noise with a large enough amplitude can still cause issues. To know how much noise is too much, please refer to the  $\Delta V_T(min)$  in the [Electrical Characteristics - 74](#). This hysteresis value will provide the peak-to-peak limit.

Unlike what happens with standard CMOS inputs, Schmitt-trigger inputs can be held at any valid value without causing huge increases in power consumption. The typical additional current caused by holding an input at a value other than  $V_{CC}$  or ground is plotted in the [Typical Characteristics](#).

Refer to the [Feature Description](#) for additional information regarding the inputs for this device.

### 9.2.1.3 Output Considerations

The positive supply voltage is used to produce the output HIGH voltage. Drawing current from the output will decrease the output voltage as specified by the  $V_{OH}$  specification in the [Electrical Characteristics - 74](#). Similarly, the ground voltage is used to produce the output LOW voltage. Sinking current into the output will increase the output voltage as specified by the  $V_{OL}$  specification in the [Electrical Characteristics 74](#).

Unused outputs can be left floating. Do not connect outputs directly to  $V_{CC}$  or ground.

Refer to [Feature Description](#) for additional information regarding the outputs for this device.

### 9.2.2 Detailed Design Procedure

1. Add a decoupling capacitor from  $V_{CC}$  to GND. The capacitor needs to be placed physically close to the device and electrically close to both the  $V_{CC}$  and GND pins. An example layout is shown in the [Layout](#).
2. Ensure the capacitive load at the output is  $\leq 70$  pF. This is not a hard limit, however it will ensure optimal performance. This can be accomplished by providing short, appropriately sized traces from the SN74HC14 to the receiving device.
3. Ensure the resistive load at the output is larger than  $(V_{CC} / I_{O(max)}) \Omega$ . This will ensure that the maximum output current from the [Absolute Maximum Ratings](#) is not violated. Most CMOS inputs have a resistive load measured in megaohms; much larger than the minimum calculated above.
4. Thermal issues are rarely a concern for logic gates, however the power consumption and thermal increase can be calculated using the steps provided in the application report, [CMOS Power Consumption and Cpd Calculation](#)

### 9.2.3 Application Curves




图 9-2. Typical application timing diagram

## 10 Power Supply Recommendations


The power supply can be any voltage between the minimum and maximum supply voltage rating located in the [Recommended Operating Conditions](#). Each  $V_{CC}$  terminal should have a bypass capacitor to prevent power disturbance. A 0.1- $\mu$ F capacitor is recommended for this device. It is acceptable to parallel multiple bypass caps to reject different frequencies of noise. The 0.1- $\mu$ F and 1- $\mu$ F capacitors are commonly used in parallel. The bypass capacitor should be installed as close to the power terminal as possible for best results, as shown in [Figure 11-1](#).

## 11 Layout

### 11.1 Layout Guidelines

When using multiple-input and multiple-channel logic devices inputs must not ever be left floating. In many cases, functions or parts of functions of digital logic devices are unused; for example, when only two inputs of a triple-input AND gate are used. Such unused input pins must not be left unconnected because the undefined voltages at the outside connections result in undefined operational states. All unused inputs of digital logic devices must be connected to a logic high or logic low voltage, as defined by the input voltage specifications, to prevent them from floating. The logic level that must be applied to any particular unused input depends on the function of the device. Generally, the inputs are tied to GND or  $V_{CC}$ , whichever makes more sense for the logic function or is more convenient.

### 11.2 Layout Example



**Figure 11-1. Example layout for the SN74HC14**

## 12 Device and Documentation Support

### 12.1 Documentation Support

#### 12.1.1 Related Documentation

For related documentation see the following:

- [HCMOS Design Considerations](#)
- [CMOS Power Consumption and CPD Calculation](#)
- [Designing with Logic](#)

### 12.2 Support Resources

[TI E2E™ support forums](#) are an engineer's go-to source for fast, verified answers and design help — straight from the experts. Search existing answers or ask your own question to get the quick design help you need.

Linked content is provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's [Terms of Use](#).

### 12.3 Trademarks

TI E2E™ is a trademark of Texas Instruments.

所有商标均为其各自所有者的财产。

### 12.4 Electrostatic Discharge Caution



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

### 12.5 Glossary

[TI Glossary](#) This glossary lists and explains terms, acronyms, and definitions.

## 13 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

## PACKAGING INFORMATION

| Orderable Device | Status<br>(1) | Package Type | Package<br>Drawing | Pins | Package<br>Qty | Eco Plan<br>(2)     | Lead finish/<br>Ball material<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5)           | Samples                 |
|------------------|---------------|--------------|--------------------|------|----------------|---------------------|--------------------------------------|----------------------|--------------|-----------------------------------|-------------------------|
| 5962-8409101VCA  | ACTIVE        | CDIP         | J                  | 14   | 1              | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | 5962-8409101VC<br>A<br>SNV54HC14J | <a href="#">Samples</a> |
| 5962-8409101VDA  | ACTIVE        | CFP          | W                  | 14   | 1              | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | 5962-8409101VD<br>A<br>SNV54HC14W | <a href="#">Samples</a> |
| 84091012A        | ACTIVE        | LCCC         | FK                 | 20   | 1              | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | 84091012A<br>SNJ54HC<br>14FK      | <a href="#">Samples</a> |
| 8409101CA        | ACTIVE        | CDIP         | J                  | 14   | 1              | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | 8409101CA<br>SNJ54HC14J           | <a href="#">Samples</a> |
| 8409101DA        | ACTIVE        | CFP          | W                  | 14   | 1              | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | 8409101DA<br>SNJ54HC14W           | <a href="#">Samples</a> |
| JM38510/65702BCA | ACTIVE        | CDIP         | J                  | 14   | 1              | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | JM38510/<br>65702BCA              | <a href="#">Samples</a> |
| JM38510/65702BDA | ACTIVE        | CFP          | W                  | 14   | 1              | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | JM38510/<br>65702BDA              | <a href="#">Samples</a> |
| M38510/65702BCA  | ACTIVE        | CDIP         | J                  | 14   | 1              | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | JM38510/<br>65702BCA              | <a href="#">Samples</a> |
| M38510/65702BDA  | ACTIVE        | CFP          | W                  | 14   | 1              | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | JM38510/<br>65702BDA              | <a href="#">Samples</a> |
| SN54HC14J        | ACTIVE        | CDIP         | J                  | 14   | 1              | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | SN54HC14J                         | <a href="#">Samples</a> |
| SN74HC14D        | ACTIVE        | SOIC         | D                  | 14   | 50             | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC14                              | <a href="#">Samples</a> |
| SN74HC14DBR      | ACTIVE        | SSOP         | DB                 | 14   | 2000           | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC14                              | <a href="#">Samples</a> |
| SN74HC14DE4      | ACTIVE        | SOIC         | D                  | 14   | 50             | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC14                              | <a href="#">Samples</a> |
| SN74HC14DG4      | ACTIVE        | SOIC         | D                  | 14   | 50             | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC14                              | <a href="#">Samples</a> |
| SN74HC14DR       | ACTIVE        | SOIC         | D                  | 14   | 2500           | RoHS & Green        | NIPDAU   SN                          | Level-1-260C-UNLIM   | -40 to 85    | HC14                              | <a href="#">Samples</a> |
| SN74HC14DRG3     | ACTIVE        | SOIC         | D                  | 14   | 2500           | RoHS & Green        | SN                                   | Level-1-260C-UNLIM   | -40 to 85    | HC14                              | <a href="#">Samples</a> |

| Orderable Device | Status<br>(1) | Package Type | Package<br>Drawing | Pins | Package<br>Qty | Eco Plan<br>(2)     | Lead finish/<br>Ball material<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5)      | Samples                 |
|------------------|---------------|--------------|--------------------|------|----------------|---------------------|--------------------------------------|----------------------|--------------|------------------------------|-------------------------|
| SN74HC14DRG4     | ACTIVE        | SOIC         | D                  | 14   | 2500           | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC14                         | <a href="#">Samples</a> |
| SN74HC14DT       | ACTIVE        | SOIC         | D                  | 14   | 250            | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC14                         | <a href="#">Samples</a> |
| SN74HC14DTG4     | ACTIVE        | SOIC         | D                  | 14   | 250            | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC14                         | <a href="#">Samples</a> |
| SN74HC14N        | ACTIVE        | PDIP         | N                  | 14   | 25             | RoHS & Green        | NIPDAU   SN                          | N / A for Pkg Type   | -40 to 85    | SN74HC14N                    | <a href="#">Samples</a> |
| SN74HC14NE4      | ACTIVE        | PDIP         | N                  | 14   | 25             | RoHS & Green        | NIPDAU                               | N / A for Pkg Type   | -40 to 85    | SN74HC14N                    | <a href="#">Samples</a> |
| SN74HC14NSR      | ACTIVE        | SO           | NS                 | 14   | 2000           | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC14                         | <a href="#">Samples</a> |
| SN74HC14NSRE4    | ACTIVE        | SO           | NS                 | 14   | 2000           | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC14                         | <a href="#">Samples</a> |
| SN74HC14PW       | ACTIVE        | TSSOP        | PW                 | 14   | 90             | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC14                         | <a href="#">Samples</a> |
| SN74HC14PWE4     | ACTIVE        | TSSOP        | PW                 | 14   | 90             | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC14                         | <a href="#">Samples</a> |
| SN74HC14PWG4     | ACTIVE        | TSSOP        | PW                 | 14   | 90             | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC14                         | <a href="#">Samples</a> |
| SN74HC14PWR      | ACTIVE        | TSSOP        | PW                 | 14   | 2000           | RoHS & Green        | NIPDAU   SN                          | Level-1-260C-UNLIM   | -40 to 85    | HC14                         | <a href="#">Samples</a> |
| SN74HC14PWRG4    | ACTIVE        | TSSOP        | PW                 | 14   | 2000           | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC14                         | <a href="#">Samples</a> |
| SN74HC14PWT      | ACTIVE        | TSSOP        | PW                 | 14   | 250            | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC14                         | <a href="#">Samples</a> |
| SN74HC14PWTG4    | ACTIVE        | TSSOP        | PW                 | 14   | 250            | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC14                         | <a href="#">Samples</a> |
| SNJ54HC14FK      | ACTIVE        | LCCC         | FK                 | 20   | 1              | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | 84091012A<br>SNJ54HC<br>14FK | <a href="#">Samples</a> |
| SNJ54HC14J       | ACTIVE        | CDIP         | J                  | 14   | 1              | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | 8409101CA<br>SNJ54HC14J      | <a href="#">Samples</a> |
| SNJ54HC14W       | ACTIVE        | CFP          | W                  | 14   | 1              | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | 8409101DA<br>SNJ54HC14W      | <a href="#">Samples</a> |

(1) The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSOLETE:** TI has discontinued the production of the device.

<sup>(2)</sup> **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

**RoHS Exempt:** TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

**Green:** TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of  $\leq 1000$ ppm threshold. Antimony trioxide based flame retardants must also meet the  $\leq 1000$ ppm threshold requirement.

<sup>(3)</sup> MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

<sup>(4)</sup> There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

<sup>(5)</sup> Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

<sup>(6)</sup> Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.


**OTHER QUALIFIED VERSIONS OF SN54HC14, SN54HC14-SP, SN74HC14 :**

- Catalog : [SN74HC14](#), [SN54HC14](#)
- Automotive : [SN74HC14-Q1](#), [SN74HC14-Q1](#)
- Military : [SN54HC14](#)
- Space : [SN54HC14-SP](#)


NOTE: Qualified Version Definitions:

- Catalog - TI's standard catalog product
- Automotive - Q100 devices qualified for high-reliability automotive applications targeting zero defects
- Military - QML certified for Military and Defense Applications
- Space - Radiation tolerant, ceramic packaging and qualified for use in Space-based application

## TAPE AND REEL INFORMATION




### QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



\*All dimensions are nominal


| Device        | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|---------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| SN74HC14DBR   | SSOP         | DB              | 14   | 2000 | 330.0              | 16.4               | 8.35    | 6.6     | 2.4     | 12.0    | 16.0   | Q1            |
| SN74HC14DR    | SOIC         | D               | 14   | 2500 | 330.0              | 16.4               | 6.6     | 9.3     | 2.1     | 8.0     | 16.0   | Q1            |
| SN74HC14DR    | SOIC         | D               | 14   | 2500 | 330.0              | 16.8               | 6.5     | 9.5     | 2.1     | 8.0     | 16.0   | Q1            |
| SN74HC14DR    | SOIC         | D               | 14   | 2500 | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| SN74HC14DR    | SOIC         | D               | 14   | 2500 | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| SN74HC14DRG3  | SOIC         | D               | 14   | 2500 | 330.0              | 16.8               | 6.5     | 9.5     | 2.1     | 8.0     | 16.0   | Q1            |
| SN74HC14DRG3  | SOIC         | D               | 14   | 2500 | 330.0              | 16.4               | 6.6     | 9.3     | 2.1     | 8.0     | 16.0   | Q1            |
| SN74HC14DRG4  | SOIC         | D               | 14   | 2500 | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| SN74HC14DRG4  | SOIC         | D               | 14   | 2500 | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| SN74HC14DT    | SOIC         | D               | 14   | 250  | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| SN74HC14NSR   | SO           | NS              | 14   | 2000 | 330.0              | 16.4               | 8.45    | 10.55   | 2.5     | 12.0    | 16.2   | Q1            |
| SN74HC14PWR   | TSSOP        | PW              | 14   | 2000 | 330.0              | 12.4               | 6.85    | 5.45    | 1.6     | 8.0     | 12.0   | Q1            |
| SN74HC14PWR   | TSSOP        | PW              | 14   | 2000 | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |
| SN74HC14PWR   | TSSOP        | PW              | 14   | 2000 | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |
| SN74HC14PWRG4 | TSSOP        | PW              | 14   | 2000 | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |
| SN74HC14PWT   | TSSOP        | PW              | 14   | 250  | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |

## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal

| Device        | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|---------------|--------------|-----------------|------|------|-------------|------------|-------------|
| SN74HC14DBR   | SSOP         | DB              | 14   | 2000 | 853.0       | 449.0      | 35.0        |
| SN74HC14DR    | SOIC         | D               | 14   | 2500 | 366.0       | 364.0      | 50.0        |
| SN74HC14DR    | SOIC         | D               | 14   | 2500 | 364.0       | 364.0      | 27.0        |
| SN74HC14DR    | SOIC         | D               | 14   | 2500 | 367.0       | 367.0      | 38.0        |
| SN74HC14DR    | SOIC         | D               | 14   | 2500 | 340.5       | 336.1      | 32.0        |
| SN74HC14DRG3  | SOIC         | D               | 14   | 2500 | 364.0       | 364.0      | 27.0        |
| SN74HC14DRG3  | SOIC         | D               | 14   | 2500 | 366.0       | 364.0      | 50.0        |
| SN74HC14DRG4  | SOIC         | D               | 14   | 2500 | 853.0       | 449.0      | 35.0        |
| SN74HC14DRG4  | SOIC         | D               | 14   | 2500 | 340.5       | 336.1      | 32.0        |
| SN74HC14DT    | SOIC         | D               | 14   | 250  | 210.0       | 185.0      | 35.0        |
| SN74HC14NSR   | SO           | NS              | 14   | 2000 | 367.0       | 367.0      | 38.0        |
| SN74HC14PWR   | TSSOP        | PW              | 14   | 2000 | 366.0       | 364.0      | 50.0        |
| SN74HC14PWR   | TSSOP        | PW              | 14   | 2000 | 364.0       | 364.0      | 27.0        |
| SN74HC14PWR   | TSSOP        | PW              | 14   | 2000 | 853.0       | 449.0      | 35.0        |
| SN74HC14PWRG4 | TSSOP        | PW              | 14   | 2000 | 853.0       | 449.0      | 35.0        |
| SN74HC14PWT   | TSSOP        | PW              | 14   | 250  | 853.0       | 449.0      | 35.0        |

**TUBE**



\*All dimensions are nominal

| Device          | Package Name | Package Type | Pins | SPQ | L (mm) | W (mm) | T (μm) | B (mm) |
|-----------------|--------------|--------------|------|-----|--------|--------|--------|--------|
| 5962-8409101VDA | W            | CFP          | 14   | 1   | 506.98 | 26.16  | 6220   | NA     |
| 84091012A       | FK           | LCCC         | 20   | 1   | 506.98 | 12.06  | 2030   | NA     |
| SN74HC14D       | D            | SOIC         | 14   | 50  | 506.6  | 8      | 3940   | 4.32   |
| SN74HC14D       | D            | SOIC         | 14   | 50  | 507    | 8      | 3940   | 4.32   |
| SN74HC14DE4     | D            | SOIC         | 14   | 50  | 507    | 8      | 3940   | 4.32   |
| SN74HC14DE4     | D            | SOIC         | 14   | 50  | 506.6  | 8      | 3940   | 4.32   |
| SN74HC14DG4     | D            | SOIC         | 14   | 50  | 507    | 8      | 3940   | 4.32   |
| SN74HC14DG4     | D            | SOIC         | 14   | 50  | 506.6  | 8      | 3940   | 4.32   |
| SN74HC14N       | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74HC14N       | N            | PDIP         | 14   | 25  | 506.1  | 9      | 600    | 5.4    |
| SN74HC14N       | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74HC14NE4     | N            | PDIP         | 14   | 25  | 506.1  | 9      | 600    | 5.4    |
| SN74HC14NE4     | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74HC14NE4     | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74HC14PW      | PW           | TSSOP        | 14   | 90  | 530    | 10.2   | 3600   | 3.5    |
| SN74HC14PWE4    | PW           | TSSOP        | 14   | 90  | 530    | 10.2   | 3600   | 3.5    |
| SN74HC14PWG4    | PW           | TSSOP        | 14   | 90  | 530    | 10.2   | 3600   | 3.5    |
| SNJ54HC14FK     | FK           | LCCC         | 20   | 1   | 506.98 | 12.06  | 2030   | NA     |



FK (S-CQCC-N\*\*)

LEADLESS CERAMIC CHIP CARRIER

28 TERMINAL SHOWN



| NO. OF<br>TERMINALS<br>** | A                |                  | B                |                  |
|---------------------------|------------------|------------------|------------------|------------------|
|                           | MIN              | MAX              | MIN              | MAX              |
| 20                        | 0.342<br>(8,69)  | 0.358<br>(9,09)  | 0.307<br>(7,80)  | 0.358<br>(9,09)  |
| 28                        | 0.442<br>(11,23) | 0.458<br>(11,63) | 0.406<br>(10,31) | 0.458<br>(11,63) |
| 44                        | 0.640<br>(16,26) | 0.660<br>(16,76) | 0.495<br>(12,58) | 0.560<br>(14,22) |
| 52                        | 0.740<br>(18,78) | 0.761<br>(19,32) | 0.495<br>(12,58) | 0.560<br>(14,22) |
| 68                        | 0.938<br>(23,83) | 0.962<br>(24,43) | 0.850<br>(21,6)  | 0.858<br>(21,8)  |
| 84                        | 1.141<br>(28,99) | 1.165<br>(29,59) | 1.047<br>(26,6)  | 1.063<br>(27,0)  |



4040140/D 01/11


- NOTES:
- All linear dimensions are in inches (millimeters).
  - This drawing is subject to change without notice.
  - This package can be hermetically sealed with a metal lid.
  - Falls within JEDEC MS-004

# MECHANICAL DATA

NS (R-PDSO-G\*\*)

PLASTIC SMALL-OUTLINE PACKAGE

14-PINS SHOWN




| DIM \ PINS ** | 14    | 16    | 20    | 24    |
|---------------|-------|-------|-------|-------|
| A MAX         | 10,50 | 10,50 | 12,90 | 15,30 |
| A MIN         | 9,90  | 9,90  | 12,30 | 14,70 |

4040062/C 03/03

- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Body dimensions do not include mold flash or protrusion, not to exceed 0,15.

W (R-GDFP-F14)

CERAMIC DUAL FLATPACK




**J 14**

## GENERIC PACKAGE VIEW


**CDIP - 5.08 mm max height**

CERAMIC DUAL IN LINE PACKAGE




Images above are just a representation of the package family, actual package may vary.  
Refer to the product data sheet for package details.

4040083-5/G

**J0014A****PACKAGE OUTLINE****CDIP - 5.08 mm max height**

CERAMIC DUAL IN LINE PACKAGE



4214771/A 05/2017


**NOTES:**

1. All controlling linear dimensions are in inches. Dimensions in brackets are in millimeters. Any dimension in brackets or parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This package is hermetically sealed with a ceramic lid using glass frit.
4. Index point is provided on cap for terminal identification only and on press ceramic glass frit seal only.
5. Falls within MIL-STD-1835 and GDIP1-T14.



D (R-PDSO-G14)

PLASTIC SMALL OUTLINE




NOTES:

- A. All linear dimensions are in inches (millimeters).
- B. This drawing is subject to change without notice.
- C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.006 (0,15) each side.
- D. Body width does not include interlead flash. Interlead flash shall not exceed 0.017 (0,43) each side.
- E. Reference JEDEC MS-012 variation AB.

D (R-PDSO-G14)


PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Publication IPC-7351 is recommended for alternate designs.
  - D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
  - E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.


PW (R-PDSO-G14)

PLASTIC SMALL OUTLINE



PW (R-PDSO-G14)

PLASTIC SMALL OUTLINE




- NOTES:
- All linear dimensions are in millimeters.
  - This drawing is subject to change without notice.
  - Publication IPC-7351 is recommended for alternate designs.
  - Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
  - Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.


## N (R-PDIP-T\*\*)

16 PINS SHOWN

## PLASTIC DUAL-IN-LINE PACKAGE



| PINS **             | 14               | 16               | 18               | 20               |
|---------------------|------------------|------------------|------------------|------------------|
| DIM                 |                  |                  |                  |                  |
| A MAX               | 0.775<br>(19,69) | 0.775<br>(19,69) | 0.920<br>(23,37) | 1.060<br>(26,92) |
| A MIN               | 0.745<br>(18,92) | 0.745<br>(18,92) | 0.850<br>(21,59) | 0.940<br>(23,88) |
| MS-001<br>VARIATION | AA               | BB               | AC               | AD               |



14/18 Pin Only  
20 Pin vendor option


4040049/E 12/2002

- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - Falls within JEDEC MS-001, except 18 and 20 pin minimum body length (Dim A).
  - The 20 pin end lead shoulder width is a vendor option, either half or full width.

## DB (R-PDSO-G\*\*)

## PLASTIC SMALL-OUTLINE

28 PINS SHOWN



- NOTES: A. All linear dimensions are in millimeters.  
 B. This drawing is subject to change without notice.  
 C. Body dimensions do not include mold flash or protrusion not to exceed 0,15.  
 D. Falls within JEDEC MO-150

## 重要声明和免责声明

TI“按原样”提供技术和可靠性数据（包括数据表）、设计资源（包括参考设计）、应用或其他设计建议、网络工具、安全信息和其他资源，不保证没有瑕疵且不做任何明示或暗示的担保，包括但不限于对适销性、某特定用途方面的适用性或不侵犯任何第三方知识产权的暗示担保。

这些资源可供使用 TI 产品进行设计的熟练开发人员使用。您将自行承担以下全部责任：(1) 针对您的应用选择合适的 TI 产品，(2) 设计、验证并测试您的应用，(3) 确保您的应用满足相应标准以及任何其他功能安全、信息安全、监管或其他要求。

这些资源如有变更，恕不另行通知。TI 授权您仅可将这些资源用于研发本资源所述的 TI 产品的应用。严禁对这些资源进行其他复制或展示。您无权使用任何其他 TI 知识产权或任何第三方知识产权。您应全额赔偿因在这些资源的使用中对 TI 及其代表造成的任何索赔、损害、成本、损失和债务，TI 对此概不负责。

TI 提供的产品受 [TI 的销售条款](#) 或 [ti.com](#) 上其他适用条款/TI 产品随附的其他适用条款的约束。TI 提供这些资源并不会扩展或以其他方式更改 TI 针对 TI 产品发布的适用的担保或担保免责声明。

TI 反对并拒绝您可能提出的任何其他或不同的条款。

邮寄地址：Texas Instruments, Post Office Box 655303, Dallas, Texas 75265

Copyright © 2022，德州仪器 (TI) 公司